HSR -2025 SUMMARY

MONARAGALA DISTRICT

Ministry of Transport, Highways, Ports and Civil Aviation Sri Lanka

Engineering Division

January 2025

Ministry of Transport, Highways, Ports and Civil Aviation

HSR Summary – 2025

CONTENTS

			<u>P</u>	AGI	<u> </u>
01.	GENERAL NOTE	ES	I	-	IX
02.	BASIC RATES		1	-	8
03.	SECTION – I	(TRANSPORT)	9	-	12
04.	SECTION – II	(ROADWAY/FOUNDATION/TRENCH EXCAVATION)	13	-	14
05.	SECTION – III	(AGGREGATE/RUBBLE PILING)	15	-	16
06.	SECTION – IV	(EARTH FILLING & COMPACTION)	17	-	18
07.	SECTION - V	(RUBBLE PITCHING/PAVING)			19
08.	SECTION - VI	(AGGREGATE SPREADING & ROLLING) (ROAD SURFACE TREATMENT) (ROAD MAINTENANCE) (ROAD SIDE DRAINAGE SYSTEM)	20	-	21
09.	SECTION - VII	(ROAD SURFACE TREATMENT)	22	-	26
10.	SECTION - VIII	(ROAD MAINTENANCE)	27	-	28
11.	SECTION – IX	(ROAD SIDE DRAINAGE SYSTEM)	29	-	30
12.	SECTION – X	(CONCRETE & STRUCTURAL WORK)	31	-	42
13.	SECTION - XI	(ROAD FURNITURE ITEMS)			43
14.	SECTION - XII	(ROAD SIGNS)	44	-	45
15.	SECTION - XIII	(MISCELLANEOUS)	46	-	51
16.	SECTION - XIV	(SURVEYING & DAY WORKS)			52
17.	ANNEX -I	RATES FOR ASPHALT MIXES FROM PLANTS			
18.	ANNEX - II	SPECIFICATIONS RELATED TO HSR ITEMS			
19.	ANNEX - III	ANALYSIS FOR MACHINE EXCAVATION			
20.	ANNEX - IV	TABLE OF TRANSPORT COST PER CU.M/KM			
21.	ANNEX - V	(Ref. General Notes 23.2) RATES FOR TRANSPORT AND PAVING OF INTERLOCKI	NG BLO	OCK	S

Ministry of Transport, Highways, Ports and Civil Aviation

1st January 2025 CONFIDENTIAL

ROAD DEVELOPMENT AUTHORITY – HSR ANALYSIS (METRIC) GENERAL NOTES

1. This **Highway Schedule of Rates (HSR)** becomes operative from **01.01.2025.** HSR has given the maximum rates adoptable in the estimation of projects. In case, the resources are available at lesser rates depending on area and locality, the Engineer shall use such rates in the BOQ for the preparation of Estimates.

- Basic prices of materials used to derive the rates in this schedule are considered without the Value Added Tax (VAT).
- **3.** The rates are not included with overheads and profits component. For the purpose of preparation of <u>Engineer's Estimates</u>, these basic rates should be added with 20% for road works and 20% for bridge works. Provisions should be made separately in the estimate for the payment of **VAT**.
- 4. Work has to be carried out as per (i) Standard Specifications for Construction & Maintenance of Roads and Bridges (S.S.C.M.), issued by the CIDA and (ii) Road Maintenance Manual issued by the RDA.
- **5.** The description of all items in the bills shall briefly conform to that in the relevant items appearing in this schedule so as to avoid any ambiguity. Control of works, control of material and measuring & paying shall be carried out as per S.S.C.M. 104 to 106.6. However, where provision for control of traffic and safety measures for the road users are not included under such items, rate shall be provided separately and paid under the relevant HSR B0-704/B0-705 or on approved S.S.RR or on closely monitored work.
- **6.** The basic labour rates given in this schedule are inclusive of 12% E.P.F., 3% E.T.F., and the special allowances ordered by the Government.
- 7. For works under Force Account, in <u>exceptional cases</u>, Sk'A" labour at higher rates than that given in this schedule may be engaged on <u>adhoc basis</u> with the DG/RDA's prior approval only.
- **8.** For items where cement and/or steel are used, the transport of same is included in the basic price. The rate of Emulsion per liter given in the HSR is exclusive of transport and shall be paid separately.
- **9.** All cement to be used for Concrete, Structural and Masonry/Rendering work shall be of approved quality and shall conform to the specifications required by the Road Development Authority.
- **10.** Materials from approved manufacturers only shall be used in all works (S.S.C.M. 1700). The borrow materials such as soil, aggregate and materials such as Bitumen binder etc. shall be subjected for quality assurance by sample checks during the construction as per S.S.C.M. 1602
- 11. S.S.RR. and day work items shall be approved by the Provincial Director, subject to the following conditions:
 - (a) Any **S.S.R.** where the amount of respective B.O.Q. item does not exceed Rs. **500,000/-,** irrespective of whether the S.S.R. is based on HSR, or not.
 - **(b)** All the **S.S.RR** and day work items, which are based on HSR, irrespective of the amount of B.O.Q. item,or as per directives issued by the Director General/R.D.A. during the year.
- **12.** Concrete mixers should be used for mixing of all reinforced concrete or concrete specified by their Grade and in other concrete mixing exceeding 3 cu.m, unless otherwise directed. Weigh batch mixers shall be used for all concrete specified on Grade 25 and above.
- **13.** In respect of all works involving improvements to existing roads, contractor shall control traffic as per S.S.C.M. 103.

14. Hire Charges

- 1. Hire charges given in this schedule are exclusive of overhead and profit component and taxes.
- 2. Actual work done in a day in machine hours (mhr) has to be paid. The minimum mhr/Day is 4 machine hours and if the actual work done is less than 4 mhr then the cost for 4 mhr is to be paid without the cost of fuel.
- 3. Plant hire charges not included in the HSR could be obtained from RDA schedule of hire charges for Machinery & Equipment given from Director/Mechanical. Otherwise procurement procedure as in General Notes Clause No. 18 should be followed.

HSR-2025: General Notes

4. Hire charges given in this schedule are provided by the Director/ Mechanical, RDA based on the fuel rates prevailed at the time of publication (Rs. 371.00 for Petrol and Rs. 363.00 for Diesel). These Hire charges should be adjusted with the price fluctuations of fuel by referring to the following formula.

Modified Hire Charge = $R[1+(n-n_0)/r]$

Where,

R = Hire charge issued in this HSR

r = Rate of fuel usage in I/km or I/hr

n = New price of fuel issued by the Ceylon Petroleum Corporation

n₀= Price of fuel considered for the hire charge as mentioned in this HSR

- **15.** In the case of building construction works, rates in BSR-2025 prices prepared by the State Organizations on building construction, shall be adopted.
- **16.** S.S.RR. approved with rates/prices applicable for a particular year, may be adopted for subsequent year/s where necessary, provided that only rates/prices are revised as applicable to the relevant year.

17. Materials available/recovered during execution of works:

All suitable earth, rock, steel or precast material and components available or recovered from road way excavations or demolition works shall be utilized in construction work with the approval of the Engineer and surplus disposed as directed. In the case of bridge re-construction works all bridge components such as steel girders, deck plates, and reinforcements etc., which are dismantled, shall be recovered and repaired for re-use. These items should be taken to an inventory by the Engineer and kept in stock under good care for reuse.

Separate items shall be included in the Estimates for reuse of such materials at recovery cost.

18. Procurement:

In cases where the resources have to be procured by tender procedure, the **Tender Committee shall take** decisions to make such awards according to the guide lines given in "Procurement Manual/Procurement Guide Lines 2006 — Goods & Works" and its subsequent amendments, issued by the National Procurement Agency, Sri Lanka.

- a. All tender committees to procure materials for RDA work on works orders shall have a member from RDA authorized by the relevant Director/Provincial Director, and prior concurrence of the relevant Director/Provincial Director shall be obtained for the prices so decided before executing the work.
- **b.** In case where Project Directors/ Provincial Directors procure materials at tender prices different to HSR or approve tender prices different to HSR fixed by other tender boards following government tender procedure as stated in above para, he shall take action to pay the contractor on prices approved by the tender board and amend / revise the relevant rates and the Estimates accordingly.

19. Payments under provisional sums:

"Provisional sum" means a sum included in the bill of quantities for the construction management services, execution of work, supply of goods/materials/ services or contingencies where the work items cannot be quantified accurately. The provisional sum amounts shall be included in the BOQ, by the **Engineer/Provincial Director** as per relevant assumptions on the matter and should be reasonable and justifiable respect to the site conditions and design requirements. This shall be executed in whole or in part or not at all at the direction and discretion of the Resident Engineer/Chief Engineer/Provincial Director. In case the provisional sum provided is not sufficient, funds allocated for contingencies item in the estimate shall be utilized to cover additional cost subject to the approval of the Provincial Director.

All such works, supplies, services or sub-contracts carried out by order of **Resident Engineer/Chief Engineer/Provincial Director** shall be valued at the relevant rates in the approved B.O.Q. or HSR if available. if the B.O.Q. or HSR does not contain any rates, then suitable S.S.RR or day works shall be agreed upon between Resident Engineer/Chief Engineer/Provincial Director and the contractor shall carry out work according to such approved S.S.RR.

20. Royalty/rental for materials mined:

Royalty/rental for approved borrow earth and aggregate materials mined from state land/private land shall be reimbursed **without overheads** to the contractor, on confirmation of the payment of royalty/rental by the Provincial Director of the relevant area where the mining is being executed. Royalty/rental rate shall not be more than the rate approved by the Government Agent/Divisional Secretary of the relevant area. In case the materials cannot be mined from state lands, government procurement procedure shall be followed as given in the General Notes **Clause No.18**.

- **21.** Prior to preparation of the BOQ, suitable borrow pits shall be identified at locations as close as possible for economical transport and to the required quality, by the Resident Engineer/Chief Engineer//Provincial Director and transport distance shall be included accordingly in the BOQ and Estimates.
- 22. a. For any price variations other than works carried out on works orders, use the ICTAD formula guidelines and indices. December 2024 shall be considered as the base month for computation of fluctuations. However for contracts/work below Rs 2.0 million, payment on price variations shall not be considered. Clause 22 b, applies for works carried out on work orders.
 - **b.** If there is a change of ex-factory/manufacture's or ware- house price of different brands of cements, considered in the build-up of **basic price of cement** in the HSR, Director/ Provincial Director shall amend the basic price of cement after verification and pay on approved SSR. Similar procedure to be followed in case of **price changes in reinforcement steel & Bitumen.**

23. Transport

Note:

- 1. The rates for "transport" include all modes of transport up to a maximum distance of the stipulated range.
- 2. The most economical mode of transport shall be always adopted. In transporting materials (soil, sand, aggregate and rubble), if the average output of the transport vehicles cannot be achieved due to unavoidable delays or any other reason justifiable and acceptable to the Chief Engineer/Provincial Director. The rate of payment for transport shall be made under any relevant item selected from codesT1-001 to T1-003b irrespective of the type of vehicles to be used. However in case the quantity involved is more than 200 cu.m. per kilometer run and in situations other than stipulated in para above, the rate of payment for transport shall be selected from item codes T1-006 or T1-007 or T1-007a in the schedule whichever is relevant, For transport of plant made Premix, rate shall be as per item T1-009.
- 3. Transport of aggregate, soil, Emulsion and Premix materials shall always be paid separately unless otherwise directed.
- **4.** Rate for rubble transport up to 3 km may be selected from item codes **T1-002** to **T1-003b** supported with justifiable reasons.

24. Excavation (S.S.C.M. 301 - 303)

Note:

1. a. Manual rates:

The rates given in this schedule if not otherwise stated are intended for manual excavation.

b. Bulk rate:

In the case of borrow earth supply where the estimated quantity <u>exceeds 200 cu. m</u> (for the whole project), the rates given under B0-201, B0-202 or item codes EW1-013 & EW1-014 shall be adopted. Similarly for Roadway Excavations with quantities <u>more than 200 cu.m.</u>, rates given under item codes E1-027, E1-028 and E1-029 shall be adopted. When deviation from above rates is necessary, payment shall be made on approved S.S.RR. Based on actual site records (machine hours) or on work-studies carried out under close supervision by the Engineer, after obtaining approval of the Technical Committee.

- **2.** The rates include for excavation and loading or depositing up to 25 meters. Transport of excavated material more than 25 meters shall always be paid separately unless otherwise directed. In case of foundation excavation for structures, backfilling and compaction to be considered separately unless otherwise specified.
- **3.** Foundation excavation shall be paid at the modified rate applicable to the item to cover up the additional excavation to maintain required slope and working space.

Modification factor for rates applicable to the item = 1+iH/L+iH/W

Where, i = 0.1 for hard clay soil or similar soil, can be cut nearly vertical walls

i = 0.2 for sandy clay (SC)soil or similar soil, can be cut walls with a slope of about 15°

H = Excavation depth of the foundation according to the approved drawing

W = Width of the excavation according to the approved drawing L = Length of the excavation according to the approved drawing

5 11

4. Soils are generally classified as in the Standard Specifications. (S.S.C.M. 301.2)

Cost for additional excavations for shoring shall be considered separately.

- 5. Construction of cofferdams that are necessary shall be paid separately. (S.S.C.M. 302(6)). Rates under items ST1-018, ST1-019 & ST1-020 are not applicable for bridge construction work. For bridge works, it shall be payable on S.S.RR based on closely monitored work-studies or on day works at HSR/machine hours, depending on the site conditions.
- **6.** De-watering necessary for cofferdams shall be paid separately. (S.S.C.M. 302(6)).
- **7.** Rates under items **E1-011 to E1-019** are not applicable for the excavation for **foundations of bridge structures**. Payment for such excavations shall be made on approved S.S.RR based on closely monitored work-studies or on day works at HSR/machine hours, depending on the site conditions.
- **8.** Trench excavation for utility services and reinstatement shall be according to S.S.C.M. 305 and shall be read in conjunction with the procedures to be followed by agencies when trenching highways. Under no circumstances pedestrians and traffic using the road shall be allowed to suffer or inconvenienced due to trenching work, adequate notice have to be given to the public and necessary safety precautions have to be taken in advance.

25. <u>Aggregate/rubble</u> (including loading & piling) Note:

- 1. Except where otherwise stated, the rates include preparing depots, loading and piling.
- 2. The rates for items B0-302 to B0-313 include the cost of blasting materials.
- **3.** In exceptional cases such as limestone, "dug out" aggregate, special rates for items B0-302 to B0-313 shall be approved by the Provincial Director.
- 4. Transport of aggregate and rubble not included in the rates shall be paid separately.
- **5.** Blasting operations shall be carried out as recommended in S.S.C.M. 306 and all works in blasting operations shall conform to the guidelines given in the National Environmental Act No. 47 of 1980 and any subsequent amendments.
- **6.** Prior approval shall be obtained from the Provincial Director for the use of 19 mm hand broken aggregate.

26. Earth filling & compaction (S.S.C.M. 304, 400 & 600) Note:

- 1. Approved soil that is piled shall be spread, watered and well compacted by rolling as per Standard Specifications.
- 2. The rates for earth compaction include the cost of watering.
- **3.** In the case of force account works, where the royalty or similar payments has to be paid for gravel, earth, clay, turf, etc., a claim shall be prepared separately for approval of the Provincial Director, subject to the conditions given under the **Clause 20 of the General Notes.** In case of works awarded on tender rates, the royalty is deemed to be included into the rates.
- **4.** Rates given for the items EW1-003, EW1-004, EW1-005, EW1-006, EW1-007, EW1-008 and EW1-009 on loose volume are for the work where the % density is not specified. If the rates are to be decided on compacted volume basis, the rate for loose volume shall be adjusted by multiplying the specified factor corresponding to the required % density by the factor given in table below.

% Density	Factor
1. For standard density not less than 95 %	1.35
2. For standard density not less than 100 %	1.42

For rates on other densities, S.S.RR. should be approved by the Provincial Director.

- **5.** Transport of water beyond 25 Meters shall be paid separately.
- **6. (i)** The normal output of earth compaction per day will be 66 Cubic Meters using 8-10 ton Road Roller.
 - (ii) For earthworks in widening of existing roads where the average width is less than 1.5 meters, the output of earth compaction using 8-10 ton Roller shall be considered as 50 Cubic Meters per day.
- **7.** Use of small compaction equipment shall be allowed only if the space is restricted for operating 10-ton Road Rollers or equivalent.

27. Rubble paving (rip rap protection - S.S.C.M. 804)

- **1.** P1-001 to P1-004 does not include the cost of rubble, which shall be paid for separately. The coverage rates of paving are as follows:
 - (i) For pitch paving 225 mm thick 0.26 cu.m. of rubble per square Meter.
 - (ii) For pitch paving 150 mm thick 0.17 cu.m. of rubble per square Meter.
 - (iii) For flat paving 225 mm thick 0.21 cu.m. rubble per square Meter.
 - (iv) For flat paving 150 mm thick 0.15 cu.m. rubble for square Meter.
- **2.** Rubble/rip rap paving shall be carried out to avoid damages by watercourses, slips, and slides to road embankments. Action shall be taken to include this item to routine/periodic maintenance flood damage items.

28. Aggregate Compaction (S.S.C.M. 403 - 408)

- 1. The normal coverage areas shall be as follows:
 - (i) For paved roads scarified for full width and for strip metaling 14.5 to 19.7 sq.m. shall be compacted with 1 cu.m. of new 50 mm aggregate.
 - (ii) For construction of new bases and for edge correction 100 sq.m. shall be compacted with 8.5 10.0 cu.m. of new 50 mm aggregate spread in two layers to 100 mm loose thickness.
- **2.** Edge correction shall be 0.6 m (approx.) in width and edge strengthening shall be 1.2 m (approx.) in width, using 100, 50 & 19 mm aggregate conforming to S.S.C.M. 1103.
- 3. Strip metaling shall be considered only when the surface sections to be metaled are in narrow strips less than 1.2 m in width.
- **4.** For construction of new bases, where aggregate compaction of the 19-mm and 50 mm is required 1.0 cu.m. of 19 mm aggregate is adequate for compacting with10 cu.m. of 50 mm.
- **5.** The normal quantities of aggregate that shall be compacted per day are as follows:
 - (i) For full width of paved road including scarifying and/or hand picking the surface will be, 12.75 cu.m. of new aggregate per day.
 - (ii) For construction of new bases, 23.5 cu.m. of new aggregate per day.
 - (iii) For strip or edge correction including loading scarifying and/or handpicking the surface, 9.90 cu.m per day.
- **6.** The average rate of travelling of Oil/Diesel Roller is 20 km per day.
- **7.** The rates for items M1-001, M1-004 & M1-007 to M1-013 include the necessary re-transport of aggregate and no further re-transport costs shall be paid.
- 8. The actual scarified area (which is not necessarily the Bitumen surfaced area) shall be paid for in items M1-002 & M1-003. Normally 0.3 m width (approx.) shall be reckoned as requiring scarifying for edge correction.
- **9.** Tempering and sharpening of scarifier tines are included in the rates for item M1-003 and shall not be paid for separately.

- **10.** The rates for aggregate compaction include the cost of watering.
- 11. Transport of water beyond 25 Meters shall be paid separately.

29. Road surface treatment (S.S.C.M. 501 - 507)

- **1.** The various Grades of Bitumen generally used for road works shall be as stipulated in the standard specifications.
- **2.** The rates for Bitumen in surfacing include cost of Bitumen firewood/fuel and blinding materials. Transport of blinding materials exceeding 16 km shall be paid for separately. One cu.m.of blinding material is allowable for 125 sq.m. of Bitumen surfacing.
- 3. The rates include the cost of internal transport of Bitumen up to 16 km from contractors yard.
- **4.** Approved sand shall be used for blinding.
- 5. The aggregate quantities and binder required per sqr. Meter of D.B.S.T or S.B.S.T work shall be as per the tables 505-1 or 505-3 of the S.S.C.M. depending on the method adopted. The application rates specified shall always be included in the description of the BOQ item for D.B.S.T or S.B.S.T.
- 6. In case of force account works, the Officer in-Charge shall study the average consumption per sq.m. obtained by dividing the actual quantity of Bitumen used, in liters, by the area treated in sq.m. for first/subsequent coat Bitumen surfacing. The Engineer approving the item shall, after satisfying himself that the quantities claimed are reasonable and within the limits specified in the HSR, approve the quantities accounted for. If the quantities are outside the specified limits, the approval of the Provincial Director should be obtained.
- 7. Cost of Binder and cover aggregate for seal coat treatment work shall be paid separately **only if specified**.
- 8. The basic rates for the Asphalt Concrete items B0-361A, B0-362 and B0-362A have been worked out taking 60/70 Penetration grade bitumen as the binder. For item B0-365, it is worked out with Cut-Back of 60/70 penetration grade Bitumen and for item B0-366, it is Bitumen Emulsion CSS-1.% Binder content used for different types of Asphalt Concrete is based on generally accepted mix designs specific to the plant location recommended by the R&D division of the RDA.

Different Bitumen penetration grades and or different binder contents may be specified for the asphalt concrete mixes for special cases. Then approved binder Type and the content as a % shall be included in the description of the item in such variations.

- 9. (i) Densities of Asphalt Premix in compacted state for general estimation purposes shall be as follows.
 - a. Wearing Course 2.450 m.t. per cu.m.
 - b. Binder Course 2.430 m.t. per cu.m.

For actual payments, design densities shall be adopted.

- (ii) Average density of Asphalt Premix in loose state shall be assumed as 1.48 m.ton per cu.m.
- **10.** The quantity of aggregate necessary for the production of 1 metric ton of Asphalt Premix (average for all six types considered in the HSR) by plant shall be taken as **0.6270 cubic meters.**
- **11.** The transport of aggregate for the production of Premix shall be paid separately and shall be decided according to the location of the mixing plant.
- **12.** The transport of Emulsion CSS-1 for the production of cold mix by plant shall be added to the rate per metric ton and shall be decided according to the location of the mixing plant. 59.17 liters of Emulsion CSS-1 are required for each metric ton of cold mix.

30. Road surface maintenance (S.S.C.M. 1100 - 1102)

1. Where method of patching per half a kilometer is adopted, the quantity of Bitumen per half a kilometer per month approved in the routine Maintenance Estimates, may be increased or decreased when necessary. But the rate payable to the contractor for the monthly maintenance of the road surface per half kilometer shall be the rate approved for that half kilometer by the Chief Engineer at the commencement of the Financial Year. The actual rate payable for patching with Bitumen will be according to the appropriate items.

- 2. All roads/sections of roads in the district for which 14, 21, 28, etc. liters per half kilometer per month have been approved shall be listed under groups 1,2, 3, etc., respectively in a schedule of roads, which will be approved by Chief Engineer, and shall become an attachment of the HSR after Section xiv.
- 3. If during the course of the year, there is considerable variation between the estimated quantity of Bitumen per half a kilometer per month and quantity actually used in respect of any road or section of road, the Executive Engineer will examine the reasons therefore and seek the Chief Engineer's approval to amend the rate payable for Bitumen patching of that road or section of road during the same and/or subsequent Financial Year and amend the schedule referred to in **General Note 30 Item 2.**, above.
- **4.** The <u>prior</u> approval of the Chief Engineer should be obtained for extensive patching. Where extensive patching is carried out, no payment should be made for normal patching on the same half kilometer in the same month.

31. Patch sealing:(S.S.C.M. 1104)

Where the road surface shows signs of deficiency of Bitumen and pitted with numerous potholes, patch sealing shall be adopted.

32. Road side and drainage systems (S.S.C.M. 701 - 707, 1302)

- The rates exclude the cost of loading, unloading and transporting but include spreading suitably in the vicinity unless otherwise directed.
- 2. Culvert inlets and outlets should be cleaned before and after the rains.
- **3.** For cleaning choked culverts (item DR1-012) with head room/diameter less than 1 meter, day works rates shall be adopted.
- **4.** Drains should be cleared before commencing any types of surfacing (S.S.C.M. 501 507).

33. <u>Bridges, culverts, retaining walls, etc. (S.S.C.M. 1001 - 1010)</u> Note:

1. Concrete work

- i. The cost of shuttering is not included in the rates, and shall be paid separately.
- ii. The cost of hire charge for concrete mixer is included in the rates for concrete 'using mixers'.
- iii. Construction of necessary cofferdams, shoring, forming islands and de-watering shall be paid separately.
- iv. For all concrete with 19mm aggregate, crusher plant materials shall be used unless otherwise directed.
- 2. Only sand of approved quality shall be used for cement mixes, mortars & concretes.
- **3.** The rates include the cost of transport up to 25 meters on level ground in the relevant items. Any vertical transport required in excess of first 1.5 meters upwards or down wards shall be separately considered.
- **4.** Transport of water beyond 25 meters shall be paid separately.
- **5.** Extra payment for scaffolding/staging where necessary is allowable if not included in the rate.
- **6.** To obtain the nominal mix of cement concrete 1:2:4 (19mm); batching of materials in the field under average conditions will be in the proportions 1:2 $^{1}/_{2}$:4 by volume. Cement concrete 1:3:6 (37.5 mm) and cement concrete 1:4:8 (50mm) may continue to be ba m mm , nm,m, m, tched by volume in the specified nominal proportions; cement should be by bags of 50 kg. and bags shall deem to be 0.035 cu. m. in volume.
- The quantities of the various materials for cement concrete and cement mortars required to yield an average workable mix shall be as follows.

Description	Proportion [nominal mix] or Grade	Yield Unit	Cement in 50 kg	Sand (cu.m)	Aggregate /rubble (cu.m)
1. Cement concrete	g 40(19 mm)	cu.m	9.87*	0.6*	0.91*
2. Cement concrete	g 30(19 mm)	cu.m	8.17*	0.6*	0.90*
3. Cement concrete	g 25(19 mm)	cu.m	6.35*	0.6*	0.90*
4. Cement concrete	g 25(37.5mm+19mm) 70% 30%	cu.m	5.86*	0.6*	37.5=0.54* 19.0=0.24*
5. Cement concrete	g 20(19 mm)	cu.m	6.04*	0.53*	0.79*
6. Cement concrete	1:1 ¹ / ₂ :3(19 mm)	cu.m	8.12	0.60	0.91
7. Cement concrete	1:2:4 (19 mm)	cu.m	5.65	0.60	0.90
8. Cement concrete	1:2:4 (37.5 mm)	cu.m	5.65	0.60	1.00
9. Cement concrete	1:3:6 (19 mm)	cu.m	4.38	0.60	0.91
10. Cement concrete	1:3:6(37.5 mm)	cu.m	4.38	0.60	1.00
11. Cement concrete	1:4:8(50 mm)	cu.m	3.18	0.60	1.00
12. 12.5mm Cement render	1:2 mix	sq.m	0.15#	0.013	-
13. 19.0mm Cement render	1:2 mix	sq.m	0.23#	0.020	-
14. 12.5mm Cement render	1:3 mix	sq.m	0.12#	0.016	-
15. 19.0mm Cement render	1:3 mix 6 10 15	sq.m	0.19#	0.024	-
16. Random Rubble masonry in cement/sand mortar	1:3 mix 1:6 mix 1:6 mix	cu.m	1.77	0.40	1.10

[#] In items 12 - 15 the cement quantity is exclusive of that required for smoothening where necessary.

8. Ready mixed concrete:

Ready mix concrete shall be used only on the written approval of the Director/Provincial Director and for the procurement of the material government tender procedure as given under **General Notes Clause No. 18** to be followed. The contractor for ready mix concrete shall be a copious supplier having minimum of one year experience of supplying ready mix concrete to projects acceptable to the tender board and shall have sufficient transport & pumping facilities, laboratory facilities for quality control and a qualified staff.

9. Wedge stones shall mean stones that are wedged and squared on one face and roughly dressed on the other five faces to enable them to be laid in courses.

10. Wearing surface for R.C.C/P.C.C decking (S.S.C.M. 1403)

Generally for 74.5 sq.m.of **50 mm. thick compacted wearing surface**, the quantities of material required will be 3.5 cu.m. 19 mm to 3.2 mm. Graded aggregate, 2.3 cu.m. sand and 381 liters Bitumen and 91 liters of kerosene. If Emulsion is used, the quantity of material required is 500 liters of Emulsion and 273 liters of water.

11. Concrete pipe culverts (S.S.C.M. 1403)

- ${f i.}$ The diameter of pipes indicated refers to the internal diameter.
- ii. The rates include the cost of pipe, collars, rolling up to a distance of 25 m & lowering to bed up to 1.8 Meter depth, aligning and fixing.

^{*} The above mix proportions for Grade concrete are given for estimation purposes. The actual proportions for Grade concrete shall be decided by mix designs at site and the rates shall be adjusted with the approval of the Provincial Director.

iii. Excavation and backfilling of trench is not included in the rates unless otherwise mentioned.

34. <u>Labour, plant and materials</u>

- 1. All labour, plant, equipment and materials have to be provided by the contractor.
- 2. The Engineer should maintain performance records of all types of machinery for future reference.

35. Day works

- 1. Day works shall be defined and adopted by the Engineer under exceptional circumstances.
- Labour rates fixed under section xiv of the HSR (Surveying, Leveling and Day works) shall be used in pricing day works. In cases of very special labour, such as skin divers etc., procument of same shall be as per General Notes clause 18.
- 3. Rate for materials in day works shall be the purchase price subject to the condition that procurement of same is done as per General Notes Clause No.18.
- **4.** It is necessary that appropriate plant is used and works are programmed to minimize the costs to the satisfaction of the Engineer.

36. Maintenance of road signs and markings: (S.S.C.M. 1501-1502)

All traffic signs, kerbs , parapets, guardrails, barricading and k.m. posts should be painted at least once a year unless otherwise directed by the Engineer.

37. Quality control work: (S.S.C.M. 1600)

- a. The Engineer is responsible for carrying out tests on all works before recommending for payments and maintenance of records. In case of dispute, it may be referred to Provincial Director. /Director (R & D) for a final decision. (S.S.C.M. 1602)
- b. Special attention should be made to control the alignment, thickness and surface regularities of pavement layers as per section 1601 of the S.S.C.M. using geodetic levels, camber boards and 3-Meter straight edges.

38. <u>Piece rates and allowances</u>: ¿

The amounts allowed for the items under "piece rates and allowances" are the anticipated basic costs to cover the expenses to be incurred, during the execution of the work.

39. Labour Inputs

The labour inputs shown against the work items in this schedule do not include the Plant and Equipment Operator costs which are deemed to have been covered under the hire charges of the Plant and Equipment.

40. HSR Analysis is for internal use only. It cannot be produced in Court of Law as reference/authority and thus is a privilege document.

Ministry of Transport, Highways, Ports and Civil Aviation

H.S.R. - SCHEDULE OF INPUTS FOR THE YEAR 2025

MONARAGALA DISTRICT

CODE UNIT PRICE(RS.)

LABOUR RATES (BASIC)

 B0-001
 SKILLED A - (SK 'A') * (Welders, Electricians, Carpenters, Masons, Miners, Painters. Hvy/Mach Operators, Ch.Hand)
 DAY (8 HRS)
 3,750.00

 B0-002
 SKILLED B - (SK 'B')
 DAY (8 HRS)
 3,500.00

 B0-003
 SEMI SKILLED - (S/SK)
 DAY (8 HRS)
 2,750.00

 B0-004
 UNSKILLED - (U/SK)
 DAY (8 HRS)
 2,500.00

HIRE CHARGES (WET LEASE BASIS - INCLUDING OPERATOR UNLESS OTHERWISE SPECIALLY MENTIONED)

B0-101	TAR BOILER(HEATING WITH FIREWOOD)(Less Operator)#	DAY	100.00
B0-102	CONCRETE / ASPHALT MIXER (400 LTRS)	DAY	7,436.16
B0-103	BITUMEN SPRAYER (Less Operator)#	DAY	110.00
B0-104	WATER TANK + 50 MM. PUMP(Less Operator) #	DAY	2,748.36
B0-105	WELDING PLANT ENGIN DRIVEN: WITH WELDER	DAY	14,070.73
B0-106	PORKER VIBRATER (Less Operator)	DAY	1,956.19
B0-107	PLATE COMPACTOR (90 KG)(Less Operator)	DAY	3,629.14
B0-108	VIBRATING RAMMER (60 KG)(Less Operator)	DAY	3,580.83
B0-109	VIBRATING ROLLER (1/2 - 1 Ton)	DAY	8,379.14
B0-110	VIBRATING ROLLER (SMOOTH-10 TONS)	DAY	31,326.43
B0-111	SMOOTH/ROAD ROLLER (8 -10 TONS:STATIC)	DAY	16,832.43
B0-112	PNEUMATIC ROAD ROLLER (8 - 10 TONS)	HOUR	6,415.59
B0-113	MOTOR GRADER (65 HP)	DAY	25,313.40
B0-114	MOTOR GRADER (120 -140 HP)	DAY	38,592.23
B0-115	BACKHOE LOADER (JCB)	DAY	29,168.67
B0-116	WHEEL LOADER (1.4 CU,M)	DAY	29,991.15
B0-116A	WHEEL LOADER (1.7 CU,M)	DAY	31,053.45
B0-117	TRACTOR & TRAILOR (3T)	DAY	9,558.37
B0-118	MATERIAL TRANSPORT BY LORRY/TIPPER/DT (EXCEEDING 10 KM DISTANCES).	KM/CU.M.	38.90
B0-119	-Do- BY LORRY/TIPPER/DT ((FOR MORE THAN 3 KM LESS THAN 10 KM. DISTANCES)	KM/CU.M.	40.34
B0-120	TRANSPORT OF PREMIX BY DUMP TRUCK	KM/M.TONNE	26.77
B0-121	SAND/CHIP SPREADER - PROPELLED	DAY	39,669.12
B0-121A	SAND/CHIP SPREADER - TOWED	DAY	3,036.15
B0-122	FARM TRACTOR & BROOM	DAY	11,077.05
B0-123	EMULSION SPRAYER SELF PROP. (4000 LITRES)	DAY	27,725.32
B0-124	WHEEL LOADER (2.7 - 3.1 CU.M)	DAY	42,259.17
B0-124A	WHEEL LOADER (2.0 - 2.3 CU.M)	DAY	34,240.37
B0-125	LORRY 3 TON(2.5 CU.M) *	KM	105.27
B0-126	LORRY 5 TON(3.5 CU.M) *	KM	124.98
B0-127	LORRY 7 TON(4.5 CU.M) *	KM	147.44
B0-128	WATER BOWSER (6000 LITRES)	DAY	21,633.24
B0-129	ASPHALT PAVER (Crawler)	HOUR	10,016.97
B0-129A	ASPHALT PAVER (Wheel)	HOUR	10,132.68
B0-130	TANKER ONLY(20,000 LITRES)	HOUR	232.52
B0-130A	LOW BED TRAILER 30 TONS *	KM	71.64
B0-131	PRIME MOVER OLD (FOR 20,000 L TANKER)	HOUR	8,531.97
B0-131A	PRIME MOVER NEW (FOR 30 T TRAILER) TIME BASIS	HOUR	8,531.97
B0-131B	PRIME MOVER NEW (FOR 30 TON TRAILER) DISTANCE BASIS *	KM	387.82
B0-132	BABY DUMPER .75 cu.m (less Operator)	HOUR	1,691.80
B0-133	WATER PUMP 4"	HOUR	1,608.04
B0-133A	WATER PUMP 2" (less Operator)	HOUR	643.09
B0-134	SLUDGE PUMP 4"	HOUR	2,243.33
B0-135	VIBRATING ROLLER (6 -7 TONS) TANDEM	HOUR	3,312.67
B0-136	CONCRETE MIXER WITH LOAD CELL WEIGH BATCHER 14/10	DAY	11,675.37
B0-137	TROLLEY EMULSION (less Operator)	HOUR	100.97
B0-138	SPRAYER EMULSION HAND CART	HOUR	1,150,43
B0-139	ROAD MARKER HAND CART GAS HEATER	HOUR	1,628.46
B0-140	BITUMEN DISTRIBUTOR 750 LITRES	HOUR	2,172.30
B0-141	TANK TRUCK BITUMEN 10000 LTR	HOUR	5,618.65
B0-142	CRUSHER STONE 40T/H	HOUR	17,720.75
B0-143	TRACK DRILL CRAWLER	HOUR	2,587.01
B0-144	COMPRESSOR AIR 750 CFM	HOUR	9,286.59
B0-145	SLURRY SEALING MACHINE	HOUR	16,333.36
B0-146	MOBILE CRANE 25 TONS	HOUR	9,747.96
	MOBILE CRANE 30 TONS	HOUR	12,863.55
B0-146A			27,250.95
B0-146A B0-147	IASPHALT PLANT 60T/H HOT MIX	IDUUK	
B0-147	ASPHALT PLANT 60T/H HOT MIX COLD MIX PLANT 30 T/H	HOUR	
B0-147 B0-147A	COLD MIX PLANT 30 T/H	HOUR	16,044.94
B0-147 B0-147A B0-148	COLD MIX PLANT 30 T/H LORRY 10 TON *		
B0-147 B0-147A B0-148 B0-149	COLD MIX PLANT 30 T/H LORRY 10 TON * ITEM DELETED	HOUR KM	16,044.94 189.84
B0-147 B0-147A B0-148	COLD MIX PLANT 30 T/H LORRY 10 TON *	HOUR	16,044.94

^{*} Note: For works under Force Account <u>in exceptional cases</u>, Sk'A' labour at higher rates than above may be engaged **on adhoc basis** with **DG/RDA's prior approval**. See General Notes **Section 6**.

H.S.R. - SCHEDULE OF INPUTS FOR THE YEAR 2025

MONARAGALA DISTRICT

CODE UNIT PRICE(RS.)

HIRE CHARGES (WET LEASE BASIS - INCLUDING OPERATOR UNLESS OTHERWISE SPECIALLY MENTIONED) (Continued)

B0-152	TRACTOR WITH EMULSION BOWSER	HOUR	1,593.40
B0-153	EMULSION TANK TRUCK (8000 LITRES) *	KM	186.99
B0-154	DOZER(CRAWLER TRACTOR) D-4,D-41(80-100 HP)	HOUR	6,435.85
B0-155	EXCAVATOR MOBILE	HOUR	9,743.94
B0-156	AIR COMPRESSOR 250 CFM	HOUR	5,741.98
B0-157	HAND HELD BREAKER / DEMOLISHER) (Less Operator)	DAY	679.05
B0-158	ROCK DRILL HAND HELD (LESS DRILL STEEL)	HOUR	518.54
B0-159	TRUCK SNOOPER 750 KG (SKY LIFT)	HOUR	5,569.88
B0-160	CHAINSAW (less Operator DRY LEASE)	DAY	3,500.00
B0-161	CHAINSAW (less Operator)	DAY	7,000.00
B0-162	ASPHALT CUTTER (with cutting blade)	HOUR	3,750.00

Note: * Cost of return trip not considered under this rate

SUPPLY OF SOIL FROM BORROW PITS INCLUDING LOADING. (FOR QUANTITIES MORE THAN 200 CU.M.)

* SEE GENERAL NOTES FOR FURTHER DETAILS ON USING THIS RATE

Note:	te: If the items from B0-201 to B0-332 are transported outside the district, the rates given for the specific district shall be used					
B0-201	APPROVED SOIL TYPE I & II FOR SUB BASES & SHOULDERS	CU.M	1,148.41			
B0-202	ADDDOVED SOIL TYPE I & II FOR EMRANKMENTS	CLIM	883 30			

AGGREGATE & RUBBLE (EX-QUARRY - BASIC) INCLUDING BLASTING, LOADING & PILING

	(ROYALTY / RENTAL TO BE ADDED SEPARATELY IN THE BOO WITHOUT ADDING OVERHEADS, IF REQUIRED TO BE REIMBURSED.)	70.	
B0-301 B0-302	(150MM - 225MM) RUBBLE - (VEHICLE MEASUREMENT, EXCLUDING PILING) (150MM - 225MM) RUBBLE PILED	CU.M CU.M	2,826.86 3,324.86
	MANUAL PRODUCTION		
B0-303 B0-304 B0-305	(100MM) AGGREGATE (75MM) AGGREGATE (50MM) AGGREGATE	CU.M CU.M CU.M	2,932.86 2,932.86 2,633.33
B0-308A B0-309 B0-310 B0-311 B0-312 B0-313	PLANT PRODUCTION (19MM) AGGREGATE (12.5MM) AGGREGATE (37.5MM) - DO - , (S.S.C.M. TB : 1701-1 / 1701-4) (50MM) - DO - , (S.S.C.M. TB : 1701-4) CRUSHER FINES (6.3MM. DOWN WARDS) (37.5MM) GRADED (TABLE 1701.5 FOR ABC)	CU.M CU.M CU.M CU.M CU.M CU.M	2,800.00 2,400.00 2,666.67 2,633.33 2,066.67 2,500.00
	AGGREGATE FOR SEAL COAT TREATMENTS		
	(GRADING AS PER SSCM TABLE 1701-8)		
DO 214	ACCDECATE 10 MM	CLLM	2 000 00

B0-314	AGGREGATE 19 MM		CU.M	2,800.00
B0-315	AGGREGATE 12.5 MM	, 0	CU.M	2,400.00
B0-316	AGGREGATE 9.5 MM	<i>YO Y</i>	CU.M	2,400.00
		. 6		

SAND (RATE TO INCLUDE TRANSPORT UP TO 16 KM.) (ADDITIONAL TRANSPORT TO BE PAID SEPARATELY)

B0-331	RIVER SAND FOR ROAD SURFACE	CU.M	3,818.49
	APPLICATIONS (SSCM TABLE 1701-9)		
B0-332	RIVER SAND FOR CONCRETE AND	CU.M	3,818.49
	MASONRY WORK (SSCM TABLE 1701-2)		

BRICKS (WITHOUT TRANSPORT)

B0-340 COMMON BURNT CLAY BUILDING BRICKS (SLS 39:1978) 1000 NOS. 16,500.00

^{*} Above rates are generated based on the latest fuel costs (Petrol = Rs. 309.00, Diesel = Rs. 286.00). These rates should be adjusted when the costs of fuel changed. See General Notes for further details.

	MONARAGALA DISTRICT		
CODE		UNIT	PRICE(RS.)
	BITUMEN & EMULSION		
	(TRANSPORT TO BE ADDED SEPARATELY)		
B0-351	BITUMEN 80/100 *[DRUMS] (Purchases>25 drums)	LITRE	154.75
B0-351A	BITUMEN 60/70[DRUMS] (Purchases>25 drums)	LITRE	154.00
B0-352	EMULSION - C.S.S. 1* (EXCLUDING TRANSP.)	LITRE	113.00
B0-353	EMULSION - C.R.S. 1* (EXCLUDING TRANSP.)	LITRE	114.00
B0-354	EMULSION - C.R.S. 2 * (EXCLUDING TRANSP.)	LITRE	115.00
B0-355	BITUMEN 80/100 * [BULK] [with De-cant cost]	KG	156.50
B0-355A B0-355B	BITUMEN 60/70 [BULK][with De-cant cost] BITUMEN 80/100* [BULK]	KG KG	156.00 154.50
B0-355C		KG	154.00
B0-356	CUTBACK BITUMEN- MC-30	LITRE	200.00
B0-357	POLYMER MODIFIED BITUMEN (PG 76-10)	LITRE	255.00
B0-358 B0-359	POLYMER MODIFIED BITUMEN EMULSION DELETED	LITRE	270.00
20 005	PREMIXED BITUMINOUS MATERIALS		
	(PRICE INCLUSIVE OF ALL RAW MATERIAL TRANSPORT AND ROYALTY ON AGGREGATE)		
BI	NDER CONTENT IS TO BE DECIDED ACCORDING TO THE JOB MIX FORMULA OF THE PLANT AND ADDED TO	THE 361B AND 3	62B RATE.
DO 2614	(FOR PROJECT USE)-	MITON	14.612.00
	ASPHALT CONCRETE: SURFACING MATERIAL- BINDER 60/70 BITUMEN @ 4.7% OF MIX ASPHALT CONCRETE: SURFACING MATERIAL- without adding BINDER	M.TON M.TON	14,612.00 6,579.00
B0-361B	ASPHALT/BITUMEN: BOUND BASE MATERIAL- BINDER 60/70 BITUMEN @ 3.4% OF MIX	M.TON	12,491.00
	ASPHALT CONCRETE: BINDER COURSE MATERIAL- BINDER 60/70 BITUMEN @ 4.1% OF MIX	M.TON	13,637.00
	ASPHALT CONCRETE: BINDER COURSE MATERIAL- without adding BINDER	M.TON	6,650.00
	(FOR PROJECTS & MAINTENANCE)-		
B0-365	CUT BACK ASPHALT-AGGREGATE COLD MIX WITH 15% CUT BACK 60/70 @ 5.5% OF MIX (19 mm)	M.TON	16,229.00
	CUT BACK ASPHALT-AGGREGATE COLD MIX WITH 15% CUT BACK 60/70 @ 5.5% OF MIX (12.5 mm)	M.TON	16,235.00
B0-366	EMULSIFIED ASPHALT AGGREGATE COLD MIX WITH EMULTION CSS1 @ 6.67% OF AGGREGATE	M.TON	10,940.00
B0-366A	EMULSIFIED ASPHALT AGGREGATE COLD MIX WITH EMULTION CSS1 $@$ 5.9% OF MIX (12.5 MM 45% AND	M.TON	,
	QUARRY DUST 55% OF AGGREGATE)		10,755.00
	GIVEN IN ANNEX I, RELEVENT TO THE MIXING PLANT CLOSET TO THE SITE, DEPENDING ON THE REQUIRED TYPE AND THE MOST ECONOMICAL RATE WITH TRANSPORT. READY-MIX CONCRETE (EXCLUDING HANDLING COST)	IE AVAILABILIT	Y OF THE
B0-380 B0-381	GRADE 15 / 20 /120mm GRADE 20 / 20 /120mm	CU.M CU.M	24,200.00 25,700.00
B0-382	GRADE 25 / 20 / 120mm	CU.M	27,850.00
B0-383	GRADE 30 / 20 /120mm	CU.M	30,400.00
B0-384 B0-385	GRADE 35 / 20 /120mm GRADE 40 / 20 /120mm	CU.M CU.M	-
		COLIT	
2.	ABOVE RATES ARE CONSIDERED WITHIN 15KM FOR 120MM SLUMP AT SITE NOMINAL AGGREGATE SIZE 20MM IF THE RATES ARE NOT PUBLISHED FOR READY MIX CONCRETE, MINIMUM RATE BY CONSIDER	ING INSITU CO	NCRETE RATE
B0-386	AND QUOTATIONS SHALL BE USED. TRANSPORT OF READY MIX CONCRETE MORE THAN 15 KM RADIUS FROM THE PLANT	CU.M/KM	180.00
B0-387	PLACING OF CONCRETE BY USING PUMP CAR (ALL INCLUSIVE)	CU.M	1,500.00
B0-388	TRANSPORT OF PUMP CAR TO THE SITE	KM	350.00
	TIMBER & FIREWOOD (INCLUDING TRANSPORT COST)		
B0-391	SAWN TIMBER CLASS 1 (LOCAL)	CU.DECI.M	220.55
B0-392	SAWN TIMBER CLASS 2 (LOCAL)	CU.DECI.M	127.55
B0-393	TIMBER ROUND JUNGLE - 100 MM (MINIMUM) TO 150 MM DIAMETER	METRE	128.00
B0-394	TIMBER ROUND JUNGLE - 150 MM (MINIMUM) TO 200 MM DIAMETER	METRE	125.00
B0-395	FIREWOOD NAME OF THE PROPERTY	CU.M	3,010.25
B0-396 B0-397	PLYWOOD(MR) FOR FORMWORK - 15 MM THICK BAMBOO TREE LENGTH GREATER THAN 8 METERS	SQ.M NO.	1,504.75 553.60
	CEMENT (INCLUDING TRANSPORT COST)		
B0-401	PORTLAND CEMENT(FOR ALL WORK)	BAG (50.Kg)	1,562.00
	STEEL AND STEEL ITEMS (INCLUDING TRANSPORT COST)		
BO. 411	·	KG	240.25
B0-411 B0-411A	MILD STEEL TOR STEEL	KG KG	249.25 255.40
B0-411A B0-431	BINDING WIRE	KG	362.65
B0-432	WIRE NAILS, M.S.BOLTS & NUTS	KG	295.50
B0-433	STAINLESS STEEL 20 MM DIA.(FOR DOWELS)	METER	1,416.70
B0-434 B0-435	GI PIPES, 50 MM DIAMETER: HEAVY DUTY TYPE M.S. SHEET, 2 MM THICK	METER SQ.METRE	3,975.50 4,953.45
		SU METRE	4 45 4 45

H.S.R. - SCHEDULE OF INPUTS FOR THE YEAR 2025

MONARAGALA DISTRICT CODE UNIT PRICE(RS.) PRECAST CONCRETE ITEMS **EX - FACTORY: AVERAGE PRICE EXCLUDING VAT REINFORCED CONCRETE PIPES & COLLARS DIAMETER (M.M)** LENGTH (M.M) **PIPES** B0-441 2438 (8') 01 NO. 9,900.00 153 (6") B0-442 229 (9") 2438 (8') 01 NO. 11,100.00 B0-443 305 (12") 2438 (8') 01 NO. 7,750.00 B0-444 450 (1' 6") 2438 (8') 01 NO. 15,000.00 610 (2' 0") B0-445 2438 (8') 01 NO. 24,500.00 B0-446 914 (3' 0") 1219 (4') 01 NO. 21,100.00 B0-446A 914 (3' 0") 2438 (8') 01 NO. 38,500.00 B0-447 1219 (4'0") 1219 (4') 01 NO. 31,400.00 1219 (4' 0") B0-447A 2438 (8') 01 NO. 62,700.00 **COLLARS** B0-441B 01 NO. 153 (6") B0-442B 1,500.00 229 (9") 01 NO. B0-443B 305 (12") 01 NO. 1,900.00 R0-444R 2,250.00 450 (1' 6") 01 NO. B0-445B 2,900.00 610 (2' 0") 01 NO. B0-446B 914 (3' 0") 01 NO. 3,800.00 B0-447B 1219 (4' 0") 01 NO. 4,500.00 B0-448 1,550.00 B0-449 850.00 B0-449A 550.00 B0-450 2,900.00 B0-451 3,700.00 B0-452 3,500.00 B0-453 01 PAIR. 250.00 2,000.00 B0-454 B0-455 90.00 B0-456 3,600.00 B0-457 3,750.00 B0-458 9,250.00 B0-459 4,000.00 B0-460 52.00 B0-461 60.00 B0-501 2,054.30 B0-502 830.90 B0-503 1,041.20 B0-504 513.40 B0-505 DYNA CORD 77.20 Μ. B0-506 WATER GEL KG. 3,722.90 B0-507 AMMONIUM NITRATE KG. 587.30 B0-508 ORDINARY DETONATOR NO. 12.00 B0-509 CRACKING POWDER 130.00 KG. PAINTS (INCLUDING TRANSPORT COST) BITUMINOUS EMULSION PAINT(CRS-2) B0-531 LITRE 115.00 B0-534 984.00 KG B0-537 LIME - BOILED 35.20 KG B0-541 PAINT-ENAMEL LITRE 1.329.45 PAINT - ANTI COROSIVE B0-542 LITRE 1,096.50 B0-543 DELETED B0-544 PAINT - EMULSION LITRE 1,043.00 2,614.41 RUST REMOVER R0-545 LITRE EMULSION FOR EXTERIOR USE (WEATHERSHIELD) B0-546 LITRE 1,188,56 ROAD MARKING PAINTS (YELLOW) ROAD MARKING PAINTS (WHITE) 1,721.40 1.721.40 B0-547 LITRE

B0-548	ROAD MARKING PAINTS (WHITE)	LITRE	1,721.40
	FUEL, OILS & LUBRICANTS		
B0-601 B0-602 B0-611 B0-612 B0-613 B0-614 B0-615 B0-616	INDUSTRIAL KEROSENE OIL (COLOMBO) MOULD OIL LUBRICANT(OIL) AUTO DIESEL (COLOMBO) PETROL (COLOMBO) FURNACE OIL FOR BURNERS LP GAS LUBRICANT(GREASE))	LITRE LITRE LITRE LITRE LITRE LITRE LITRE KG KG	191.00 120.00 1,541.54 286.00 309.00 132.00 266.05 2,562.18

CODE		UNIT	PRICE(RS.)					
	MISCELLANEOUS MATERIALS							
B0-637B B0-637C	BASKETS (WITH TRANSPORT) GUNNY BAGS NEW(LARGE) (WITH TRANSPORT) POLY SACS (65 KG CAPACITY) (WITH TRANSPORT) COTTON WASTE (WITH TRANSPORT) SALT (WITH TRANSPORT) EMPTY TAR BARRELS (140 LTRS) WITH TRANSPORT) P.V.C. PIPE 110 MM DIA TYPE 250 PE (WITH TRANS.) P.V.C. PIPE 110 MM DIA TYPE 400 PE (WITH TRANS.) PVC PIPE 110 MM DIA TYPE 600 PE (WITH TRANSPORT) PVC PIPE 110 MM DIA TYPE 1000 PE (WITH TRANSPORT) PVC PIPE 110 MM DIA TYPE 1000 PE (WITH TRANSPORT) PVC PIPE 110 MM DIA TYPE 1000 PE (WITH TRANSPORT) P.V.C. PIPE 50 MM DIA TYPE 400 PE (WITH TRANS.) P.V.C. PIPE 90 MM DIA TYPE 400 PE (WITH TRANS.) P.V.C. PIPE 90 MM DIA TYPE 600 PE (WITH TRANS.) P.V.C. PIPE 90 MM DIA TYPE 500 PE (WITH TRANS.) P.V.C. PIPE 160 MM DIA TYPE 250 PE (WITH TRANS.)	01 NO. 01 NO. 01 NO. KG KG NO METRE METRE METER METER MOS METRE	300.00 85.80 60.20 112.75 75.00 90.55 1,058.20 1,606.80 1,886.45 2,839.85 4,843.80 328.55 282.50 961.35 1,568.65					
B0-637E B0-637F	P.V.C. PIPE 160 MM DIA TYPE 400 PE (WITH TRANS.) P.V.C. PIPE 160 MM DIA TYPE 400 PE (WITH TRANS.) P.V.C. PIPE 160 MM DIA TYPE 600 PE (WITH TRANS.) P.V.C. PIPE 160 MM DIA TYPE 1000 PE (WITH TRANS.) HARD RUBBER 12MM THICK X 75 MM WIDE (WITH TRANS) POLYTHENE 325 MM DIA GAUGE 300 (APPROX.14.0 METERS/KG) (TUBULAR FLAT WIDTH APP. 505 MM, WITH TRANS.)	METRE METRE METRE METRE KG	3,111.05 3,856.80 5,926.00 2,694.73 615.00					
B0-639A	POLYTHENE 230 MM DIA GAUGE 300 (APPROX.19.5 METERS/KG) (TUBULAR FLAT WIDTH APP. 355 MM, WITH TRANS.)	KG	615.00					
B0-649 B0-641 B0-642 B0-643 B0-644 B0-645 B0-646 B0-647 B0-648 B0-649	CTUBULAR FLAT WIDTH APD 355 MM, WITH TRANS.) POLYTHENE 150 MM DIA GAUGE 300 (APPROX.28.0 METERS/KG) (TUBULAR FLAT WIDTH APP. 241 MM, WITH TRANS.) ALLUMINIUM SHEET 24 SWG (WITH TRANSPORT) ANGLE IRON 50X50X6 MM (WITH TRANSPORT) M.S. PLATE 12 MM THICK (WITH TRANSPORT) ADHESIVE (WATER RESISSTANT) EMULSIFIER- CSS/CRS EARLY STRENGTH ADMIXER (Usage:300 ml per 50 kg Cement bag) TRAFFIC CONES 75 MM X 8 MM DIA NUTS AND BOLTS SAW DUST (LOOSE) DRILL STEEL PIECE RATES & ALLOWANCES ALLOW FOR:	SQ.METRE METRE SQ.M KG KG LTR NO. NO. CU.M METER	615.00 2,369.05 1,112.70 27,697.75 1,308.75 2,560.00 380.30 2,489.50 24.15 127.55 150.06					
	PIECE RATES & ALLOWANCES							
B0-704 B0-705 B0-711 B0-712 B0-713 B0-714 B0-715 B0-716 B0-717 B0-718 B0-720 B0-723 B0-732 B0-741 B0-746 B0-751 B0-761 B0-762	CEMENT, SAND & WATER FOR JOINTING HUME [PIPES 152 MM DIAMETER - DO - 229 TO 610 MM DIAMETER - DO - 915 MM DIAMETER - DO - 1220 MM DIAMETER COIR ROPE (FOR SCAFFOLDING 93 SQ.M AREA) COIR STRING FOR CUTTING SIDE DRAINS (PER 2.83 CU.M) - DO - FIXING SCAFFOLDING (PER 93 SQ.M) MINOR REPAIRS OF PARAPETS WITH CEMENT, SAND & WATER (PER 9.29 SQ.M) FUEL *(FOR LOOSENING ROAD SURFACE IN MANUAL BREAKING 50 MM DEPTH X 307 SQ.M) FUEL, FORGE ETC.(PER 2.83 CU.M BLASTING) LADDERS (PER 93 SQ.M) PAINT (FOR LETTERING & NUMBERING ITEMS) PEGS (FOR TURFING IN 19 SQ.M AREA) SAND PAPER & COTT. WASTE (PER 9.29 SQ.M) SHARP, SCARIFIER TYNES (FOR 307 SQ.M) TIMBER PLANKS & BAMBOOS (FOR 93 SQ.M)) TIMBER POST, HORIZONTAL ETC. (FOR BARRICADING WORK IN 4 L.M.) WATER FOR CONCRETING:	ITEM DAY JOINT JOINT JOINT ITEM ITEM ITEM ITEM ITEM ITEM ITEM ITE	1,100.00 2,750.00 110.00 220.00 440.00 770.00 550.00 82.50 440.00 550.00 110.00 220.00 550.00 330.00 110.00 1,430.00 2,200.00					
	<u>ii</u>							
B0-781 B0-782	ALLOW FOR WATER (FOR MIXING BY MACHINE) ALLOW FOR WATER (FOR MIXING MANUALLY) PER PER	CU.M CU.M	55.00 55.00					
	WATER FOR COMPACTION & GENERAL USE							
B0-784 B0-785 B0-786 B0-787 B0-788	ALLOW FOR WATER (GRAVEL COMPACTION) PER ALLOW FOR WATER (AGGREGATE COMPACTION) PER ALLOW FOR WATER (MOISTENING ROAD SURFACE) ALLOW FOR WATER SUPPLY (BY BUCKET & COIR ROPE) WATER FOR GENERAL PURPOSES	CU.M CU.M ITEM ITEM LITRE	27.50 38.50 110.00 110.00 27.50					

			MC	JNAKAGALA DIS	IRICI		
CODE						UNIT	PRICE(RS.)
			A/11TTF \A//	SUTNC FOR R	ARRICARING		
		,	MHTIE MY	ASHING FOR B	ARRICADING		
B0-791 B0-792	WHITE WASHING EN				4 L.M. BARRICADING)	01 NO. 01 ITEM	250.00 93.75
	!				FOR ESTIMATION ONLY PROVED TENDER PRICES)		
		THEF		DING TRANSPO	KING MATERIALS DRT & VAT		
B0-800	THERMO PLASTIC R	OAD MARKIN	G MATERIA	 (WHITF)		KG	251.00
B0-801	THERMO PLASTIC		YELLOW)	_(,		KG	251.00
B0-802 B0-803	GLASS BEADS CATS EYE (ALUMINI	UM ROAD ST	JD, DOUBLI	E SIDED)		KG NO.	251.00 4,845.00
B0-804	DELETED		,	•			-
B0-805 B0-806	DELETED ZEBRA BARRICADIN	G TAPE (POL)	THENE)			METRE	33.63
		P.C.C. BI	AMS (Wir	es) EXCLUDIN	G TRANSPORT & VAT		
NOTE	Specifications of the RN indicates Rates a				ational highways		
	BEAM LENGTH	FT.	M	WT.(Tonnes)		
B0-810	P.C.C BEAM	11'.0	3.35	0.89		PER BEAM	55,000.00
B0-811	P.C.C BEAM	14'.0	4.26	1.13		PER BEAM	71,000.00
B0-812 B0-813	P.C.C BEAM P.C.C BEAM	17'.0 20'.0	5.18 6.09	1.57 2.08	D3	PER BEAM PER BEAM	88,000.00 112,000.00
B0-814	P.C.C BEAM	23'.0	7.01	2.26		PER BEAM	125,000.00
B0-814A		27'.0	8.23	2.19		PER BEAM	168,000.00
B0-815 B0-816	P.C.C BEAM P.C.C BEAM	32'.0 35'.0	9.75 10.67	2.59 2.86	20	PER BEAM PER BEAM	181,000.00 206,000.00
B0-817	P.C.C BEAM	40'.0	12.19	3.80	in all	PER BEAM	239,000.00
B0-818	P.C.C BEAM	44'.0	13.41	4.22	0,0,0,0,0	PER BEAM	266,000.00
B0-819	P.C.C BEAM	53'.0	16.15	5.07	2025 wision and civil Avis	PER BEAM	361,000.00
		P.C.C. BE	AMS(Strai	nds) EXCLUDI	NG TRANSPORT & VAT		
NOTE	Specifications of the	beams should	d be in com	pliance to the n	ational highways		
	BEAM LENGTH	FT.	M 	WT.(Tonne	5)(1 ¹ / ₁)		
B0-830	P.C.C BEAM	31.16'	9.5	2.32		PER BEAM	130,000.00
B0-831 B0-832	P.C.C BEAM P.C.C BEAM	37.72' 44.28'	11.5 13.5	3.21 4.20		PER BEAM PER BEAM	164,000.00 200,000.00
B0-833	P.C.C BEAM	47.56'	14.5	4.71		PER BEAM	250,000.00
B0-834	P.C.C BEAM	50.84'	15.5	5.44		PER BEAM	285,000.00
B0-835	P.C.C BEAM	54.12'	16.5	6.16		PER BEAM	305,000.00
		GABI	ON MESH	EXCLUDING 1	RANSPORT & VAT		
	ZINC COATED GA	BION BOXES	£4				
B0-850	1X1X1M INCLU. CO	ATED TIE (BI	NDING/WID	E @ 5% OE GA	RION WEIGHT	PER BOX	6,154,25
B0-851	2X1X0.5M INCLU. C					PER BOX	6,694.90
B0-852	1.5X1X1M INCLU. CO	OATED TIE (B	inding) w	IRE @ 5% OF G	ABION WEIGHT	PER BOX	8,325.40
B0-853 B0-854	2X1X1M INCLU. COA 3X1X1M INCLU. COA					PER BOX PER BOX	10,884.75 14,576.25
DU-03 4	PVC COATED GAB	· ·	IDING)WIKI	L @ 5% OF GAE	ION WEIGHT	PER BOX	14,570.25
DO 0501			UDINGWA	F @ F0/ OF C:	NON WEIGHT	DED DOV	0.026.26
B0-850A B0-851A	1X1X1M INCLU. CO. 2X1X0.5M INCLU. C	•	•	_		PER BOX PER BOX	8,826.20 10,765.45
	1.5X1X1M INCLU. CO					PER BOX	11,277.60
B0-853A	2X1X1M INCLU. COA	ATED TIE (BÎN	IDING)WIRI	E @ 5% OF GAE	ION WEIGHT	PER BOX	15,154.95
B0-854A	3X1X1M INCLU. COA	ATED TIE (BIN	IDING)WIRI	E @ 5% OF GAE	ION WEIGHT	PER BOX	21,624.95
		GEO	TEXTILES	EXCLUDING T	RANSPORT & VAT		
B0-860	GEOTEXTILE					PER 1 SQ.M	305.00

CODE		UNIT	PRICE(RS.)
	SIGNALIZATION EXCLUDING TRANSPORT AND VAT		
B0-900	SIGNAL POLE 4M THICKNESS 5MM, DIA 125MM, OCTAGANAL STEEL POLE HOT DIPPED GALVANIZED,	NOS	
B0-901	PLASTIC COATING INCLUDING WASHER NUT, WASHER PLATE 32MM NUTS AND BOLTS 5M ARM WITH POLE, MATERIAL Q235, THICKNESS SSM ,DIA. 230MM, OCTAGONAL CROSS SHAPE, HOT	NOS	
B0-902	DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC WHITE COLOR, 6.3M POLE HEIGHT 6M ARM WITH POLE, MATERIAL Q235, THICKNESS 5MM, DIA. 230MM, OCTAGONAL CROSS SHAPE, HOT	NOS	
B0-903	DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC WHITE COLOR, 6.3M POLE HEIGHT 7M ARM WITH POLE, MATERIAL Q235, THICKNESS 5MM ,DIA. 230MM, OCTAGONAL CROSS SHAPE, HOT	NOS	
B0-904	DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC WHITE COLOR, 6.3M POLE HEIGHT 9M ARM WITH POLE, MATERIAL Q235, THICKNESS 5MM, DIA. 230MM, OCTAGONAL CROSS SHAPE, HOT	NOS	
B0-905	DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC WHITE COLOR, 6.3M POLE HEIGHT 10.5M ARM WITH POLE, MATERIAL Q235, THICKNESS 8MM, DIA. 230MM,OCTAGONAL CROSS SHAPE, HOT	NOS	
B0-906	DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC WHITE COLOR,6.3M POLE HEIGHT 12M ARM WITH POLE,MATERIAL Q235, THICKNESS 8MM, DIA 330MM BOTTOM, 280MM TOP, OCTAGONAL CROSS SHAPE, HOT DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC WHITE	NOS	
B0-907	COLOR.6.3M POLE HEIGHT 7M DOUBLE ARM WITH POLE,MATERIAL Q235, THICKNESS 8MM ,DIA 330MM BOTTOM, 280MM TOP,OCTAGONAL CROSS SHAPE, HOT DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC	NOS	
B0-908	WHITE COLOR.6.3M POLE HEIGHT 9M DOUBLE ARM WITH POLE,MATERIAL Q235, THICKNESS 8MM ,DIA 330MM BOTTOM, 280MM TOP,OCTAGONAL CROSS SHAPE, HOT DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC	NOS	
B0-909	WHITE COLOR,6.3M POLE HEIGHT 12M DOUBLE ARM WITH POLE, MATERIAL Q235, THICKNESS 8MM ,DIA 330MM BOTTOM, 280MM TOP, OCTAGONAL CROSS SHAPE, HOT DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC	NOS	
B0-910	WHITE COLOR.6.3M POLE HEIGHT 7M ARM WITH ROTATABLE ARM, MATERIAL Q235, THICKNESS 8MM, DIA 320MM BOTTOM, 219MM TOP,OCTAGONAL CROSS SHAPE, HOT DIPPED GALVANIZED AFTER MANUFACTURED, AND THEN SPRAY PLASTIC WHITE COLOR. 6.3M POLE HEIGHT	NOS	
B0-911	9M ARM WITH ROTATABLE ARM, MATERIAL Q235, THICKNESS 8MM ,DIA 230MM BOTTOM, 219MM TOP,OCTAGONAL CROSS SHAPE, HOT DIPPED GALVANIZED AFTER MANUFACTURED, THEN SPRAY PLASTIC WHITE COLOR.6.3M POLE HEIGHT	NOS	
B0-912	3 CORE ARMOURED CABLE 3NOSX1.5MM2 (CU/PVC/SWA/PVC)	METER	
B0-913	4 CORE ARMOURED CABLE 4NOSX1.5MM2 (CU/PVC/SWA/PVC)	METER	
B0-914	24/0.20 3 CORE FLEXIBLE CABLE (CU/PVC/PVC/FLEXIBLE)	METER	
B0-915	24/0.20 4 CORE FLEXIBLE CABLE (CU/PVC/PVC/FLEXIBLE)	METER	
B0-916 B0-917	SLT FIBER CABLE 4 CORE 3 ASPECT SIGNAL HEAD 300MM DIA (LED DOUBLE COBWEB LENCE) WITH BRACKETS (IP 55 INCLUDING	NOS NOS	
B0-918	PLASTIC HOLISING) 2 ASPECT SIGNAL HEAD 300MM DIA (LED) WITH RED & GREEN 230VAC WITH BRACKETS (IP 55)	NOS	To be Published
B0-919	INCLUDING PLASTIC HOUSING) 2 ASPECT SIGNAL HEAD WITH COUNTDOWN 300MM DIA (LED) WITH RED & GREEN 230VAC WITH	NOS	in Future
B0-920	BRACKETS SINGAL ASPECT SIGNAL HEAD 300MM DIA (LED DOUBLE COBWEB LENSE) 230VAC WITH BRACKETS (IP 55	NOS	
B0-921	INCLUDING PLASTIC HOUSING) COUNTDOWN RED AND GREEN 400MM DIA, 2DIGIT, LED, 230V INCLUDING BRACKETS, NUT AND BOLTS	NOS	
B0-922 B0-923	COUNTDOWN RED 400MM DIA,2 DIGIT,LED,230V INCLUDING BRACKETS, NUT AND BOLTS COUNTDOWN RED 400MM DIA,3 DIGIT,LED,230V INCLUDING BRACKETS, NUT AND BOLTS		
B0-924	LED PATHWAY LIGHTS (30W,230VAC)	NOS	
B0-925	SIGNAL CONTROLLER INCLUDING SSR, SURGE ARRESTERS FOR JUNCTION (SIZE 500MM X 350MM X1200MM AND POWDER COATING, CONSIST WITH SIEMENS PLC + OUTPUT MODULE WITH SSR, 230VAC	NOS	
B0-926	POWER, DC/RELAY,1/0:14/10 INCLUDING CLOCK MODULE) SIGNAL CONTROLLER INCLUDING SSR, SURGE ARRESTERS FOR PELICAN CROSSING (SIZE 500MM X 350MM X1200MM AND POWDER COATING, CONSIST WITH SIEMENS PLC + OUTPUT MODULE WITH SSR, 230VAC POWER, DC/RELAY,1/0:14/10 INCLUDING CLOCK MODULE)	NOS	
B0-927	SIGNAL CONTROLLER INCLUDING SSR, SURGE ARRESTERS FOR FOR MULTIPLE COMBINED JUNCTIONS (SIZE 500MM X 350MM X1200MM AND POWDER COATING, CONSIST WITH SIEMENS PLC + OUTPUT MODULE WITH SSR, 230VAC POWER, DC/RELAY,1/0:14/10 INCLUDING CLOCK MODULE)	NOS	
B0-928	PUSH BUTTON BOX WITH WAIT INDICATOR(320MM X 200MM) DIE CAST ALUMINUM HOUSEING WITH PRINTED PERSPEX TRANSPARENT SHEET, MACHANICLE PUSH BUTTON AND 24VDC LED WAIT	NOS	
B0-929	INDICATOR.24VDC SWITCHED) PEDESTRIAN ILLUMINATION LIGHT BOX (POWDER COATED BOX WITH FRONT COVER MADE OF PRINTED TRANSPARENT PERSPECT BLUE COLOUR 750MM X 750MM X 130MM AND 230Vac TUBE LIGHTS)	NOS	
B0-930	ARROW SIGN BOARD 3M STICKER IN CLADDING SHEET WHITE AND GREEN	NOS	
B0-931	TARGET BOARD FOR 300MM 3 ASPECT SIGNAL HEAD (3MM, SS NUT & BOLT)	NOS	
B0-932	TARGET BOARD FOR 300MM 2 ASPECT SIGNAL HEAD (3MM, SS NUT & BOLT)	NOS	
B0-933	TARGET BOARD FOR 300MM SINGLE (1A) ASPECT SIGNAL HEAD (3MM, SS NUT & BOLT)	NOS	
BO-165 B0-934	MOUNTING BRACKET SOUND SYSTEM FOR BLIND PEDESTRIANS (MAX WORK POWER <18W, VOICE PROMPT RATE = 70±5	NOS NOS	
B0-935	TIMES/MIN (RED), 700±5 TIMES/MIN (GREEN), AC 85V-AC230V) SAFETY COVER FOR POLE FOOTING (FIBER MATERIAL)	NOS	
B0-936	COIL LOOP SYSTEM WITH RELAYS	NOS	
B0-937	SURGE ARRESTERS 230V	NOS	
B0-938 B0-939	POWER SUPPLY UNIT (12VDC, 4A) POWER SUPPLY UNIT (24VDC, 4A)	NOS NOS	
B0-939 B0-940	CONTROL PANEL (FIBER HOUSING, IP64)	NOS	
B0-941	CCTV CAMERA FOR DETECTING PEDESTRIANS (24VAC - 230VAC, BLUETOOTH FACILITY, IP 65, MIN. AMBIENT LIGHTING 10 LUX, 180MA @ 24VAC, RELAY TYPE DIRECT OUTPUT, 3M TO 2M DETECTION ZONE)	NOS	

H.S.R. - SCHEDULE OF INPUTS FOR THE YEAR 2025

MONARAGALA DISTRICT

	UNII	PRICE(RS.)
STRUCTURAL STEEL ITEMS EXCLUDING TRANSPORT A	ND VAT	
NOMINAL SIZE (mmxmmxmm)		
H IRON 100x100x6-8 125x125x6.5-9 150x75x5-7 150x100x6-9 150x150x6.5-9 200x100x5.5-8 200x200x8-12 250x125x6-9 250x150x6.10-8.60 250x250x9-14 300x150x6.5-9	METER	4,998.83 6,937.00 4,532.00 6,048.00 9,160.67 6,048.67 14,573.67 9,162.50 10,666.67 26,433.33 12,810.00
GALVANIZED IRON BOX BARS 12x12x1.2 20x20x2 25x25x2 30x30x2 40x20x1.4 40x40x2 50x25x2 50x50x2 80x25x2 80x80x2	METER	127.01 323.33 403.97 446.33 304.31 632.84 625.56 843.19 873.45 1,250.16
GALVANIZED IRON C PURLIN 100x50x2	METER	1,037.86
Winish of Leans both Highways,	Esand	
	NOMINAL SIZE (mmxmmxmm) H IRON 100x100x6-8 125x125x6.5-9 150x75x5-7 150x100x6-9 150x150x6.5-9 200x100x5.5-8 200x200x8-12 250x125x6-9 250x125x6-9 250x125x6-9 250x150x6.10-8.60 250x250x9-14 300x150x6.5-9 GALVANIZED IRON BOX BARS 12x12x1.2 20x20x2	STRUCTURAL STEEL ITEMS EXCLUDING TRANSPORT AND VAT

UNIT

PRICE(RS.)

CODE

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT (RS.)	LABOUR INPUT	OTHER INPUTS
	SECTION I				
	TRANSPORT				
	* SEE SECTION 23 OF GENERAL NOTES FOR SELECTION OF MODE OF TRANSPORT				
T1-001	TRANSPORT OF SOILS 25M TO 100M BY ANY MEANS (INCL. LOADING AND UNLOADING):	CU.M	704.70	687.50	17.20
T1-002	TRANSPORT 100M TO 0.5 KM BY ANY MEANS (EXCLUDING LOADING):	CU.M	382.35	0.00	382.35
T1-003	TRANSPORT 0.5 KM TO 1.0 KM BY ANY MEANS (EXCLUDING LOADING):	CU.M	409.65	0.00	409.65
T1-003A	TRANSPORT OF EACH SUBSEQUENT 1.0 KM FROM 1.0 - 8.0 KM. BY ANY MEANS : (EXCLUDING LOADING)	CU.M	63.70	0.00	63.70
T1-003B	TRANSPORT OF EACH SUBSEQUENT 1.0 KM BEYOND 8 KM. BY ANY MEANS: (EXCLUDING LOADING)	CU.M.J	42.80	0.00	42.80
>	* T1-003A, T1-003B: CODES CHANGED AS T1-003A AND T1-003B	الني:			
T1-006	TRANSPORT OF EACH SUBSEQUENT 1.0 KM FROM 1.0 - 8.0 KM. BY ANY MEANS: (EXCLUDING LOADING) TRANSPORT OF EACH SUBSEQUENT 1.0 KM BEYOND 8 KM. BY ANY MEANS: (EXCLUDING LOADING) * T1-003A, T1-003B: CODES CHANGED AS T1-003A AND T1-003B TRANSPORT OF MATERIAL IN BULK EXCLUDING LOADING (FOR DISTANCE LESS THAN OR EQUAL 3 KILO METRES): TRANSPORT OF MATERIAL IN BULK EXCLUDING LOADING (FROM 3 KM UPTO 10 KILO METRES DISTANCE): TRANSPORT OF MATERIAL IN BULK EXCLUDING LOADING (FOR DISTANCE MORE THAN 10 KILO METRES): * T1-008: CODE AMENDED AS T1-007A TRANSPORT OF PREMIX IN BULK, EXCLUDING	CU.M	121.00	0.00	121.00
T1-007	TRANSPORT OF MATERIAL IN BULK EXCLUDING LOADING (FROM 3 KM UPTO 10 KILO METRES DISTANCE):	CU.M/KM	40.35	0.00	40.35
T1-007A	TRANSPORT OF MATERIAL IN BULK EXCLUDING LOADING (FOR DISTANCE MORE THAN 10 KILO METRES):	CU.M/KM	38.90	0.00	38.90
,	* T1-008 : CODE AMENDED AS T1-007A				
T1-009	TRANSPORT OF PREMIX IN BULK, EXCLUDING LOADING OTHER THAN AT MIXING PLANT	M.TON/KM	26.75	0.00	26.75
T1-010	TRANSPORT OF BARRELS OF BITUMEN FOR FIRST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	NOS.	60.15	6.41	53.74
T1-010A	TRANSPORT OF BARRELS OF BITUMEN FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM. (EXCLUDING LOADING AND UNLOADING):	NOS.	14.75	6.41	8.34
T1-010B	TRANSPORT OF BARRELS OF BITUMEN FOR EACH SUBSEQUENT 1.0 KM BEYOND 8 KM. (EXCLUDING LOADING AND UNLOADING):	NOS.	10.30	4.69	5.61
,	* T1-011 & T1-012 CODES CHANGED				
T1-013	LOADING BARRELS OF BITUMEN INCLUSIVE OF ROLLING UPTO 25M:	NOS.	43.75	43.75	0.00
T1-014	UNLOADING BARRELS OF BITUMEN INCLUSIVE OF ROLLING AND STACKING:	NOS.	18.75	18.75	0.00

CODE	DESCRIPTIO	ON OF ITEM	UNIT	AMOUNT (RS.)	LABOUR INPUT	OTHER INPUTS
T1-015	TRANSPORT OF HUME PIPES 152MM DIA. FOR 1ST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	45.45	6.26	39.19
T1-015A	TRANSPORT OF HUME PIPES 152MM DIA. FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	12.35	6.26	6.09
T1-015B	TRANSPORT OF HUME PIPES 152MM DIA. FOR EACH SUBSEQUENT 1.0 KM BEYOND 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	8.85	4.78	4.07
;	* T1-016 & T1-017 CODES CHANGED					
T1-018	TRANSPORT OF HUME PIPES 229 MM DIA. FOR 1ST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	51.10	7.04	44.06
T1-018A	TRANSPORT OF HUME PIPES 229 MM DIA. FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	Engine Prind Division sand Care and Car	L.M.	13.90	7.04	6.86
T1-018B	TRANSPORT OF HUME PIPES 229 MM DIA. FOR EACH SUBSEQUENT 1.0 KM BEYOND 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	Op ision sand	L.M	10.00	5.38	4.62
3	* T1-019 & T1-020 : CODES CHANGED	50 014 601				
T1-021	TRANSPORT OF HUME PIPES 305 MM DIA. FOR 1ST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	HSP HINDYS,	L.M	68.15	9.39	58.76
T1-021A	TRANSPORT OF HUME PIPES 305 MM DIA. FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	Eng. His	L.M	18.55	9.39	9.16
T1-021B	TRANSPORT OF HUME PIPES 305 MM DIA. FOR EACH SUBSEQUENT 1.0 KM BEYOND 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	13.30	7.17	6.13
3	* T1-022 & T1-023: CODES CHANGED					
T1-024	TRANSPORT OF HUME PIPES 457 MM DIA. FOR 1ST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	102.25	14.09	88.16
T1-024A	TRANSPORT OF HUME PIPES 457 MM DIA. FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	27.80	14.09	13.71
T1-024B	TRANSPORT OF HUME PIPES 457 MM DIA. FOR EACH SUBSEQUENT 1.0 KM BEYOND 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	19.95	10.76	9.19
,	* T1-025 & T1-026: CODES CHANGED					

CODE	DESCRIPTIO	ON OF ITEM	UNIT	AMOUNT (RS.)	LABOUR INPUT	OTHER INPUTS
T1-027	TRANSPORT OF HUME PIPES 610 MM DIA. FOR 1ST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	136.30	18.78	117.52
T1-027A	TRANSPORT OF HUME PIPES 610 MM DIA. FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	37.05	18.78	18.27
T1-027B	TRANSPORT OF HUME PIPES 610 MM DIA. FOR EACH SUBSEQUENT 1.0 KM BEYOND 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):		L.M	26.60	14.34	12.26
;	* T1-028 & T1-029: CODES CHANGED					
T1-030	TRANSPORT OF HUME PIPES 915 MM DIA. FOR 1ST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING) :		L.M	204.45	28.18	176.27
T1-030A	TRANSPORT OF HUME PIPES 915 MM DIA. FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	Engine Ping Division sand Care Sort Sand Care Sort, Highways, Ports and Care Sand Care	L.M. Vidi	55.60	28.18	27.42
T1-030B	TRANSPORT OF HUME PIPES 915 MM DIA. FOR EACH SUBSEQUENT 1.0 KM BEYOND 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	as sion sand	L.M	39.95	21.52	18.43
2	* T1-031 & T1-032: CODES CHANGED	Solinbour				
T1-033	TRANSPORT OF HUME PIPES 1220 MM DIA. DIA. FOR 1ST 1.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	HSP ind Mays,	L.M	465.25	112.70	352.55
T1-033A	TRANSPORT OF HUME PIPES 1220 MM DIA. FOR EACH SUBSEQUENT 1.0 KM, FROM 1.0 - 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING):	Eng. His	L.M	167.55	112.70	54.85
T1-033B	TRANSPORT OF HUME PIPES 1220 MM DIA. FOR EACH SUBSEQUENT 1.0 KM BEYOND 8.0 KM OF TRANSPORT (EXCLUDING LOADING AND UNLOADING) :	O	L.M	121.85	85.04	36.81
;	* T1-034 & T1-035: CODES CHANGED					
T1-036	LOADING AND UNLOADING 152 MM DIA. 2.44 M LONG HUME PIPES :		NOS	135.00	135.00	0.00
T1-037	LOADING AND UNLOADING 229 MM DIA. 2.44 M LONG HUME PIPES :		NOS	157.50	157.50	0.00
T1-038	LOADING AND UNLOADING 305 MM DIA. 2.44 M LONG HUME PIPES :		NOS	312.50	312.50	0.00
T1-039	LOADING AND UNLOADING 457 MM DIA. 2.44 M LONG HUME PIPES :		NOS	520.00	520.00	0.00
T1-040	LOADING AND UNLOADING 610 MM DIA. 2.44 M LONG HUME PIPES :		NOS	677.50	677.50	0.00

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT (RS.)	LABOUR INPUT	OTHER INPUTS
T1-041	LOADING AND UNLOADING 915 MM DIA. 1.22 M LONG HUME PIPES :	NOS	1,250.00	1250.00	0.00
T1-042	LOADING AND UNLOADING 1220 MM DIA. 1.22 M LONG HUME PIPES :	NOS	2,500.00	2500.00	0.00
T1-043	TRANSPORT OF PRECAST KERB STONES (ALL TYPES) FOR ROAD WORKS, INCLUDING LOADING AND UNLOADING:	L.M/KM	3.25	0.25	3.00
T1-044	TRANSPORT OF PRECAST KERB STONES FOR BRIDGE WORKS, INCLUDING LOADING AND UNLOADING :	L.M/KM	4.85	0.55	4.30
T1-045	TRANSPORT OF PRECAST CONCRETE HAND RAILS, UP-RIGHTS AND JOINTS FOR BRIDGE WORKS, INCLUDING LOADING AND UNLOADING :	L.M/KM	7.25	0.66	6.59
T1-046	TRANSPORT OF PRECAST CONCRETE SLABS 450X450X50 MM FOR FOOT WALKS, INCLUDING LOADING AND UNLOADING:	SQ.M/KM	9.15	0.75	8.40
T1-047	TRANSPORT OF PRECAST STANDARD BOUNDARY MARKERS, INCLUDING UNLOADING ONLY*:	NO./KM	4.50	0.27	4.23
	* SUPPLY RATE INCLUDE LOADING AT YARD.				
T1-048	TRANSPORT OF EMULSION RATE FOR 100 LITERS PER KILO METRE	100L/KM	4.70	0.00	4.70
T1-049	TRANSPORT OF GABION MESH 4 X 1 X1 M SIZE	NO./KM	2.25	0.03	2.22
	TRANSPORT OF PRECAST CONCRETE SLABS 450X450X50 MM FOR FOOT WALKS, INCLUDING LOADING AND UNLOADING: TRANSPORT OF PRECAST STANDARD BOUNDARY MARKERS, INCLUDING UNLOADING ONLY*: * SUPPLY RATE INCLUDE LOADING AT YARD. TRANSPORT OF EMULSION RATE FOR 100 LITERS PER KILO METRE TRANSPORT OF GABION MESH 4 X 1 X1 M SIZE * * * *				

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION II ======== ROADWAY AND FOUNDATION / TRENCH EXCAVATION				
	(INCLUDING LOADING, UNLOADING AND TRANSPORTING WITHIN 25 METERS DISTANCE UNLESS OTHERWISE SPECIFIED)				
* NOTE	FOR ROADWAY EXCAVATIONS INVOLVING MORE THAN 200 CU.M , MACHINE RATES SHOULD BE ADOPTED.				
E1-001	EXCAVATION IN LOOSE SOIL (DRY) [SSCM 301.2(IV)]:	CU.M	940.80	883.39	57.41
E1-002	EXCAVATION IN LOOSE SOIL (WET) IN SLIPS [SSCM 301.3(0)]:	CU.M	1,167.20	1,104.24	62.96
E1-003	EXCAVATION IN ORDINARY SOIL (CUTTING MEASUREMENT) [SSCM 301.2(V)] :	CU.M	1,393.55	1,325.09	68.46
E1-004	EXCAVATION IN ORDINARY SOIL (VEHICLE MEASUREMENT) [SSCM 301.2(V)]:	CU.M	1,254.20	1,192.58	61.62
E1-005	EXCAVATION IN MEDIUM SOIL (CUTTING MEASUREMENT) [SSCM 301.2(VI)] :	CU.M	1,846.30	1,766.78	79.52
E1-006	EXCAVATION IN MEDIUM SOIL (VEHICLE MEASUREMENT) [SSCM 301.2(VI)]:	CU.M	1,569.35	1,501.77	67.58
E1-007	EXCAVATION IN HARD SOIL (CUTTING MEASUREMENT) [SSCM 301.2(VII)]:	CU.M	2,751.75	2,650.18	101.57
E1-008	EXCAVATION IN MEDIUM SOIL (CUTTING MEASUREMENT) [SSCM 301.2(VI)]: EXCAVATION IN MEDIUM SOIL (VEHICLE MEASUREMENT) [SSCM 301.2(VI)]: EXCAVATION IN HARD SOIL (CUTTING MEASUREMENT) [SSCM 301.2(VII)]: EXCAVATION IN HARD SOIL (VEHICLE MEASUREMENT) [SSCM 301.2(VII)]: EXCAVATION IN UNCLASSIFIED SOIL (CUTTING MEASUREMENT) [SSCM 301.2(VII)]:	CU.M	2,339.00	2,252.65	86.35
E1-009	EXCAVATION IN UNCLASSIFIED SOIL (CUTTING MEASUREMENT) [SSCM 301.2(VII)]:	CU.M	1,997.20	1,914.02	83.18
NOTE:	SEE CODE NOS. FROM E1-027 ON PAGE 13 FOR ROADWAY EXCAVATION USING MACHINERY				
E1-010	EXCAVATION IN SOFT ROCK (CUTTING MEASUREMENT) [SSCM 301.2(VII)]:	CU.M	2,978.15	2,871.02	107.13
E1-010A	EXCAVATION IN MUD MARSHY MATERIAL (CUTTING MEASUREMENT) [SSCM 301.2(VII)] :	CU.M	2,299.05	2,208.48	90.57
E1-011	EXCAVATION PIT/TRENCH FOR FOUNDATION IN ORDINARY SOIL NOT EXCEEDING 1.5 M. DEEP, INCLUDING LEVELLING AND RAMMING BOTTOM, EXCAVATED MATERIAL DEPOSITED AT SITE WITH IN 25 M OR AS DIRECTED. * (SHORING, DEWATERING IF NECESSARY SHALL BE PAID SEPERATELY) [SSCM 302.1-302.3]:	CU.M	1,846.30	1,766.78	79.52
* NOTE	SEE GENERAL NOTES 24(2) FOR DETAILS REGARDING ADDITIONAL EXCAVATION REQUIRED FOR WORKING SPACE.				

	MUNARAGALA DISTRICT				
CODE	DESCRIPTION OF ITEM	UNIT 	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
E1-012	DITTO - MEDIUM SOIL, - DO - DO - :	CU.M	2,299.05	2,208.48	90.57
E1-013	DITTO - HARD SOIL, - DO - DO - :	CU.M	3,204.50	3,091.87	112.63
E1-014	DITTO - IN UNCLASSIFIED SOIL, - DO - DO - :	CU.M	2,449.95	2,355.71	94.24
E1-015	DITTO - MUD/MARSHY MATERIAL, - D0 -	DO CU.M	2,751.75	2,650.18	101.57
E1-016	DELETED				
E1-017	DELETD				
E1-018	DELETED				
E1-019	EXCAVATING SOFT ROCK, NOT EXCEEDING 1.5 M DEPTH [SSCM 301.2(II)] :	CU.M	3,657.25	3,533.57	123.68
* NOTE	EXCAVATING ROCK FOR FOUNDATION TO BE PAID ON S.S.R.				
			,iO1.		
E1-020	DELETED	P	lation		
E1-021	PILING AVAILABLE SOIL :	CU.M	226.35	220.85	5.50
E1-022	LOADING AVAILABLE SOIL	CU.M	298.80	291.52	7.28
E1-023	EXCAVATING ROCK, REQUIRING BLASTING, FOR ROADWAY AND AT QUARRY FOR BOULDERS (BANK MEASUREMENT -)			
	EXCLUDING DOZING AWAY) [SSCM 301.2(III) & 306.1 - 306.4]:	CU.M	2,809.65	63.48	2,746.17
E1-024	PILING AVAILABLE SOIL: LOADING AVAILABLE SOIL EXCAVATING ROCK, REQUIRING BLASTING, FOR ROADWAY AND AT QUARRY FOR BOULDERS (BANK MEASUREMENT - EXCLUDING DOZING AWAY) [SSCM 301.2(III) & 306.1 - 306.4]: BOULDERS SLEDGING, PILING, ETC.: ROCK REQUIRING BLASTING (BANK MEASUREMENT):	CU.M	4,482.10	4,372.79	109.31
E1-025	ROCK REQUIRING BLASTING (BANK MEASUREMENT):	CU.M	5,280.05	3,798.59	1,481.46
E1-026	ROCK REQUIRING BLASTING AND PILING (BANK MEASUREMENT)	CU.M	6,502.45	4,991.17	1,511.28
E1-027	ROADWAY EXCAVATION IN UNCLASSIFIED SOIL USING MACHINERY EXCLUDING LOADING AND PILING. (CUTTING MEASUREMENT)	CU.M	306.30	12.48	293.82
	nights				
E1-028	LOADING MATERIAL BY MACHINERY IN ROADWAY EXCAVATIONS (CUTTING MEASUREMENT)	CU.M	112.75	6.89	105.86
E1-029	TRIMMING / CAMBERING BY MOTOR GRADER (CUTTING MEASUREMENT)	CU.M	37.80	2.52	35.28
	,	551	27.130		22.20
E1-029A	- DO - RATE PER 1 SQ.M	SQ.M	7.55	0.50	7.05
E1-030	ROCK BLASTING USING CHEMICAL POWDER FALLEN ROCKS OF BOULDERS > 1 M3 (ONLY FOR ESSENTIAL CONDITIONS) EXCLUDING LOADING & TRANSPORTING AFTER BREAKING ***	CU.M	9,237.30	520.83	8,716.47

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR OTHER	
	SECTION III				
	AGGREGATE/RUBBLE PILING INCLUDING LOADING				
A1-001	SLEDGING AVAILABLE ROCK 150-225 MM RUBBLE INCLUDING PILING & LOADING :	CU.M	3,621.90	3,533.57 88.3	3
A1-002	BLASTING ETC. & PILING 150-225MM RUBBLE INCLUDING LOADING :	CU.M	6,366.60	4,858.66 1,507.9	4
A1-002A	BLASTING SLEDGING ETC. & PILING 150-225MM RUBBLE USING COMPRESSOR & HAND HELD DRILLS INCLUDING LOADING :	CU.M	4,363.90	1,319.44 3,044.4	6
A1-003	BLASTING ETC. & PILING 100 MM AGGREGATE, INCLUDING LOADING :	CU.M	2,932.86	External Sources	
A1-004	BLASTING ETC. & PILING 75 MM AGGREGATE INCLUDING LOADING :	CU.M	2,932.86	External Sources	
A1-005	BLASTING ETC. & PILING 50 MM AGGREGATE INCLUDING LOADING :	CU.M. I Zili	2,633.33	External Sources	
A1-006	BLASTING ETC. & PILING 37.5 MM AGGREGATE INCLUDING LOADING :*	DELETED			
A1-007	INCLUDING LOADING: BLASTING ETC. & PILING 37.5 MM AGGREGATE INCLUDING LOADING:* BLASTING ETC. & PILING 25 MM AGGREGATE INCLUDING LOADING:* BLASTING ETC. & PILING 19 MM AGGREGATE INCLUDING LOADING:* PRIOR APPROVAL OF THE P.DD. SHOULD BE OBTAINED FOR THE USE OF 19 MM, 25 MM AND 37.5 MM HAND	DELETED			
A1-008	BLASTING ETC. & PILING 19 MM AGGREGATE INCLUDING LOADING : *	DELETED			
* NOTE	PRIOR APPROVAL OF THE P.DD. SHOULD BE OBTAINED FOR THE USE OF 19 MM, 25 MM AND 37.5 MM HAND BROKEN AGGREGATE.				
A1-009	50 MM AGGREGATE, SINGLE SIZE, CRUSHER PRODUCTION INCLUDING PILING AND LOADING [SSCM404.1-406.1]:	CU.M	2,633.35	External Sources	
A1-010	37.5 MM AGGREGATE, SINGLE SIZE, CRUSHER PRODUCTION INCLUDING PILING AND LOADING [SSCM404.1-406.1]:	CU.M	2,666.65	External Sources	
A1-011	19 MM AGGREGATE, SINGLE SIZE CRUSHER PRODUCTION INCLUDING PILING AND LOADING [SSCM404.1-406.1]:	CU.M	2,800.00	External Sources	
A1-012	12.5 MM AGGREGATE, SINGLE SIZE CRUSHER PRODUCTION INCLUDING PILING AND LOADING FOR 1.0 CUBE :	CU.M	2,400.00	External Sources	

HIGHWAY SCHEDULE OF RATES - SUMMARY 2025

MONARAGALA DISTRICT

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	PLANT PRODUCED AGGREGATE FOR DENSE GRADED AGGREGATE BASE COURSE				
A1-013	AGGREGATE 37.5 MM, DOWN GRADED (SSCM - TABLE 1701.5) INCLUDING PILING & LOADING :	CU.M	2,500.00	External Sou	rces
A1-014	CRUSHER FINES 6.3 MM DOWN, INCLUDING PILING AND LOADING FOR 1.0 CUBE:	CU.M	2,066.65	External Sou	rces
A1-015	AGGREGATE 19 MM FOR SEAL COAT TREATMENTS AS PER SSCM TABLE 1701-8	CU.M	2,800.00	External Sou	rces
A1-016	AGGREGATE 12.5 MM FOR SEAL COAT TREATMENTS AS PER SSCM TABLE 1701-8	CU.M	2,400.00	External Sources	
A1-017	BLENDED AGGREGATE FOR RECTIFICATION OVERLAY, WITH 37.5 MM SINGLE SIZE AGGREGATE AND 19 MM & 12.5 MM CRUSHED AGGREGATE MIXED IN THE VOLUME RATIO OF 7:2:1, INCLUDING MIXING, LOADING. (PILING TO PLAY SEPARATELY) :* * PRIOR APPROVAL OF THE P.DD SHOULD BE OBTAINED	CU.M	2,692.90	0.00	2,692.90
	FOR THE USE OF BLENDED AGGREGATE IN RECTIFICATION OVERLAY CONSTRUCTION WORK.	الم الد			
A1-018	PILING AVAILABLE AGGREGATE:	CU.M	249.00	242.93	6.07
A1-019	PILIING AVAILABLE RUBBLE:	CU.M	498.00	485.87	12.13
A1-020	LOADING AVAILABLE RUBBLE/AGGREGATE:	CU.M	452.75	441.70	11.05
	BLENDED AGGREGATE FOR RECTIFICATION OVERLAY, WITH 37.5 MM SINGLE SIZE AGGREGATE AND 19 MM & 12.5 MM CRUSHED AGGREGATE MIXED IN THE VOLUME RATIO OF 7:2:1, INCLUDING MIXING, LOADING. (PILING TO PLAY SEPARATELY):* * PRIOR APPROVAL OF THE P.DD SHOULD BE OBTAINED FOR THE USE OF BLENDED AGGREGATE IN RECTIFICATION OVERLAY CONSTRUCTION WORK. PILING AVAILABLE AGGREGATE: PILIING AVAILABLE RUBBLE: LOADING AVAILABLE RUBBLE/AGGREGATE:				

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION IV				
	======== APPROVED EARTH FILLING & COMPACTION				
* NOTE	RATES FOR BORROW EARTH SUPPLY GIVEN UNDER ITEM CODES EW1-001 & EW1-011 IN THIS SHEDULE IS BASED ON MANUAL EXCAVATION AND INTENDED FOR SMALL WORKS INVOLVING LESS THAN 200 CU.M. IN THE CASE OF BORROW EARTH SUPPLY EXEEDS 200 CU.M(FOR THE WHOLE PROJECT), RATES BASED ON MACHINE EXCAVATION AS PER B0-201, B0-202, EW1-013 OR EW1-014 SHALL BE ADOPTED. FOR ANY DEVIATIONS THE PROCURAMENT PROCEDURE GIVEN IN "GENERAL NOTES", SHALL BE FOLLOWED.				
EW1-001	APPROVED SOIL (TYPE I & II MATERIALS)				
	EXCAVATION FOR SUB BASES & SHOULDER CONSTRUCTION INCLUDING LOADING AND PILING (LOOSE VOLUME) [SSCM 601.1 TO 601.4]:	CU.M	2,655.50	2,544.17	111.33
EW1-002	SPREADING PILED GARVEL (LOOSE VOLUME):	CU.M	312.65	275.94	36.71
EW1-003 *	APPROVED SOIL SPREAD & ROLLED INCLUDING HIRE CHARGES, FUEL & WATERING (LOOSE VOLUME) [SSCM 601.1 TO 4]:	CU.M. još	593.25	275.94	317.31
k	SEE GENERAL NOTES SECTION 26.4 FOR RATE ON COMPACTED VOLUME.	النا			
	ADOPTED ON APPROVAL BY PD / CF FOR SMALL WORKS ONLY, WHEN).			
EW1-003A	MACHINERY IS USED FOR SPREADING AND COMPACTION, EW1-003A SHALL BE ADOPTED. APPROVED SOIL SPREAD & ROLLED USING MACHINERY INCLUDING MOTOR GRADER & ROLLER HIRE CHARGES, FUEL & WATERING (LOOSE VOLUME) [SSCM 601.1 TO 4]: SEE GENERAL NOTES SECTION 26.4 FOR RATE ON COMPACTED VOLUME. APPROVED SOIL SPREAD & ROLLED IN STRIPS WHERE AVERAGE WIDTH IS LESS THAN 1.2 METERS FOR ROAD WIDENING, INCLUDING HIRE CHARGES ELIEL &	CU.M	234.10	0.00	234.10
*	SEE GENERAL NOTES SECTION 26.4 FOR RATE ON COMPACTED VOLUME.				
EW1-004	APPROVED SOIL SPREAD & ROLLED IN STRIPS WHERE AVERAGE WIDTH IS LESS THAN 1.2 METERS FOR ROAD WIDENING, INCLUDING HIRE CHARGES, FUEL & WATERING (LOOSE VOLUME) [SSCM 601.1 TO 4]:	CU.M	697.00	275.94	421.06
*	SEE GENERAL NOTES SECTION 26.4 FOR RATE ON COMPACTED VOLUME.				
EW1-005	DELETED				
EW1-006	APPROVED SOIL SPREAD AND COMPACTED IN PLACES BEHIND ABUTMENTS AND STRUCTURES, SHOULDERS ABOVE SUB BASE LEVEL AND IN SERVICE LINE TRENCHES USING 1/2 - 1 TON VIBRATING ROLLER INCLUDING WATERING. (LOOSE VOLUME):	CU.M	724.95	357.14	367.81
*	SEE GENERAL NOTES SECTION 26.4 FOR RATE ON COMPACTED VOLUME.				

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
EW1-007	APPROVED SOIL SPREAD AND COMPACTED USING MACHINE RAMMER IN NARROW PLACES. (LOOSE VOLUME):	CU.M	677.55	357.14	320.41
EW1-008	SPREADING, LEVELLING AND COMPACTING MANUALLY, USING STANDARD CAST IRON TAMPER OR EQUIVALENT AND FILLING IN 150-225 MM THICK LAYERS (LOOSE VOLUME):	CU.M	1,018.65	993.82	24.83
EW1-009	TRIMMING, LEVELLING AND COMPACTION OF ORIGINAL GROUND/SUBGRADE TO 100% STD. DENSITY. [SSCM 304.3(C)]:	SQ.M	85.80	8.50	77.30
EW1-010	TRIMMING, LEVELLING AND COMPACTION OF ORIGINAL GROUND/SUBGRADE TO 95% STD. DENSITY. [SSCM 304.3(C)]:	SQ.M	78.00	7.73	70.27
EW1-011	APPROVED SOIL EXCAVATION FOR EMBANKMENT FILLING INCLUDING LOADING AND PILING. (LOOSE VOLUME) [SSCM 601.1 TO 601.4]:	CU.M	1,885.85	1,793.29	92.56
EW1-012	DELETED	il Pil	(O-		
EW1-013	APPROVED SOIL(TYPE I & II MATERIALS) EXCAVATION USING MACHINERY FOR SUB BASES & SHOULDER CONSTRUCTION INCLUDING LOADING AND PILING. (LOOSE VOLUME) [SSCM 601.1 TO 604.4]	CU.M	1,374.80	220.85	1,153.95
EW1-014	APPROVED SOIL(TYPE I & II MATERIALS) EXCAVATION USING MACHINERY FOR EMBANKMENT FILLING INCLUDING LOADING AND PILING. (LOOSE VOLUME) [SSCM 601.1 TO 604.4]	CU.M	1,109.75	220.85	888.90
EW1-015	GRADING AND SPREADING BY MOTOR GRADER RATE PER CU.M (LOOSE)	SAY	68.90	0.00	68.90
	APPROVED SOIL EXCAVATION FOR EMBANKMENT FILLING INCLUDING LOADING AND PILING. (LOOSE VOLUME) [SSCM 601.1 TO 601.4]: DELETED APPROVED SOIL(TYPE I & II MATERIALS) EXCAVATION USING MACHINERY FOR SUB BASES & SHOULDER CONSTRUCTION INCLUDING LOADING AND PILING. (LOOSE VOLUME) [SSCM 601.1 TO 604.4] APPROVED SOIL(TYPE I & II MATERIALS) EXCAVATION USING MACHINERY FOR EMBANKMENT FILLING INCLUDING LOADING AND PILING. (LOOSE VOLUME) [SSCM 601.1 TO 604.4] GRADING AND SPREADING BY MOTOR GRADER RATE PER CU.M (LOOSE) ****				

HIGHWAY SCHEDULE OF RATES - SUMMARY 2025

MONARAGALA DISTRICT

CODE	DESCRIPTION OF ITEM	UNIT 	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION V =======				
	RUBBLE PAVING ========== (RUBBLE TO BE PAID SEPARATELY)				
P1-001	PITCHED PAVING 225 MM THICK:	SQ.M	606.85	592.03	14.82
P1-002	PITCHED PAVING 150 MM THICK:	SQ.M	455.15	444.03	11.12
P1-003	FLAT PAVING 225 MM THICK:	SQ.M	403.55	393.70	9.85
P1-004	FLAT PAVING 150 MM THICK:	SQ.M	303.40	296.02	7.38

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

**

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION VI				
	AGGREGATE SPREADING & COMPACTION				
	COST OF WATERING TO BE DEDUCTED FROM RATE IF NOT CARRIED OUT UNDER THE RELEVANT ITEMS.				
	NOTE: COST OF AGGREGATE SUPPLY AND TRANSPORT, NOT INCLUDED IN THE RATES F M1-004,M1-007,M1-008 AND M1-009	FOR ITEMS: I	M1-001,		
M1-001	SPREADING, WATERING & ROLLING 100 MM AGGREGATE INCLUDING HIRE CHARGES OF ROLLER. (LOOSE VOLUME) [SSCM 304.3(d),(e)]:	CU.M	1,337.95	607.06	730.89
M1-002	BREAKING ROAD SURFACE TO 50 MM DEPTH BY HAND, SCREEN & REPLACE OLD AGGREGATE. :	SQ.M	166.90	159.62	7.28
M1-003	SCARIFYING ROAD SURFACE TO 50 MM DEPTH BY MACHINARY, SCREEN, & REPLACE OLD AGGREGATE. :	SQ.M	120.25	69.11	51.14
M1-004	SPREADING & COMPACTING 50-19 MM NEW AGGREGATE BY ROLLER INCLUDING WATERING HIRE, ETC.(LOOSE VOLUME)[SSCM 403.3(c)]:	CU.M.	2,076.25	1,144.68	931.57
M1-005	BREAKING 50 MM ADDITIONAL DEPTH BY HAND SCREENING & REPLACING OLD AGGREGATE. :	SQ.M	100.05	94.39	5.66
M1-006	SCARIFYING 50 MM ADDITIONAL DEPTH WITH MACHINARY, SCREENING & REPLACING OLD AGGREGATE. :	SQ.M	95.20	44.65	50.55
M1-007	SCARIFYING ROAD SURFACE TO 50 MM DEPTH BY MACHINARY, SCREEN, & REPLACE OLD AGGREGATE.: SPREADING & COMPACTING 50-19 MM NEW AGGREGATE BY ROLLER INCLUDING WATERING HIRE, ETC.(LOOSE VOLUME)[SSCM 403.3(c)]: BREAKING 50 MM ADDITIONAL DEPTH BY HAND SCREENING & REPLACING OLD AGGREGATE.: SCARIFYING 50 MM ADDITIONAL DEPTH WITH MACHINARY, SCREENING & REPLACING OLD AGGREGATE.: SPREADING & COMPACTING 50-19 MM AGGREGATE IN EDGE CORRECTION USING ROLLER INCLUDING HIRE, ETC.(LOOSE VOLUME)[SSCM 1103.3]: SPREADING & COMPACTING 50-19 MM AGGREGATE	CU.M	2,493.55	797.81	1,695.74
M1-008	SPREADING & COMPACTING 50-19 MM AGGREGATE IN STRIP CORRECTION USING ROLLER INCLUDING HIRE, ETC.(LOOSE VOLUME)[SSCM 1103.3]:	CU.M	2,060.40	797.81	1,262.59
M1 008A	225X150MM RUBBLE FILLING FOR CHOCKING WITH AGGRGATE BASE COURSE FOR SOFT GROUND TREATMENT (INCLUDING LOADING, UNLOADING AND TRANSPORT OF MATRERIALS)	CU.M	3,583.55	151.54	3,432.01
M1-009	SPREADING & COMPACTING 50-19 MM AGGREGATE BY D.ROLLER AFTER APPLYING TACK COAT IN OVERLAY. (LOOSE VOLUME)(TACK COAT PAID SEPARATELY):	CU.M	1,868.55	797.81	1,070.74
M1-010	WATER BOUND MACADAM - SPREADING WATERING AND COMPACTING 50-25 MM AGGREGATE AND FILLING THE VOIDS TO REFUSAL WITH CRUSHER FINES BY WATERING AND ROLLING TO FORM A WATER BOUND MACADAM BASE EXCLUDING TRANSPORT FOR AGGREGATES AND FINES. (LOOSE VOLUME) [(SSCM 404.1)]:	CU.M	6,312.10	1,455.88	4,856.22
M1-011	DRY BOUND MACADAM - SPREADING WATERING AND COMPACTING 50-25 MM AGGREGATE AND FILLING THE VOIDS TO REFUSAL WITH CRUSHER FINES BY ROLLING WITH VIBRATING ROLLER TO FORM A DRY BOUND MACADAM BASE EXCLUDING TRANSPORT FOR AGGREGATES AND FINES (LOOSE VOLUME)[SSCM 404.1]:	CU.M	5,950.10	1,455.88	4,494.22

HIGHWAY SCHEDULE OF RATES - SUMMARY 2025

MONARAGALA DISTRICT

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
M1-012	DELETED				
M1-012A	DENSE GRADED AGGREGATE BASE [AGGREGATE BASE COURSE] SPREADING WATERING AND COMPACTING GRADED 37.5 MM AGGREGATE TO FORM A DENSE AGGREGATE BASE USING MACHINERY INCLUDING MOTOR GRADER & ROLLER HIRE CHARGES (TRANSPORT OF AGGREGATES TO BE PAID SEPARATELY) (LOOSE VOLUME)[SSCM 405.1]:	CU.M *	2,919.51	0.00	2,919.51
*	FOR THE RATE ON COMPACTED VOLUME, INCREASE THE LOOSE VOLUME RATE BY 42%. IF MEASUREMENT IS ON END PRODUCT, PILING COST OF AGGREGATE AS PER A1-018 SHALL BE DEDUCTED.				
M1-013	DENSE GRADED AGGREGATE BASE [AGGREGATE BASE COURSE] SPREADING, WATERING AND COMPACTING GRADED 37.5 MM AGGREGATE TO FORM A DENSE AGGREGATE BASE IN STRIPS OF AVERAGE WIDTH NOT EXCEEDING 1.2 M FOR ROAD WIDENING EXCLUDING TRANSPORT OF AGGREGATES (LOOSE VOLUME)[SSCM 405.1]:	CU.M *	4,542.15	832.49	3,709.66
*	FOR THE RATE ON COMPACTED VOLUME, INCREASE THE LOOSE VOLUME RATE BY 42%. IF MEASUREMENT IS ON END PRODUCT, PILING COST OF AGGREGATE AS PER A1-018 SHALL BE DEDUCTED.	juli Aridi	on		
** NOTE	THIS ITEM M1-013 ON MANUAL LABOUR SHOULD BE ADOPTED ON APPROVAL BY PD /CE FOR SMALL WORKS ONLY. WHEN MACHINERY IS USED FOR SPREADING AND COMPACTION, M1-012A / M1-013A SHALL BE ADOPTED DEPENDING ON SITE SITUATION.	iville			
M1-013A	USED FOR SPREADING AND COMPACTION, M1-012A / M1-013A SHALL BE ADOPTED DEPENDING ON SITE SITUATION. SPREADING WATERING AND COMPACTING GRADED 37.5 MM AGGREGATE IN STRIPS, AVERAGE WIDTH NOT EXCEEDING 1.2 METERS TO FORM A DENSE AGGREGATE BASE USING MACHINERY INCLUDING MOTOR GRADER & ROLLER HIRE CHARGES (TRANSPORT OF AGGREGATES TO BE PAID SEPARATELY)				
	(LOOSE VOLUME)[SSCM 405.1]:	CU.M *	3,112.90	80.00	3,032.90

* FOR THE RATE ON COMPACTED VOLUME, INCREASE THE LOOSE VOLUME RATE BY 42%. IF MEASUREMENT IS ON END PRODUCT, PILING COST OF AGGREGATE AS PER A1-018 SHALL BE DEDUCTED.

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION VII				
	======== ROAD SURFACE TREATMENT				
	(SAND TRANSPORT UP TO 16 KM INCLUDED IN THE RATES. TRANSPORT OF BITUMEN EMULSION / BITUMEN TO BE PAID SEPARATELY.)				
S1-001	BITUMEN(80/100) SURFACING FIRST COAT USING 2 LTR/SQ.M INCLUDING BLINDING WITH SAND AT THE RATE OF 125 SQ.M/CU.M [SSCM 503.1]:	SQ.M	415.30	69.89	345.41
S1-002	BITUMEN(80/100) SURFACING FIRST COAT, USING 2 LTR/SQ.M, INCLUDING BLINDING WITH GRAVEL WHERE SAND IS NOT AVAILABLE WITHIN 16 KM. :	SQ.M	414.35	69.89	344.46
S1-003	DOUBLE BITUMENOUS SURFACE TREATMENT WITH HOT BITUMEN (MANUAL) INCLUDING INTERNAL TRANSPORT (BINDER AND AGGREGATE PAID SEPARATELY) [SSCM 505.b1 - 505.b5 & TABLE 505-b1]:	SQ.M	336.80	108.87	227.93
S1-004	SINGLE BITUMENOUS SURFACE TREATMENT WITH HOT BITUMEN (MANUAL) INCLUDING INTERNAL TRANSPORT (BINDER AND AGGREGATE PAID SEPARATELY) [SSCM 505.b1 - 505.b5 & TABLE 505-b1]:	SQ.M	177.20	61.38	115.82
S1-005	DOUBLE BITUMENOUS SURFACE TREATMENT WITH HOT BITUMEN (MANUAL) INCLUDING INTERNAL TRANSPORT (BINDER AND AGGREGATE PAID SEPARATELY) [SSCM 505.b1 - 505.b5 & TABLE 505-b1]: SINGLE BITUMENOUS SURFACE TREATMENT WITH HOT BITUMEN (MANUAL) INCLUDING INTERNAL TRANSPORT (BINDER AND AGGREGATE PAID SEPARATELY) [SSCM 505.b1 - 505.b5 & TABLE 505-b1]: DOUBLE BITUMENOUS SURFACE TREATMENT WITH EMULSION(CRS-2)(MANUAL) INCLUDING INTERNAL TRANSPORT (BINDER AND AGGREGATE PAID SEPARATELY): SINGLE BITUMENOUS SURFACE TREATMENT WITH EMULSION(CRS-2)(MANUAL) INCLUDING INTERNAL TRANSPORT (BINDER AND AGGREGATE PAID SEPARATELY): BITUMEN(80/100) SURFACING SUBSEQUENT COAT USING 0.75 LTR/SQ.M INCLUDING BLINDING WITH SAND @ 125 SQ.M/CU.M [SSCM 503.1 (b)] :	SQ.M	331.25	108.87	222.38
S1-006	SINGLE BITUMENOUS SURFACE TREATMENT WITH EMULSION(CRS-2)(MANUAL) INCLUDING INTERNAL TRANSPORT (BINDER AND AGGREGATE PAID SEPARATELY):	SQ.M	172.75	61.38	111.37
S1-007	BITUMEN(80/100) SURFACING SUBSEQUENT COAT USING 0.75 LTR/SQ.M INCLUDING BLINDING WITH SAND @ 125 SQ.M/CU.M [SSCM 503.1 (b)]:	SQ.M	194.30	44.02	150.28
S1-008	BITUMEN(80/100) SURFACING 1ST/SUBSEQUENT COAT USING 1.0 LTR/SQ.M INCLUDING BLINDING AT THE RATE OF 125 SQ.M/CU.M (NEW WORK)[SSCM 503.1(b)]:	SQ.M	233.00	44.02	188.98
S1-009	BITUMEN(80/100) SURFACING SUBSEQUENT COAT USING 0.75 LTR/SQ.M INCLUDING BLINDING WITH GRAVEL FREE OF CLAY WHERE SAND IS NOT AVAILABLE WITHIN 16 KM [SSCM 503.2(b)]:	SQ.M	193.45	44.02	149.43
S1-010	BITUMEN(80/100) SURFACING 1ST/SUBSEQUENT COAT USING 1 LTR/SQ.M INCLUDING BLINDING WITH GRAVEL FREE OF CLAY WHERE SAND IS NOT AVAILABLE WITHIN 16 KM (NEW WORK) [SSCM 503.3(c)]:	SQ.M	232.10	44.02	188.08
S1-011	BITUMEN EMULSION(CRS-1) SURFACE TREATMENT 1ST COAT WITH 3.5 LTR/SQ.M INCLUDING BLINDING WITH SAND, @ 125 SQ.M/CU.M (MANUAL):	SQ.M	471.15	40.32	430.83

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
S1-012	BITUMEN EMULSION(CRS-1) SURFACE TREATMENT 1ST COAT WITH 3.5 LTR/SQ.M (USING TROLLEY, EMULSION), INCLUDING BLINDING WITH SAND, @ 125 SQ.M/CU.M:	SQ.M	448.20	16.73	431.47
S1-013	BITUMEN EMULSION(CRS-1) SURFACE TREATMENT SUBSEQUENT COAT USING 0.75 LTR/SQ.M, INCLUDING BLINDING WITH SAND @ 125 SQ.M/CU.M (MANUAL) :	SQ.M	134.90	18.15	116.75
S1-014	BITUMEN EMULSION(CRS-1) SURFACE TREATMENT SUBSEQUENT COAT WITH 0.75 LTR/SQ.M (USING TROLLEY, EMULSION), INCLUDING BLINDING WITH SAND @ 125 SQ.M PER CU.M:	SQ.M	126.05	8.30	117.75
S1-015	TACK COAT USING BITUMEN EMULSION(CSS-1) @ THE RATE OF 0.5 LTR/SQ.M INCLUSIVE OF BRUSHING, CLEANING ROAD SURFACE AND COST OF BITUMEN EMULSION (MANUAL) [SSCM 502.3]:	SQ.M	79.95	22.87	57.08
S1-016	TACK COAT USING BITUMEN EMULSION(CSS-1) @ THE RATE OF 0.5 LTR/SQ.M INCLUSIVE OF BRUSHING, CLEANING ROAD SURFACE AND COST OF BITUMEN EMULSION (MANUAL) [SSCM 502.3]:	LITRE	159.85	45.73	114.12
S1-017	TACK COAT USING BITUMEN EMULSION(CSS-1) @ THE RATE OF 0.75 LTR/SQ.M INCLUSIVE OF BRUSHING, CLEANING ROAD SURFACE AND COST OF BITUMEN EMULSION (MANUAL) [SSCM 502.1-503.3]:	LITRE SQ.M	108.20	22.87	85.33
S1-017A	TACK COAT USING BITUMEN EMULSION(CRS-1) @ THE RATE OF 0.5 LTR/SQ.M INCLUSIVE OF BRUSHING, CLEANING ROAD SURFACE AND COST OF BITUMEN EMULSION (MANUAL) [SSCM 502,1]:	SQ.M	80.45	22.87	57.58
S1-017B	[SSCM 502.1-503.3]: TACK COAT USING BITUMEN EMULSION(CRS-1) @ THE RATE OF 0.5 LTR/SQ.M INCLUSIVE OF BRUSHING, CLEANING ROAD SURFACE AND COST OF BITUMEN EMULSION (MANUAL) [SSCM 502:1]: TACK COAT USING BITUMEN EMULSION(CRS-1) @ THE RATE OF 0.75 LTR/SQ.M INCLUSIVE OF BRUSHING, CLEANING ROAD SURFACE AND COST OF BITUMEN EMULSION (MANUAL) [SSCM 502.1-503.3]: TACK COAT WITH CUT BACK BITUMEN(MC 30) USING 0.5 LTR/SQ.M. INCLUDING BRUSHING AND CLEANING ROAD SURFACE (MANUAL): DELETED	SQ.M	108.95	22.87	86.08
S1-018	TACK COAT WITH CUT BACK BITUMEN(MC 30) USING 0.5 LTR/SQ.M. INCLUDING BRUSHING AND CLEANING ROAD SURFACE (MANUAL):	SQ.M	131.55	45.04	86.51
S1-019	DELETED				
S1-020	TACK COAT WITH CUT BACK BITUMEN(80/100) USING 0.75 LTR/SQ.M INCLUDING BRUSHING AND CLEANING ROAD SURFACE (MANUAL)[SSCM 502.4]:	SQ.M	173.60	45.04	128.56
S1-021	ROLLING OVER BLINDING MATERIAL SPREAD OVER SUBSEQUENT BITUMEN SURFACING USING DIESEL ROLLER (8-10 TONS) [SSCM 502.4]:	SQ.M	15.10	-	15.10
S1-022	PRIME COAT WITH BITUMEN EMULSION(CSS-1) USING 1 LTR/SQ.M INCLUDING BLINDING WITH SAND AT THE RATE OF 250 SQ.M/CU.M AND BRUSHING CLEANING AND MOISTENING ROAD SURFACE:	SQ.M	155.90	26.23	129.67
S1-023	PRIME COAT WITH BITUMEN EMULSION(CSS-1) USING 1 LTR/SQ.M WITHOUT BLINDING, BUT INCLUSIVE OF BRUSHING, CLEANING AND MOISTENING ROAD SURFACE:	SQ.M	136.90	22.87	114.03
S1-024	PRIME COAT WITH CUT BACK BITUMEN(MC 30) USING 1 LTR/SQ.M INCLUDING BLINDING WITH SAND AT THE RATE OF 250 SQ.M/CU.M AND BRUSHING, CLEANING AND MOISTENING ROAD SURFACE:	SQ.M	236.85	48.40	188.45

CODE	DESCRIPTION OF ITEM	UNIT 	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
S1-025	PRIME COAT WITH CUT BACK BITUMEN(MC 30) USING 1 LTR/SQ.M WITHOUT BLINDING BUT INCLUSIVE OF BRUSHING, CLEANING, AND MOISTENING ROAD SURFACE.:	SQ.M	216.60	45.04	171.56
S1-026	SWEEPING OVER TARRED SURFACE TO ARREST BLEEDING :	SQ.M	7.00	6.72	0.28
S1-027	APPLICATION OF BITUMEN EMULSION FOR SURFACE TREATMENT USING CRS - 1 (USING PLANT) "RATE PER LITRE"	LITRE	127.30	5.66	121.64
S1-028	BLINDING THE BITUMEN SURFACING WITH SAND AT THE RATE OF 125 SQ.M PER 1 CU.M USING MATERIAL FROM STOCK PILE:	SQ.M	39.70	5.83	33.87
S1-029	SINGLE BITUMINOUS SURFACE TREATMENT WITH BITUMEN EMULSION(CRS-2) USING PLANT. (BINDER AND AGGREGATE PAID SEPARATELY) (RATE TO INCLUDE TRANSPORT COST OF AGGREGATE UP TO 16 KMS) [SSCM-505.3(d)]:	SQ.M	89.15	14.53	74.62
S1-030	DOUBLE BITUMINOUS SURFACE TREATMENT WITH BITUMEN EMULSION(CRS-2) USING PLANT. (BINDER AND AGGREGATE PAID SEPARATELY) (RATE TO INCLUDE TRANSPORT COST OF AGGREGATE UP TO 16 KMS) [SSCM-505.3(e)]:	SQ.M	180.00	29.05	150.95
S1-030A	[SSCM-505.3(d)]: DOUBLE BITUMINOUS SURFACE TREATMENT WITH BITUMEN EMULSION(CRS-2) USING PLANT. (BINDER AND AGGREGATE PAID SEPARATELY) (RATE TO INCLUDE TRANSPORT COST OF AGGREGATE UP TO 16 KMS) [SSCM-505.3(e)]: DELETED DOUBLE BITUMINOUS SURFACE TREATMENT WITH HOT BITUMEN(80/100) USING 19 MM AND 9.5 MM SINGLE SIZE SELECTED AGGREGATES ON EXISTING BITUMINOUS SURFACES USING PLANT. RATE TO INCLUDE				
S1-030B	DOUBLE BITUMINOUS SURFACE TREATMENT WITH HOT BITUMEN(80/100) USING 19 MM AND 9.5 MM SINGLE SIZE SELECTED AGGREGATES ON EXISTING BITUMINOUS SURFACES USING PLANT. RATE TO INCLUDE ALL LABOUR, MATERIAL, PLANT AND TRANSPORT COST OF AGGREGATE UP TO 16 KM. (TRANSPORT OF BINDER AND ADDITIONAL TRANSPORT OF AGGREGATE TO BE PAID SEPARATELY)[SSCM 505b.5(e)]:	SQ.M	561.50	29.05	532.45
NOTE:	QUANTITIES OF AGGREGATES AND BINDER (PEN GRADE BITUMEN) FOR DBST [SSCM 505.5] 1ST SEAL 19 MM AGGREGATE - BINDER PENGRADE BITUMEN 2ND SEAL 12.5 MM AGGREGATE - BINDER PENETRATION GRADE BITUMEN 1ST SEAL 12.5 MM AGGREGATE - BINDER PENGRADE BITUMEN	AGGREGATE CU.M/100 M ² 1.3 - 1.7 0.7-1.0 1.0 - 1.3	BINDER LTR/SQ.M 0.65-0.85 1.0-1.3		
	2ND SEAL 9.5 MM AGGREGATE - BINDER PENETRATION GRADE BITUMEN	0.55-0.75	0.75-1.05		

CODE 	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
S1-031	SUPPLY, LAY AND COMPACT ASPHALT CONCRETE (19 MM, 60/70 BINDER 4.7% **) - DENSE (PLANT MADE) IN WEARING SURFACE OF SMALL WORKS SUCH AS BRIDGE DECKING, REINSTATEMENT OF TRENCHES ETC. (SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY.)[SSCM-506]	M.TON	18,109.20	1,975.00	16,134.20
NOTE**	(FOR BINDER CONTENTS SEE GENERAL NOTES - SECTION 29. 8				
:	* AVERAGE 0.6270 CU.M OF AGGREGATE IS REQUIRED FOR 1.0 M.TON OF PREMIX.				
S1-032	LAY AND COMPACT ASPHALT CONCRETE (37.5MM, 60/70 BINDER, 3.5% **) - BOUND BASE MATERIAL (PLANT MADE) IN SMALL WORKS SUCH AS BRIDGE DECKING, REINSTATEMENT OF TRENCHES ETC. (SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY.)[SSCM-506]	M.TON	15,988.20	1,975.00	14,013.20
NOTE**	FOR BINDER CONTENTS SEE GENERAL NOTES - SECTION 29. 8				
:	* AVERAGE 0.6270 CU.M OF AGGREGATE IS REQUIRED FOR 1.0 M.TON OF PREMIX.	: 2	ijor		
S1-033	TO BE PAID SEPARATELY.)[SSCM-506] FOR BINDER CONTENTS SEE GENERAL NOTES - SECTION 29. 8 * AVERAGE 0.6270 CU.M OF AGGREGATE IS REQUIRED FOR 1.0 M.TON OF PREMIX. SUPPLY, LAY AND COMPACT CUTBACK ASPHALT CONCRETE COLD MIX WITH MC30 (19 MM AGGREGATE, 15% CUT BACK 60/70 BINDER 5.5%**) DENSE (PLANT MADE) IN SMALL WORKS SUCH AS BRIDGE DECKING, REINSTATEMENT OF TRENCHES ETC. (TRANSPORT OF PREMIX TO BE PAID SEPARATELY.)[SSCM-507] (FOR BINDER CONTENTS SEE GENERAL NOTES - SECTION 29. 8 * AVERAGE 0.6270 CU.M OF AGGREGATE IS REQUIRED FOR 1.0 M.TON OF PREMIX. SUPPLY, LAY AND COMPACT IMULSIFIED ASPHALT CONCRETE COLD MIX WITH BITUMEN EMULSION CSS-1(6.67%** BY WCT OF AGG.) AND	M.TON	19,726.20	1,975.00	17,751.20
NOTE**	(FOR BINDER CONTENTS SEE GENERAL NOTES - SECTION 29. 8				
S1-033A	* AVERAGE 0.6270 CU.M OF AGGREGATE IS REQUIRED FOR 1.0 M.TON OF PREMIX. SUPPLY, LAY AND COMPACT IMULSIFIED ASPHALT CONCRETE COLD				
	MIX WITH BITUMEN EMULSION CSS-1(6.67%** BY WGT OF AGG.) AND 19 MM AGGREGATE, DENSE (PLANT MADE) IN SMALL WORKS SUCH AS BRIDGE DECKING, REINSTATEMENT OF TRENCHES ETC. [TRANSPORT OF PREMIX(COLD MIX) TO BE PAID SEPARATELY.] [SSCM-507]	M.TON	14,437.20	1,975.00	12,462.20
NOTE**	(FOR BINDER CONTENTS SEE GENERAL NOTES - SECTION 29. 8				
	* AVERAGE 0.6270 CU.M OF AGGREGATE REQUIRED FOR 1.0 M.TON OF PREMIX.				
S1-034	LAY AND COMPACT ASPHALT CONCRETE USING PAVER.(COST OF SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY.):	M.TON	1,794.70	494.38	1,300.33
S1-034A	LAY AND COMPACT ASPHALT CONCRETE MANUALY.(COST OF SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY.):	M.TON	1,701.60	1,229.17	472.43
S1-035	SURFACING (SAND SEALING - MANUAL) USING BITUMEN EMULSION CRS-1, AT THE RATE OF 1 LTR/SQ.M INCLUDING PREPARING SURFACE, BLINDING WITH SAND AT THE RATE OF 4 CU.M/500 SQ.M AND PRESSING WITH IMPROVISED HAND ROLLERS: (PATCING POT HOLES IF NECESSARY & EXTERNAL TRANSPORT TO PAY				
	SEPARATELY.)	SQ.M	169.85	18.15	151.70
S1-035A	PATCHING MINOR POT HOLES USING SAND, BITUMEN EMULSION MIX 1:8 WHERE NECESSARY, PRIOR TO SAND SEALING	SQ.M	26.70	14.78	11.92

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
S1-036*	SAND SEALING WITH BITUMEN EMULSION CRS-1 AT THE RATE OF 1 LTR/SQ.M USING PLANT, INCLUDING BRUSHING, CLEANING BLINDING WITH SAND AT THE RATE OF 125 SQ.M/CU.M AND ROLLING WITH PNEUMATIC ROLLER & INTERNAL TRANSPORT [SSCM 504]: (PATCHING POT HOLES IF NECESSARY & EXTERNAL TRANSPORT TO PAY SEPARATELY.)	SQ.M	184.90	13.79	171.11
S1-036A*	CHIP SEALING WITH BITUMEN EMULSION CRS-1 AT THE RATE OF 1.25 LTR/SQ.M USING PLANT, INCLUDING BRUSHING, CLEANING BLINDING) (PATCHING POT HOLES IF NECESSARY & EXTERNAL TRANSPORT TO PAY SEPARATELY.)	SQ.M	205.40	8.13	197.28
S1-036B*	FOG SEALING WITH BITUMEN EMULSION CRS-1 AT THE RATE OF 1.5 LTR/SQ.M USING PLANT, INCLUDING BRUSHING, CLEANING BLINDING) (PATCHING POT HOLES IF NECESSARY & EXTERNAL TRANSPORT TO PAY SEPARATELY.)	SQ.M	248.55	8.13	240.43
S1-036C*	CRACK SEALING WITH BITUMEN EMULSION CSS-1 AT THE RATE OF 1.25 LTR/SQ.M USING PLANT, INCLUDING BRUSHING, CLEANING BLINDING) (PATCHING POT HOLES IF NECESSARY & EXTERNAL TRANSPORT TO PAY SEPARATELY.)	SQ.M	216.70	8.13	208.58
* NOTE :	THE ABOVE RATE IS APPLICABLE FOR PAYMENT ONLY IF CHIP SPREADER(SELF PROPELLED) AND PNEUMATIC ROLLER ARE USED FOR THE CONSTRUCTION. OTHERWISE APPROVED SSR SHOULD BE ADOPTED.	Ail Pair			
S1-037	CRACK SEALING WITH BITUMEN EMULSION CSS-1 AT THE RATE OF 1.25 LTR/SQ.M USING PLANT, INCLUDING BRUSHING, CLEANING BLINDING) (PATCHING POT HOLES IF NECESSARY & EXTERNAL TRANSPORT TO PAY SEPARATELY.) THE ABOVE RATE IS APPLICABLE FOR PAYMENT ONLY IF CHIP SPREADER(SELF PROPELLED) AND PNEUMATIC ROLLER ARE USED FOR THE CONSTRUCTION. OTHERWISE APPROVED SSR SHOULD BE ADOPTED. RECONSTRUCT BASE WITH PENETRATION MACADAM USING NOMINAL SIZE 50 MM AGGREGATE AND 19 MM KEY AGGREGATE FROM STOCK PILES, TO A COMPACTED THICKNESS OF 75 MM, ON EXISTING PAVEMENTS. [SSCM 406] (COST OF BINDER, AND AGGREGATE INCLUDING TRANSPORT TO BE PAID SEPARATELY) : RECONSTRUCT BASE WITH PENETRATION MACADAM USING NOMINAL SIZE 37.5 MM AGGREGATE AND 12.5 MM KEY AGGREGATE FROM STOCK PILES, TO A COMPACTED THICKNESS OF 75 MM, ON EXISTING PAVEMENTS, [SSCM 406] (COST OF BINDER, AND AGGREGATE INCLUDING TRANSPORT TO BE PAID SEPARATELY) : CORRECTION OF CORRUGATIONS, DEPRESSIONS AND CAMBERING ROAD SURFACES USING ASPHALT CONCRETE COMPACTED BY VIBRATING ROLLER INCLUDING INTERNAL TRANSPORT. (APPLICATION OF TACK COAT AND SUPPLY OF ACCURANT AND SUPPLY OF ADDITIONAL SUPPLY OF	SQ.M	231.25	130.35	100.90
S1-038	RECONSTRUCT BASE WITH PENETRATION MACADAM USING NOMINAL SIZE 37.5 MM AGGREGATE AND 12.5 MM KEY AGGREGATE FROM STOCK PILES, TO A COMPACTED THICKNESS OF 75 MM, ON EXISTING PAVEMENTS. [SSCM 406] (COST OF BINDER, AND AGGREGATE INCLUDING TRANSPORT TO BE PAID SEPARATELY) :	SQ.M	162.70	92.57	70.13
S1-039	CORRECTION OF CORRUGATIONS, DEPRESSIONS AND CAMBERING ROAD SURFACES USING ASPHALT CONCRETE COMPACTED BY VIBRATING ROLLER INCLUDING INTERNAL TRANSPORT. (APPLICATION OF TACK COAT AND SUPPLY OF ASPHALT CONCRETE TO BE PAID SEPARATELY):	M.TON	3,167.90	2,020.83	1,147.07
S1-040*	SAND SEALING WITH BITUMEN EMULSION CRS-2 AT THE RATE OF 1.0 LTR/SQ.M USING PLANT, AND BLINDING WITH SAND AT THE RATE OF 125 SQ.M/CU.M ON D.B.S.T / S.B.S.T. (TRIPLE SEAL) INCLUDING INTERNAL TRANSPORT(SSCM 504) (BINDER TRANSPORT TO SITE SHALL BE PAID SEPARATELY)	SQ.M	181.95	11.37	170.58
* NOTE	: THIS ITEM SHOULD BE USED ONLY FOR SAND SEALING ON ROAD SURFACE AFTER D.B.S.T. / S.B.S.T. WORK AND USE OF PNEUMATIC ROLLER IS ESSENTIAL. IF EMULSION AND/OR THE RATE OF APPLICATION OR THE METHOD OF SAND SPREADING TO BE CHANGED, S.S.R. SHALL BE PREPARED AND APPROVED.				
S1-041	SLURRY SEALING TO A THICKNESS OF 6 MM, USING MACHINERY WITH EMULSION (USING CSS-1H) AS THE BINDER (TRANSPORT OF AGGREGATE TO PAY SEPARATELY:	SQ.M	192.10	8.15	183.95
S1-042	SLURRY SEALING TO A THICKNESS OF 6 MM USING CONCRETE MIXTURE, MANUAL WITH EMULSION (USING CSS-1H) AS THE BINDER (TRANSPORT OF AGGREGATE TO PAY SEPARATELY):	SQ.M	723.40	183.33	540.07

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION VIII				
	ROAD SURFACE MAINTENANCE				
MN1-001	PATCHING WITH HOT BITUMEN(60/70) USING 14 LITRES PER 1/2 KM (SSCM 1102.1 - 1102.3):	1/2 KM	4,645.10	1,762.70	2,882.40
MN1-002	PATCHING WITH HOT BITUMEN(60/70) USING 21 LTRS. PER 1/2 KM.:	1/2 KM	6,967.65	2,644.04	4,323.61
MN1-003	PATCHING WITH HOT BITUMEN(60/70) USING 28 LTRS. PER 1/2 KM.:	1/2 KM	9,290.20	3,525.39	5,764.81
MN1-004	PATCHING WITH HOT BITUMEN(60/70) USING 35 LTRS. PER 1/2 KM.:	1/2 KM	11,612.75	4,406.74	7,206.01
MN1-005	USING 42 LTRS, PFR 1/2 KM.:	1/2 KM	13,935.30	5,288.09	8,647.21
MN1-006	PATCHING WITH HOT BITUMEN(60/70) USING 49 LTRS. PER 1/2 KM.:	1/2 KM	16,257.85	6,169.43	10,088.42
MN1-007	PATCHING WITH HOT BITUMEN(60/70) USING 56 LTRS. PER 1/2 KM.:	1/2 KM	18,580.40	7,050.78	11,529.62
MN1-008	EXTENSIVE PATCHING FOR EVERY ADDITIONAL 7 LTRS. HOT BITUMEN(60/70)	1/2 KM	2,322.55	881.35	1,441.20
MN1-009	PATCHING WITH HOT BITUMEN(60/70) USING 49 LTRS. PER 1/2 KM.: PATCHING WITH HOT BITUMEN(60/70) USING 56 LTRS. PER 1/2 KM.: EXTENSIVE PATCHING FOR EVERY ADDITIONAL 7 LTRS. HOT BITUMEN(60/70) PATCHING WITH BITUMEN EMULSION (CRS-1) USING 14 LTRS PER 1/2 KILO METRE: PATCHING WITH BITUMEN EMULSION CRS-1 USING 21 LTRS. PER 1/2 KM.: PATCHING WITH BITUMEN EMULSION CRS-1 USING 28 LTRS. PER 1/2 KM.:	1/2 KM	2,976.90	742.19	2,234.71
MN1-010	PATCHING WITH BITUMEN EMULSION CRS-1 USING 21 LTRS. PER 1/2 KM.:	1/2 KM	4,465.35	1,113.28	3,352.07
MN1-011	PATCHING WITH BITUMEN EMULSION CRS-1 USING 28 LTRS. PER 1/2 KM.:	1/2 KM	5,953.85	1,484.38	4,469.48
MN1-012	PATCHING WITH BITUMEN EMULSION CRS-1 USING 35 LTRS. PER 1/2 KM.:	1/2 KM	7,442.30	1,855.47	5,586.83
MN1-013	USING 42 LTRS. PER 1/2 KM.:	1/2 KM	8,930.75	2,226.56	6,704.19
MN1-014	PATCHING WITH BITUMEN EMULSION CRS-1 USING 49 LTRS. PER 1/2 KM.:	1/2 KM	10,419.20	2,597.66	7,821.54

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
MN1-015	PATCHING WITH BITUMEN EMULSION, CRS-1 USING 56 LTRS. PER 1/2 KM.:	1/2 KM	11,907.65	2,968.75	8,938.90
MN1-016	EXTENSIVE PATCHING FOR EVERY ADDITIONAL 7 LTRS. BITUMEN EMULSION, CRS-1:	1/2 KM	1,488.45	371.09	1,117.36
MN1-017	50 MM - 19.5 MM AGGREGATE ROLLER PATCHING:	CU.M	6,202.85	3,705.88	2,496.97
MN1-018	50 MM - 19.5 MM AGGREGATE STAMPED PATCHING:	CU.M	7,814.60	7,570.42	244.18

* * *

White thy of Transport, Highways, Ports and Civil Aviation

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION IX				
	ROAD SIDE AND DRAINAGE SYSTEM (SSCM 701.3)				
	(* RATE TO INCLUDE SPREADING THE RESULTING MATERIALS SUITABLY IN THE VICINITY UNLESS OTHERWISE DIRECTED.)				
DR1-001	CUTTING NEW SIDE DRAINS IN ORD. SOIL :*	CU.M	1,286.55	1192.58	93.97
DR1-002	CUTTING NEW SIDE DRAINS IN MED. SOIL :*	CU.M	1,784.55	1678.45	106.10
DR1-003	CUTTING NEW SIDE DRAINS IN HARD SOIL :*	CU.M	2,282.55	2164.31	118.24
DR1-004	CUTTING NEW SIDE DRAINS IN SOFT ROCK :*	CU.M	2,531.55	2407.24	124.31
DR1-005	CUTTING NEW SIDE DRAINS IN UNCLASSIFIED SOIL :*	CU.M	1,784.55	1678.45	106.10
DR1-005A	CUTTING SIDE DRAINS OF STD. DIMENSIONS IN UNCLASSIFIED SOIL USING (BACK HOE J.C.B.) INCLUDING SHAPING, TRIMMING AND LEVELLING BOTTOM MANUALLY.	CU.M	803.15	484.29	318.86
DR1-006	CUTTING NEW SIDE DRAINS IN ROCK :*	CU.M	6,351.65	4461.13	1,890.52
DR1-007	IN UNCLASSIFIED SOIL USING (BACK HOE J.C.B.) INCLUDING SHAPING, TRIMMING AND LEVELLING BOTTOM MANUALLY. CUTTING NEW SIDE DRAINS IN ROCK :* TURFING (EXCLUDING ROYALTY, TRANSPORT AND WATERING AND MAINTENANCE) [SSCM 802.3a]: WATERING AND MAINTAINING TURF FOR THREE MONTHS INCLUDING TRANSPORT OF WATER: LEVELLING & TRIMMING EARTH :* CLEARING SILT ETC. FROM KERBS & CHANNELS (CSCM 12065) :*	SQ.M	301.35	263.16	38.19
DR1-008	WATERING AND MAINTAINING TURF FOR THREE MONTHS INCLUDING TRANSPORT OF WATER:	SQ.M	329.95	210.00	119.95
DR1-009	LEVELLING & TRIMMING EARTH :*	SQ.M	35.95	33.78	2.17
DR1-010	CLEARING SILT ETC. FROM KERBS & CHANNELS (SSCM 12053) :*	L.M	21.80	20.83	0.97
DR1-011	CUTTING SCUPPER DRAINS ON ANY SOIL OTHER THAN ROCK TO AN AVERAGE WIDTH OF .75 METRE, WITH PROPER GRADIENT AND AN AVERAGE DEPTH OF 100 MM (S.S.C.M. 1304.3) :*	L.M	159.40	152.78	6.62
DR1-012	CLEANING AND DESILTING OF CULVERTS (SSCM 1303.3) :*	NO.	443.75	416.67	27.08

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
DR1-013	CLEANING CHOKED CULVERTS (WITH HEAD ROOM > 1 M **) :*	CU.M	1,846.30	1766.78	79.52
*:	* IF THE CULVERT HEAD ROOM IS LESS THAN 1 METRE, WORK SHALL BE CARRIED OUT ON DAY WORKS BASIS.				
DR1-014	CLEANING DESILTING EXISTING SIDE DRAINS AND LEAD UP DRAINS TO PROPER SHAPE AND GRADIENT AND TRANSPORT OF EXCAVATED MATERIALS FROM				
	ROAD SIDE UP TO 100 M. :*	L.M	54.20	52.11	2.09
DR1-015	CLEARING INLETS AND OUTLETS OF CULVERTS :*	NO.	399.40	375.00	24.40

White thy of Transport, Highways, Ports and Civil Aviation

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION X				
	======= BRIDGES, CULVERTS & RETAINING WALLS ETC.				
	·				
ST1-001	DEMOLISHING DRY COURSED MASONRY INCLUDING STACKING OR LOADING. [SSCM 202.2]:	CU.M	5,523.40	5,388.69	134.71
ST1-002	DEMOLISHING COURSED MASONRY IN CEMENT MORTAR INCLUDING STACKING OR LOADING.:	CU.M.	6,428.90	6,272.08	156.82
ST1-003	DEMOLISHING RANDOM RUBBLE MASONRY IN CEMENT MORTAR INCLUDING STACKING OR LOADING.:	CU.M	2,897.55	2,826.86	70.69
ST1-003A	DEMOLISHING BRICK MASONRY IN CEMENT MORTAR INCLUDING STACKING OR LOADING.:	CU.M	2,807.00	2,738.52	68.48
ST1-004	RANDOM RUBBLE MASONRY, 150-225 MM RUBBLE IN CEMENT SAND MORTAR 1:6 (EXCLUDING TRANSPORT OF RUBBLE & PILING) [SSCM 1006.3]:	CU.M	17,452.85	9,540.64	7,912.21
ST1-005	RANDOM RUBBLE MASONRY, 150-225 MM RUBBLE IN CEMENT SAND MORTAR 1:5 (EXCLUDING TRANSPORT OF RUBBLE & PILING) [SSCM 1006.3]:	CU.M. Pail	18,058.20	9,540.64	8,517.56
ST1-006	RANDOM RUBBLE MASONRY IN CEMENT SAND MORTAR 1:6 WITH AVAILABLE RUBBLE 150-225 MM:	CU.M	14,346.30	9,540.64	4,805.66
ST1-007	RANDOM RUBBLE MASONRY IN CEMENT SAND MORTAR 1:5 WITH AVAILABLE RUBBLE 150-225 MM:	CU.M	14,951.70	9,540.64	5,411.06
ST1-008	IN CEMENT SAND MORTAR 1:5 (EXCLUDING TRANSPORT OF RUBBLE & PILING) [SSCM 1006.3]: RANDOM RUBBLE MASONRY IN CEMENT SAND MORTAR 1:6 WITH AVAILABLE RUBBLE 150-225 MM: RANDOM RUBBLE MASONRY IN CEMENT SAND MORTAR 1:5 WITH AVAILABLE RUBBLE 150-225 MM: DRY MASONRY WITH AVAILABLE HEAVY RUBBLE OR BOULDERS (SSCM 1006.3 (B): DRY RANDOM MASONRY WITH RUBBLE 150-225 MM (EXCLUDING TRANSPORT OF RUBBLE & PILING):	CU.M	8,375.65	8,171.38	204.27
ST1-009	DRY RANDOM MASONRY WITH RUBBLE 150-225 MM (EXCLUDING TRANSPORT OF RUBBLE & PILING):	CU.M	9,527.40	6,537.10	2,990.30
ST1-010	DRY RANDOM MASONRY WITH AVAILABLE RUBBLE 150-225 MM:	CU.M	6,700.55	6,537.10	163.45
ST1-011	PACKING AVAILABLE RUBBLE AND AGGREGATE FILTER LAYERS BEHIND MASONRY WALLS:	CU.M	1,619.90	1,545.94	73.96
ST1-012	CLAY PUDDLED & LAID BEHIND MASONRY WALLS (EXCL. TRANSPORT OF CLAY) (SSCM 705.3):	CU.M	3,279.80	3,136.04	143.76
ST1-013	GROUTING COURSED STONE MASONRY JOINTS WITH CEMENT SAND MORTAR 1:3 (SSCM 804.2(C):	SQ.M	690.25	486.84	203.41
ST1-014	GROUTING RUBBLE PAVING WITH CONCRETE CLASS C, 1:2:4(19 MM) (EXCL. TRANSPORT OF AGGR. FOR CONCRETE & PILING):	CU.M	2,982.50	1,587.90	1,394.60
ST1-015	GROUTING RUBBLE PAVING WITH CEMENT SAND MORTAR (1:3):	SQ.M	1,130.95	730.26	400.69

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-016	FORMING WEEP HOLES IN MASONRY CONSTRUCTION (LABOUR ONLY) [SSCM 706.3] :	NO.	640.65	625.00	15.65
ST1-017	FORMING WEEP HOLES USING P.V.C. PIPES OF INT. DIA. NOT LESS THAN 100 MM. COMPLETE WITH DRIPLEDGE AND SURROUND FINISH SMOOTH:	METRE	1,486.10	333.33	1,152.77
ST1-018	SHORING WITH 37.5 MM THICK CLASS II TIMBER PLANKS UP TO 3 M DEPTH.:	SQ.M	1,517.55	625.00	892.55
ST1-019	SUPPLYING & FIXING CLASS II TIMBER STRUTS ETC. FOR SHORING UP TO 3 M DEPTH.:	CU.DECI.M	123.05	97.22	25.83
ST1-020	SUPPLYING AND FIXING CLASS II TIMBER IN SHORING UP TO 3 M DEPTH	SQ.M	1,823.30	866.62	956.68
ST1-021	LIFTING SOIL FOR EVERY 1.5 M BEYOND THE INITIAL 1.5 M:	CU.M / LIFT	905.50	883.39	22.11
ST1-022	LIFTING WEDGE STONES EVERY 1.5 M BEYOND THE INITIAL 1.5 M:	CU.M / LIFT	2,716.45	2,650.18	66.27
ST1-023	LIFTING RUBBLE OR CONCRETE EVERY 1.5 M BEYOND THE INITIAL 1.5 M:	CU.M / LIFT	1,358.20	1,325.09	33.11
ST1-024	LIFTING RUBBLE OR CONCRETE EVERY 1.5 M BEYOND THE INITIAL 1.5 M: LOWERING WEDGED STONES EVERY 1.5 M BEYOND THE INITIAL 1.5 M: LOWERING RUBBLE OR CONCRETE FOR EVERY 1.5 M BEYOND THE INITIAL 1.5 M: RENDERING 12.5 MM THICK IN CEMENT SAND MOTAR 1:2 MIX (ROUGH): RENDERING 12.5 MM THICK IN CEMENT SAND MORTAR 1:2 MIX (SMOOTH FINISH): RENDERING 19 MM THICK IN CEMENT SAND MORTAR 1:2 MIX (ROUGH):	CU.M / LOWER	1,810.95	1,766.78	44.17
ST1-025	LOWERING RUBBLE OR CONCRETE FOR EVERY 1.5 M BEYOND THE INITIAL 1.5 M:	CU.M / LOWER	905.50	883.39	22.11
ST1-026	RENDERING 12.5 MM THICK IN CEMENT SAND MOTAR 1:2 MIX (ROUGH):	SQ.M	1,153.70	745.97	407.73
ST1-027	RENDERING 12.5 MM THICK IN CEMENT SAND MORTAR 1:2 MIX (SMOOTH FINISH):	SQ.M	1,355.25	846.77	508.48
ST1-028	RENDERING 19 MM THICK IN CEMENT SAND MORTAR 1:2 MIX (ROUGH):	SQ.M	1,615.45	994.62	620.83
ST1-029	RENDERING 19 MM THICK IN CEMENT SAND MORTAR 1:2 MIX (SMOOTH FINISH):	SQ.M	1,817.00	1,095.43	721.57
ST1-030	RENDERING 12.5 MM THICK IN CEMENT SAND MORTAR 1:3 MIX (ROUGH):	SQ.M	1,093.55	745.97	347.58
ST1-031	RENDERING 12.5 MM THICK IN CEMENT SAND MORTAR 1:3 MIX (SMOOTH FINISH):	SQ.M	1,310.70	846.77	463.93
ST1-032	RENDERING 19 MM THICK IN CEMENT SAND MORTAR 1:3 MIX (ROUGH):	SQ.M	1,528.60	994.62	533.98

	MONANDALA DISTRICT				
CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-033	RENDERING 19 MM THICK IN CEMENT SAND				
311-055	MORTAR 1:3 MIX (SMOOTH FINISH):	SQ.M	1,731.30	1,095.43	635.87
ST1-034 ³	MIXING & LAYING MANUALLY, CEMENT CONCRETE				
	1:4:8(50 MM) (VOLUME BATCHING) USING				
	CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING) (SSCM 1001.4):	CU.M	16,766.10	6,824.20	9,941.90
	or noncome an intro (oscin iouni).	CO 1	10,7 00.10	0,02 1120	3/3 11.30
ST1-035 *	MIXING & LAYING USING CONCRETE MIXER,				
511 055	CEMENT CONCRETE 1:4:8(50 MM) (VOLUME				
	BATCHING) USING CRUSHER RUN AGGREGATE				
	(EXCL. TRANSPORT OF AGGREGATE & PILING) (SSCM 1001.8-1001.9):	CU.M	16,063.95	5,294.12	10,769.83
			,	,	· ·
ST1-036 *	MIXING & LAYING MANUALLY CEMENT CONCRETE				
311 030	1.4.9/FO MM\ WITH 200/ DILIMS(V/OLLIME				
	BATCHING), USING CRUSHER RUN AGGREGATE.	CLLAA	46 204 45	7 707 60	0.506.05
	(EXCL. TRANSPORT OF AGGREGATE & PILING) :	CU.M	16,304.45	7,707.60	8,596.85
CT4 027 V	ANYTHIS & LAVING LIGHIG CONCRETE MIVED				
S11-03/ 1	MIXING & LAYING USING CONCRETE MIXER, CEMENT CONCRETE 1:4:8(50 MM) WITH 20%	+. (20		
	PLUMS(VOLUME BATCHING) USING				
	CRUSHER RUN AGGREGATE.(EXCLUDING TRANSPORT OF AGGREGATE & PILING):	CHMP	14,710.90	5,294,12	0.416.70
	TRANSPORT OF AGGREGATE & PILING).	CO.M	14,/10.90	5,294.12	9,416.78
CT1 020 ×	BATCHING), USING CRUSHER RUN AGGREGATE. (EXCL. TRANSPORT OF AGGREGATE & PILING): MIXING & LAYING USING CONCRETE MIXER, CEMENT CONCRETE 1:4:8(50 MM) WITH 20% PLUMS(VOLUME BATCHING) USING CRUSHER RUN AGGREGATE. (EXCLUDING TRANSPORT OF AGGREGATE & PILING): MIXING & LAYING MANUALLY, CEMENT CONCRETE 1:3:6(37.5 MM) WITH 20% PLUMS(VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING): MIXING & LAYING USING CONCRETE MIXER, CEMENT CONCRETE 1:3:6(37.5 MM) WITH 20% PLUMS(VOLUME BATCHING) USING CRUSHER RUN AGGREGATE.(EXCL.TRANSPORT OF AGGREGATE & PILING): MIXING & LAYING MANUALLY, CEMENT CONCRETE 1:3:6(37.5 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT	Ci/J,			
311-030	MIXING & LAYING MANUALLY, CEMENT CONCRETE 1:3:6(37.5 MM) WITH 20% PLUMS(VOLUME				
	BATCHING) USING CRUSHER RUN AGGREGATE				
	(EXCL. TRANSPORT OF AGGREGATE & PILING):	CU.M	17,325.80	7,707.60	9,618.20
	20 01/201				
ST1-039 *	MIXING & LAYING USING CONCRETE MIXER,				
	CEMENT CONCRETE 1:3:6(37.5 MM) WITH 20% PLUMS(VOLUME BATCHING) USING				
	CRUSHER RUN AGGREGATÉ.(EXCL.TRANSPORT OF				
	AGGREGATE & PILING):	CU.M	15,715.80	5,294.12	10,421.68
ST1-040 ³	MIXING & LAYING MANUALLY, CEMENT CONCRETE 1:3:6(37.5 MM) (VOLUME BATCHING) USING				
	CRUSHER RUN AGGREGATE (EXCL. TRANSPORT				
	OF AGGREGATE & PILING) (SSCM 1001.4):	CU.M	19,581.50	7,707.60	11,873.90
ST1-041 ³	MIXING & LAYING USING CONCRETE MIXER,				
	CEMENT CONCRETE 1:3:6(37.5 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE				
	(EXCL. TRANSPORT OF AGGREGATE &				
	PILING):	CU.M	17,977.20	5,294.12	12,683.08
* NOTE:	WHEN HAND BROKEN AGGREGATE(50 MM OR 37.5 MM) ARE USED,				
	INPLACE OF CRUSHER RUN AGGREGATE, ON APPROVAL BY PD/CE SSRR TO BE PREPARED BASED ON THE SAME NORMS.				
ST1-042	MIXING & LAYING MANUALLY, CEMENT CONCRETE				
- · - v · -	1:3:6(19 MM) (VOLUME BATCHING) USING				
	CRUSHED AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING) (SSCM 1001.4):	CU.M	10 630 RE	7 707 60	11 923 25
	OF AGGREGATE & PILLING) (SOCIA 1001.4).	CU.IM	19,630.85	7,707.60	11,923.25

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-043	MIXING & LAYING USING CONCRETE MIXER, CEMENT CONCRETE 1:3:6(19 MM) (VOLUME BATCHING) USING CRUSHED AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING):	CU.M	17,882.45	5,294.12	12,588.33
ST1-044 *	* MIXING & LAYING MANUALLY CEMENT CONCRETE 1:2:4(37.5 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING):	CU.M	21,568.50	7,707.60	13,860.90
ST1-045 *	* MIXING & LAYING USING CONCRETE MIXER, CEMENT CONCRETE 1:2:4(37.5 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING): **	CU.M	20,186.50	5,294.12	14,892.38
* NOTE:	** (RATE INCLUDES VIBRATOR COST) : WHEN HAND BROKEN AGGREGATE(50 MM OR 37.5 MM) ARE USED, INPLACE OF CRUSHER RUN AGGREGATE, ON APPROVAL BY PD/CE SSRR TO BE PREPARED BASED ON THE SAME NORMS.				
ST1-046	MIXING & LAYING MANUALLY CEMENT CONCRETE 1:2:4(19 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING):	CU.M Pyloži	21,449.45	7,707.60	13,741.85
ST1-047	MIXING & LAYING USING CONCRETE MIXER, CEMENT CONCRETE 1:2:4(19 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING): **	CU.M	20,059.35	5,294.12	14,765.23
** ST1-048	* (RATE INCLUDES VIBRATOR COST) MIXING & LAYING USING CONCRETE MIXER		7	., .	,
	E WHEN HAND BROKEN AGGREGATE(50 MM OR 37.5 MM) ARE USED, INPLACE OF CRUSHER RUN AGGREGATE, ON APPROVAL BY PD/CE SSRR TO BE PREPARED BASED ON THE SAME NORMS. MIXING & LAYING MANUALLY CEMENT CONCRETE 1:2:4(19 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING): MIXING & LAYING USING CONCRETE MIXER, CEMENT CONCRETE 1:2:4(19 MM) (VOLUME BATCHING) USING CRUSHER RUN AGGREGATE (EXCL. TRANSPORT OF AGGREGATE & PILING): ** (RATE INCLUDES VIBRATOR COST) MIXING & LAYING USING CONCRETE MIXER (W/BATCHING), CEMENT CONCRETE GRADE 25(19 MM) USING CRUSHER RUN AGGREGATES IN FOUNDATIONS AND FLOORS. (EXCLUDING TRANSPORT OF AGGREGATE & PILING): SEE GENERAL NOTES: SECTION 33. 7	CU.M	21,660.65	5,294.12	16,366.53
	MIXING & LAYING USING CONCRETE MIXER [W/BATCHING], CEMENT CONCRETE GRADE 25(70% 37.5 + 30% 19 MM) USING CRUSHER RUN AGGREGATES (EXCLUDING TRANSPORT OF AGGREGATE & PILING) :*	CU.M	20,515.25	5,294.12	15,221.13
k	SEE GENERAL NOTES: SECTION 33. 7				
ST1-049	MIXING & LAYING USING CONCRETE MIXER (W/BATCHING) CEMENT CONCRETE GRADE 30(19 MM), WITH CRUSHER RUN AGGREGATE. (EXCLUDING TRANSPORT OF AGGREGATE & PILING):	CU.M	24,434.10	5,294.12	19,139.98
k	* SEE GENERAL NOTES: SECTION 33. 7				

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-050	MIXING & LAYING USING CONCRETE MIXER(W/BATCHING), CEMENT CONCRETE GRADE 40(19 MM), WITH CRUSHER RUN AGGREGATE. (EXCLUDING TRANSPORT OF AGGREGATE AND PILING):	CU.M	27,185.20	5,294.12	21,891.08
,	* SEE GENERAL NOTES: SECTION 33. 7				
ST1-051	MIXING & LAYING CEMENT CONCRETE BY HAND:	CU.M	8,025.95	7,707.60	318.35
ST1-052	MIXING & LAYING CEMENT CONCRETE BY POWER DRIVEN CONCRETE MIXER V/BATCHING:	CU.M	6,426.90	5,294.12	1,132.78
ST1-053	CURING OF CONCRETE DECKS, SLABS, BEAMS, WALLS ETC. [SSCM 1011.11]:	SQ.M/DAY	45.15	12.76	32.39
ST1-054	FABRICATE & LAY M.S. BARS AS REINFORCEMENT(INCL. TRANSPORT):	KG	436.20	130.00	306.20
ST1-055	FABRICATE & LAY TOR STEEL AS REINFORCEMENT(INCL. TRANSPORT):	KG Nidi	443.20	130.00	313.20
ST1-056	CUTTING & LAYING REINFORCEMENT FABRIC (EXCLUDING COST OF REINFORCEMENT FABRIC):	SQ.M	362.35	351.35	11.00
ST1-057	SUPPLYING & FIXING 25 MM THICK PLANKS OF CLASS II TIMBER AS SHUTTERING, INCLUDING REMOVING [SSCM 1008.3 (b)]:	SQ.M	1,887.05	672.04	1,215.01
ST1-057A	CUTTING & LAYING REINFORCEMENT FABRIC (EXCLUDING COST OF REINFORCEMENT FABRIC): SUPPLYING & FIXING 25 MM THICK PLANKS OF CLASS II TIMBER AS SHUTTERING, INCLUDING REMOVING [SSCM 1008.3 (b)]: SUPPLYING & FIXING 25 MM THICK PLANKS OF CLASS II TIMBER AS SHUTTERING FOR CONCRETE ROADS AND CURB FOR INTERLOCKING BLOCK PAVING ROADS INCLUDING REMOVING [SSCM 1008.3 (b)]: SUPPLYING & FIXING CLASS II TIMBER BEARERS, JOISTS, ETC. INCLUDING DISMANTLING IN SHUTTERING. [SSCM 1008.3(a)]: 100 - 150 MM DIA. ROUND JUNGLE TIMBER SUPPLIED & FIXED AS PROPS.:	SQ.M	999.70	268.82	730.88
ST1-058	SUPPLYING & FIXING CLASS II TIMBER BEARERS, JOISTS, ETC. INCLUDING DISMANTLING IN SHUTTERING . [SSCM 1008.3(a)]:	CU.DECI M.	95.95	66.25	29.70
ST1-059	100 - 150 MM DIA. ROUND JUNGLE TIMBER SUPPLIED & FIXED AS PROPS.:	METRE	159.45	128.07	31.38
ST1-060	150 - 200 MM DIA. ROUND JUNGLE TIMBER SUPPLIED & FIXED AS PROPS.:	METRE	158.80	128.07	30.73
ST1-061	FORMWORK SMOOTH FINISH WITH CLASS II TIMBER FOR BRIDGE BEAMS, BRIDGE DECK UNDER SIDES AND SIDES INCLUDING DISMANTLING. [SSCM 1008.3(B)]:	SQ.M	4,616.60	2,168.72	2,447.88
ST1-062	FORMWORK SMOOTH FINISH WITH CLASS II TIMBER FOR BRIDGE COLUMN SHAFTS INCLUDING DISMANTLING. [SSCM 1008.3(b)]:	SQ.M	4,194.25	2,199.07	1,995.18
ST1-063	FORMWORK SMOOTH FINISH USING PLYWOOD (SHUTTER 15 MM) AND CLASS II TIMBER BEARERS,JOISTS AND JUNGLE TIMBER PROPS FOR BRIDGE ABUTMENTS, WINGWALLS ETC.:	SQ.M	4,374.35	3,049.69	1,324.66

CODE	DESCRIPTION OF	ITEM UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-064	SUPPLYING & FIXING 25 MM THICK PLANKS AND STRUTS OF CLASS II TIMBER AS FORMWORK ROUGH FINISH, IN FOUNDATION ETC. INCLUDING REMOVING.[SSCM 1008.3(b)]:	SQ.M	2,088.85	1,122.08	966.77
ST1-065	FORMWORK SMOOTH FINISH FOR GENERAL PURPOSES, USING 25 MM THICK PLANKS & STRUTS OF CLASS II TIMBER AND ROUND JUNGLE TIMBER PROPS 100-150 MM DIA., INCLUDING DISMANTLING:	SQ.M	2,885.80	1,615.80	1,270.00
ST1-066	LAYING & JOINTING 153 MM DIA. CONCRETE PIPES (TRANSPORT AND BEDDING MATERIAL PAID SEPARATELY) [SSCM 707.3(C)-707.4]:	METRE	5,160.95	1,047.36	4,113.59
ST1-067	LAYING & JOINTING 229 MM DIA. CONCRETE PIPES (TRANSPORT AND BEDDING MATERIAL PAID SEPARATELY) [SSCM 707.3(C)-707.4]:	METRE	6,130.60	1,084.36	5,046.24
ST1-068	LAYING & JOINTING 305 MM DIA. CONCRETE PIPES (TRANSPORT AND BEDDING MATERIAL PAID SEPARATELY) [SSCM 707.3(C)-707.4]:	METRE	4,963.20	1,178.28	3,784.92
ST1-069	LAYING & JOINTING 450 MM DIA. CONCRETE PIPES (TRANSPORT AND BEDDING MATERIAL PAID SEPARATELY) [SSCM 707.3(C)-707.4]:	METRE AND METRE METRE METRE METRE METRE METRE METRE	8,030.15	1,178.28	6,851.87
ST1-070	LAYING & JOINTING 610 MM DIA. CONCRETE PIPES (TRANSPORT AND BEDDING MATERIAL PAID SEPARATELY) [SSCM 707.3(C)-707.4]:	SR ind us METRE	13,308.90	2,356.56	10,952.34
ST1-071	LAYING & JOINTING 914 MM DIA. CONCRETE PIPES (TRANSPORT AND BEDDING MATERIAL PAID SEPARATELY) [SSCM 707.3(C)-707.4]:	dillight METRE	24,059.50	3,773.91	20,285.59
ST1-072	LAYING & JOINTING 1219 MM DIA. CONCRETE PIPES (TRANSPORT AND BEDDING MATERIAL PAID SEPARATELY) [SSCM 707.3(C)-707.4]:	METRE	34,763.50	5,293.72	29,469.78
ST1-073	LAYING & JOINTING 153 MM DIA. AVAILABLE CONCRETE PIPES AND COLLARS:	METRE	1,103.60	1,047.36	56.24
ST1-074	LAYING & JOINTING 229 MM DIA. AVAILABLE CONCRETE PIPES WITH COLLARS :	METRE	1,171.60	1,084.36	87.24
ST1-075	LAYING & JOINTING 305 - 450 MM DIA. AVAILABLE CONCRETE PIPES AND COLLARS :	METRE	1,267.85	1,178.28	89.57
ST1-076	LAYING & JOINTING 610 MM DIA. AVAILABLE CONCRETE PIPES AND COLLARS :	METRE	2,475.60	2,356.56	119.04
ST1-077	LAYING & JOINTING 914 MM DIA. AVAILABLE CONCRETE PIPES AND COLLARS :	METRE	4,168.80	3,773.91	394.89

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-078	LAYING & JOINTING 1219 MM DIA. AVAILABLE CONCRETE PIPES AND COLLARS :	METRE	5,952.00	5,293.72	658.28
ST1-079	FIXING NEW BRIDGE PLANKS RUNNERS AND STACKING OLD PLANKS AVAILABLE [SSCM 1402.2(a)]:	NO.	1,494.80	1,458.33	36.47
ST1-080	REMOVING & RE-SETTING OLD BRIDGE PLANKS.:	NO.	934.25	911.46	22.79
ST1-081	SUPPLYING & FIXING NEW BRIDGE PLANKS OF CLASS I TIMBER.:	CU.DECI M.	247.80	26.56	221.24
ST1-082	SUPPLYING & FIXING 31 MM THICK DECK PLANKS OF CLASS I TIMBER.:	SQ.M	9,684.25	2,777.78	6,906.47
ST1-083	FIXING NEW CHEQUERED OR M.S. PLATES ON TIMBER - DECKED BRIDGE.[SSCM 1402.2(d)]:	METRE	2,205.45	2,151.64	53.81
ST1-084	REMOVING & REFIXING CHEQUERED M.S. PLATES ON TIMBER - DECKED BRIDGE.:	METRE	2,940.55	2,868.85	71.70
ST1-085	TIGHTENING BOLTS & NUTS OF CHEQUERED OR M.S. PLATES.:	METRE	441.10	430.33	10.77
ST1-086	REMOVING & REFIXING 'U' CLIPS. '[SSCM 1402.2(b)]:	NO.	320.30	312.50	7.80
ST1-087	CLEANING, WIRE BRUSHING & PAINTING STEELWORK, ONE COAT ENAMEL PAINT.:	SQ.M	390.05	275.83	114.22
ST1-088	CLEANING, WIRE BRUSHING & APPLYING TAR ON STEELWORK, ONE COAT :	SQ.M	296.65	275.83	20.82
ST1-089	CLEANING, WITH COTTON WASTE AND PAINTING STEEL WORK WITH ENAMEL PAINT, ONE COAT :	SQ.M	240.40	129.17	111.23
ST1-090	TIGHTENING BOLTS & NUTS OF CHEQUERED OR M.S. PLATES.: REMOVING & REFIXING 'U' CLIPS. '[SSCM 1402.2(b)]: CLEANING, WIRE BRUSHING & PAINTING STEELWORK, ONE COAT ENAMEL PAINT.: CLEANING, WIRE BRUSHING & APPLYING TAR ON STEELWORK, ONE COAT: CLEANING, WITH COTTON WASTE AND PAINTING STEEL WORK WITH ENAMEL PAINT, ONE COAT: CHIPPING TO BARE METAL ETC. & PAINTING WITH ANTICORROSIVE PAINT, ONE COAT:	SQ.M	1,350.45	1,231.16	119.29
ST1-091	PAINTING WITH ONE COAT OF ENAMEL PAINT AFTER CLEANING, DERUSTING & APPLICATION OF ONE COAT ANTICORROSIVE PAINT. [SSCM 1401.3(c)]:	SQ.M	947.50	733.32	214.18
ST1-092	PAINTING WITH TWO COATS OF ENAMEL PAINT, AFTER CLEANING, DERUSTING & APPLICATION OF ONE COAT ANTICORROSIVE PAINT:	SQ.M	1,173.50	875.94	297.56
ST1-093	OILING STEEL CABLES ON SUSPENSION BRIDGES [SSCM 1405.3] :	SQ.M	1,726.90	592.03	1,134.87

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-094	CLEANING BOOMS OF STEEL BRIDGES INCLUDING SCAFFOLDING WHERE NECESSARY [SSCM 1401.3]:	METRE	121.25	90.16	31.09
ST1-095	DEMOLISHING UNREINFORCED CEMENT CONCRETE INCLUDING CLEANING OF DEBRIS IN FOUNDATION AND SUPER STRUCTURE IN DRY CONDITION EXCLUDING UNDER WATER STRUCTURES [SSCM 202.2]:	CU.M	4,995.60	4,770.32	225.28
ST1-096	DEMOLISHING REINFORCED CONCRETE AND DEBRIS CLEARED :	CU.M	7,168.75	6,890.46	278.29
ST1-097	DEMOLISHING REINFORCED CONCRETE IN VERY HEAVY STRUCTURES BUILD UP OF GRADE 30 ABOVE CONCRETE IN WORK SUCH AS BRIDGE BEAMS & DECK SLABS, INCLUDING COLLECTING & REMOVING:	CU.M	22,338.85	5,477.03	16,861.82
ST1-098	SUPPLYING & FIXING M.S. DOWELS, SPLICED AND DOVE TAILED WITH WEDGE AT ONE END, 16 MM DIA. AND 1 M LONG, BORING HOLES TO 0.3 M DEPTH IN FIXING:	NO pridi	1,274.80	850.00	424.80
ST1-099	TO 0.3 M DEPTH IN FIXING:	NO	1,603.85	950.00	653.85
ST1-099A	SUPPLYING & FIXING OF 400MM LONG , 20MM DIA. STAINLESS STEEL BARS AS DOWELS IN CAPPING BEAM AT FIXED END	NO	686.80	117.19	569.61
ST1-100	SUPPLYING & FIXING OF 400MM LONG , 20MM DIA. STAINLESS STEEL BARS AS DOWELS IN CAPPING BEAM AT FIXED END SUPPLYING & FIXING M.S. DOWELS, SPLICED AND DOVE TAILED WITH WEDGE AT ONE END, 25 MM DIA. AND 1 M LONG, BORING HOLES TO 0.3 M DEPTH IN FIXING :	NO	2,163.30	1,150.00	1,013.30
	LAY STANDARD TYPE ROAD KERBS(125 MM WIDE X 900 MM LONG), SET ON 19 MM THICK 1:3 CEMENT SAND MORTAR LAYER ON150 MM X 275 MM WIDE 1:2:4(19 MM) CONCRETE FOUNDATION WITH AVERAGE 157 MM X 150 MM WIDE BACKING WITH SAME CONCRETE INCLUDING EXCAVATION AND SHUTTERING.(COST OF KERB STONES INCLUDING TRANSPORT AND AGGREGATE* TRANSPORT TO PAY SEPARATELY): * QUANTITY OF AGGREGATE REQUIRED FOR CONCRETING IN 1 METER LENGTH IS EQUAL TO: 0.06 CU.M	METRE	3,496.05	1,878.24	1,617.81
ST1-102	LAY STANDARD PRECAST BRIDGE KERBS [TYPE DRAWING NO. T/B/106 OF RDA] (COST OF PRECAST KERBS INCLUDING TRANSPORT TO BE PAID SEPARATELY) :	METRE	811.90	763.89	48.01
ST1-103	CONSTRUCTING 150X50 MM THICK INSITU LOWER KERB IN GRADE 20(14 MM) CONCRETE FOR BRIDGES (AGGREGATE TRANSPORT TO BE PAID SEPARATELY):	METRE	398.15	235.07	163.08
ST1-104	LAYING 450 X 450 X 50 MM PRECAST CONCRETE SLABS ON ON FOOT WALKS INCLUDING AVERAGE 40 MM THICK 1:3 CEMENT MORTAR BEDDING.(COST OF PRECAST SLABS AND TRANSPORT, TO BE PAID SEPARATELY):	SQ.M	2,433.10	1,498.33	934.77

	MONARAGALA DISTRICT				
CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-105	LAYING 450 X 450 X 50 MM PRECAST CONCRETE SLABS ON ON FOOT WALKS INCLUDING AVERAGE 40 MM THICK SAND BEDDING.(COST OF PRECAST SLABS AND TRANSPORT, TO BE PAID SEPARATELY):	SQ.M	1,601.15	1,375.00	226.15
ST1-106	FIXING PRECAST HAND RAILING AND UPRIGHTS USING GRADE 25(19 MM) CONCRETE INCLUDING FORMWORK FOR POCKETS.(COST OF THE PRECAST ITEMS INCLUDING TRANSPORT AND AGGREGATE* TRANSPORT, TO BE PAID SEPARATELY.) [TYPE DRAWING NO. T/B/102/B] * QUANTITY OF AGGREGATE REQUIRED FOR CONCRETING IN	METRE	2,213.10	1,660.74	552.36
ST1-107	PILLASTER, TYPE I (AGGREGATE* TRÀNSPORT AND IRON PILING TO BE PAID SEPARATELY) [TYPE DRAWING NO. T/B/106-REV 1]:	NO.	66,847.50		42,843.19
ST1-108	CONSTRUCTION OF R.C.C. GRADE 25(19 MM) END PILLASTER, TYPE II (AGGREGATE* TRANSPORT AND IRON PILLING TO BE PAID SEPARATELY) [TYPE DRAWING NO. T/B/106-REV 1]: * AGGREGATE QTY. REQUIRED PER PILLASTER: 37.5 MM - 0.09 CU.M	MO, VIII AVIOŽI	73,862.80	27,100.60	46,762.20
ST1-109	* AGGREGATE QTY. REQUIRED PER PILLASTER: 37.5 MM - 0.08 CU.M 19 MM - 0.95 CU M CONSTRUCTION OF R.C.C. GRADE 25(19 MM) END PILLASTER, TYPE II (AGGREGATE* TRANSPORT AND IRON PILING TO BE PAID SEPARATELY) [TYPE DRAWING NO. T/B/106-REV 1]: * AGGREGATE QTY. REQUIRED PER PILLASTER: 37.5 MM - 0.09 CU.M 19 MM - 1.16 CU.M CONSTRUCTION OF R.C.C. GRADE 25(19 MM) END PILLASTER, TYPE III (AGGREGATE* TRANSPORT AND BUILTUP RUBBLE FOUNDATION TO BE PAID SEPARATELY) [TYPE DRAWING NO. T/B/106-REV 1]: * AGGREGATE QTY. REQUIRED PER PILLASTER: 19 MM - 0.70 CU.M CONSTRUCTION OF R.C.C. GRADE 25(19 MM) END PILLASTER, TYPE IV (AGGREGATE* TRANSPORT TO BE PAID SEPARATELY) [TYPE DRAWING NO. T/B/106-REV 1]: * AGGREGATE QTY. REQUIRED PER PILLASTER: 19 MM - 0.70 CU.M	NO.	42,969.10	15,181.95	27,787.15
ST1-110	CONSTRUCTION OF R.C.C. GRADE 25(19 MM) END PILLASTER, TYPE IV (AGGREGATE* TRANSPORT TO BE PAID SEPARATELY) [TYPE DRAWING NO. T/B/106-REV 1]: * AGGREGATE QTY. REQUIRED PER PILLASTER: 19 MM - 0.70 CU.M	NO.	46,413.30	16,192.21	30,221.09
ST1-111	LAYING OF GRADE 20 CONCRETE PRECSAT PIN KERBS IN GRADE 20(19) CONCRETE FOUNDATION AS EDGING: (AGGREGATE TRANSPORT TO BE PAID SEPARATELY)	METRE	1,137.90	668.69	469.21
ST1-112	SUPPLYING AND FIXING 25 MM THICK TONGUE AND GROOVED PLANKS WITH 50 X 50 MM STRUTS OF CLASS I TIMBER IN PANELS AS SMOOTH SHUTTERING FOR CONCRETE DRAINS (12 USES) :	SQ.M	2,099.15	1,166.25	932.90
ST1-113	SUPPLY AND PACKING 50-200 MM DRY STONE LINING BEHIND ABUTMENTS AND WING WALLS : (AGGREGATE TRANSPORT PAID SEPARATELY)	CU.M	4,557.50	1,545.94	3,011.56

	MONANAGALA DISTRICT				
CODE	DESCRIPTION OF ITEM	UNIT 	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-114	LAYING GEOTEXTILE ON PREPARED SURFACE (SUPPLY AND TRANSPORT OF GEOTEXTILE TO BE PAID SEPARATELY):	SQ.M	99.30	96.87	2.43
ST1-115	CONSTRUCTION OF GABION WALL USING 4X1X1 M MESH INCLUDING LACING WIRE ON PREPARED GROUND (SUPPLY AND TRANSPORT OF GABION MESH TO BE PAID SEPARATELY):	CU.M	9,511.40	5,832.03	3,679.37
ST1-116	CONSTRUCTION OF GABION WALL USING 4X1X.5 M MESH INCLUDING LACING WIRE ON PREPARED GROUND (SUPPLY AND TRANSPORT OF GABION MESH TO BE PAID SEPARATELY):	CU.M	10,189.00	6,493.13	3,695.88
ST1-117	CONSTRUCTION OF KERB INLET TYPE: K1 / T1 WITH COVER SLABS AS PER AS PER R.D.A. DRAWING AGGREGATE TRANSPORT TO PAY SEPARATELY.	NO.	15,605.40	6,039.38	9,566.02
* NOTE	: EARTH EXCAVATION TO BE CONSIDERED BY THE ENGINEER AS PER SITE CONDITION AND ADD SEPARATELY IF REQUIRED.				
	ITEMS RESERVED FOR BRIDGE WORKS ONLY				
	THE RATES IN THE FOLLOWING ITEMS FROM ST1-118 TO ST1-120 SHOULD BE ADDED TO THE CONCRETE RATE SELECTED FROM ITEM CODES ST1-038 TO ST1-050, DEPENDING ON THE STRUCTURAL LOCATION.	CHILDING			
ST1-118	ADDITIONAL LABOUR FOR POURING, COMPACTING AND LEVELLING CONCRETE IN SCREED UNDER FOUNDATION SLAB	CU.M	1,385.40	1,385.40	0.00
ST1-119	ADDITIONAL LABOUR FOR POURING, COMPACTING AND LEVELLING CONCRETE IN SCREED UNDER FOUNDATION SLAB ADDITIONAL LABOUR FOR POURING, COMPACTING CONCRETE IN ABUTMENTS, WINGWALLS, CAPPING BEAMS OF PIERS AND FOOTWALKS OF BRIDGES	CU.M	441.20	441.20	0.00
ST1-120	ADDITIONAL LABOUR FOR POURING, COMPACTING AND LEVELLING INFILLER CONCRETE BETWEEN BRIDGE BEAMS INCLUDING SCREED OF BRIDGE BEAMS	CU.M	2,062.50	2,062.50	0.00
ST1-121	LAYING READY MIXED GRADE CONCRETE INCLUDING VIBRATION* (SUPPLY OF CONCRETE TO BE PAID SEPARATELY)	CU.M	2,732.35	2,441.18	291.17
ST1-122	SUPPLYING AND LAYING APPROVED HARD RUBBER BEARING PADS 75 X12 MM OVER CAPPING BEAMS AND UNDER THE APPROACH SLABS	L.M	2,858.15	159.44	2,698.71
ST1-123	BITUMENOUS SEALING MATERIAL SUPPLIED AND LAID UNDER BEAM ENDS TO PREVENT GROUT LEAK ON TO CAPPING BEAM INCLUSIVE OF TRANSPORT OF EMULSION.	L.M	197.55	137.50	60.05
ST1-124	150 MM DIA. POLYTHENE DISPLACERS SUPPLIED AND FILLED WITH SAW DUST OR SIMILAR LIGHT MATERIAL IN DECK. TRANSPORT OF SAW DUST TO PAY SEPARATELY:	L.M	66.95	31.25	35.70
ST1-125	230 MM DIA. POLYTHENE DISPLACERS SUPPLIED AND FILLED WITH SAW DUST OR SIMILAR LIGHT MATERIAL IN DECK. (TRANSPORT OF SAW DUST TO PAY SEPARATELY).	L.M	113.30	62.50	50.80

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-126	325 MM DIA. POLYTHENE DISPLACERS SUPPLIED AND FILLED WITH SAW DUST OR SIMILAR LIGHT MATERIAL IN DECK. (TRANSPORT OF SAW DUST TO PAY SEPARATELY).	L.M	175.15	100.00	75.15
ST1-127	PCC BEAMS 16.15M LONG LAUNCHED INTO POSITION	BEAM	20,707.90	5,937.50	14,770.40
ST1-128	PCC BEAMS 13.41M AND 12.19M LONG LAUNCHED INTO POSITION	BEAM	14,625.25	1,718.75	12,906.50
ST1-129	PCC BEAMS 10.67M, 9.75M AND 8.23M LONG LAUNCHED INTO POSITION	BEAM	10,963.20	2,968.75	7,994.45
ST1-130	PCC BEAMS 7.01M, 6.09M, 5.18M, 4.26M AND 3.35M LONG LAUNCHED INTO POSITION	BEAM	8,374.70	2,226.56	6,148.14
ST1-131	EXPANSION JOINTS WITH M.S. ANGLE IRON AND HARD RUBBER AS PER DRAWING NO. T/B/107 REV.1	L.M	12,246.30	5,805.16	6,441.14
ST1-132	TRANSPORT OF 355 X355X9144 MM R.C.C. PILES TO THE SITE (EXCLUDING UNLOADING AND STACKING)	PER NO./KM	114.85	0.00	114.85
ST1-133	STACKING OF 355 X355X9144 MM R.C.C. PILES	NO	6,155.25	1,250.00	4,905.25
ST1-134	TRANSPORT OF 305 X200X6100 MM R.C.SHEET PILES TO THE SITE (EXCLUDING UNLOADING AND STACKING)	PER NO./KM	42.20	0.00	42.20
ST1-135	STACKING OF 305 X200X6100 MM R.C.SHEET PILES	NO	3,020.40	833.33	2,187.07
ST1-136	DRIVING 305 X200X6100 MM R.C.SHEET PILES USING HAND MONKEY	METRE	11,845.50	11,556.60	288.90
ST1-137	SATURATED SAND FILLING	CU.M	4,313.15	294.12	4,019.03
ST1-138	STACKING OF P.S.C.BEAM 16.15M (53' 0") LONG	BEAM	12,310.45	2,500.00	9,810.45
ST1-139	TRANSPORT OF 305 X200X6100 MM R.C.SHEET PILES TO THE SITE (EXCLUDING UNLOADING AND STACKING) STACKING OF 305 X200X6100 MM R.C.SHEET PILES DRIVING 305 X200X6100 MM R.C.SHEET PILES USING HAND MONKEY SATURATED SAND FILLING STACKING OF P.S.C.BEAM 16.15M (53' 0") LONG TRANSPORT OF P.S.C.BEAM 16.15M (53' 0") LONG TO THE SITE STACKING OF P.S.C.BEAM 13.41M (44' 0") OR 12.19M (40' 0") LONG	PER BEAM /KM	229.75	0.00	229.75
ST1-140	STACKING OF P.S.C.BEAM 13.41M (44' 0") OR 12.19M (40' 0") LONG	BEAM	9,061.15	2,500.00	6,561.15
ST1-141	TRANSPORT OF P.S.C.BEAM 13.41M (44' 0") OR 12.19M (40' 0") LONG TO THE SITE	PER BEAM /KM	153.15	0.00	153.15
ST1-142	STACKING OF P.S.C.BEAM 10.63M (35' 0"), 9.75M (32' 0") OR 8.23M (27' 0") LONG	BEAM	6,795.85	1,875.00	4,920.85
ST1-143	TRANSPORT OF P.S.C.BEAM 10.63M (35' 0"), 9.75M (32' 0") OR 8.23M (27' 0") LONG TO THE SITE	PER BEAM /KM	114.85	0.00	114.85
ST1-144	STACKING OF P.S.C.BEAM 7.01M (23' 0") LONG	BEAM	4,530.55	1,250.00	3,280.55

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
ST1-145	TRANSPORT OF P.S.C.BEAM 7.01M (23' 0") LONG TO THE SITE	PER BEAM /KM	76.60	0.00	76.60
ST1-146	50mm THICK COVER SLABS FOR SERVICE DUCTS IN GRADE 25(20) CONCRETE INCLUSIVE OF LIGHT REINFORCEMENT	SQ.M	4,387.35	185.19	4,202.16
ST1-147	110mm Ø TYPE 400 P.V.C. SERVICE DUCT SUPPLYING AND FIXING IN DECK	L.M	1,927.10	312.50	1,614.60
ST1-148	110mm Ø TYPE 250 P.V.C. RAIN WATER OUTLETS SUPPLIED AND FIXED THROUGH DECK	L.M	1,687.65	562.50	1,125.15
ST1-149	50mm Ø TYPE 400 P.V.C. DRAIN PIPES SUPPLIED AND FIXED THROUGH DECK	L.M	734.85	375.00	359.85
ST1-150	25mm Ø TYPE 1000 P.V.C. DRAIN PIPES SUPPLIED AND FIXED THROUGH DECK	L.M	591.95	281.25	310.70
ST1-151	SUPPLYING & LAYING 110 MM DIAMETER PVC PIPE (GAUGE 600) UNDER THE ELECTRICAL LINE INSTALATION ON CENTER MEDIAN	L.M	3,108.70	141.67	2,967,03
	* * *				
		civil Avigil			
),			
	2025 rision res				
	ER in 15,				
	Hoekhyay				
	Engl. Hig				
	,,500				
	K/Log.				
	lities.				
	Milly				
	SUPPLYING & LAYING 110 MM DIAMETER PVC PIPE (GAUGE 600) UNDER THE ELECTRICAL LINE INSTALATION ON CENTER MEDIAN *** *** *** *** *** *** ** **				

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION XI				
	======== KILOMETER POSTS AND GUARD STONES				
RF1-001	WHITE WASHING, TWO COATS TO GUIDE/GUARD STONES:	NO.	106.30	91.88	14.43
RF1-002	WHITEWASHING TWO COATS K.M. STONES INC. NUMBERING & TAR SKIRTING:	NO.	1,115.05	1,050.00	65.05
RF1-003	PAINTING WHITE BACK GROUND ON PARAPETS ETC. & STENCILLING NOS.:	NO.	416.55	367.50	49.05
RF1-004	FIXING GUARD STONES IN ANY SOIL:	NO.	320.30	312.50	7.80
RF1-005	CASTING STD. K.M. STONES WITH R.C.C [1:2:4(19 MM) & CEMENT 282.5 KG/CU.M], FOR "A" AND "B" CLASS ROADS :	NO.	8,843.85	5,611.21	3,232.64
RF1-006	CASTING STD. K.M. STONES WITH R.C.C [1:2:4(19 MM) & CEMENT 282.5 KG/CU.M], FOR "C" AND "D" CLASS ROADS :	NO. Pilail	5,975.55	3,793.89	2,181.66
RF1-007	FIXING STANDARD TYPE K.M. STONES IN ANY SOIL:	NO.	2,387.25	2,322.92	64.33
RF1-008	CASTING STD. K.M. STONES WITH R.C.C [1:2:4(19 MM) & CEMENT 282.5 KG/CU.M], FOR "A" AND "B" CLASS ROADS: CASTING STD. K.M. STONES WITH R.C.C [1:2:4(19 MM) & CEMENT 282.5 KG/CU.M], FOR "C" AND "D" CLASS ROADS: FIXING STANDARD TYPE K.M. STONES IN ANY SOIL: FIXING NEW OR REFIXING GUARD STONES IN 225 MM THICK CEMENT CONCRETE [1:3:6(37.5 MM) AND CEMENT 219 KG/CU.M] WITH MINIMUM COVER 75 MM X 300 MM DEPTH: CASTING STANDARD TYPE GUARD STONES IN CONCRETE [1:2:4(19 MM) & CEMENT 282.5 KG/CU.M]: CASTING STANDARD TYPE GUARD STONES IN IN CONCRETE GRADE 20(19) AS PER DRAWING	NO.	1,113.35	624.66	488.69
RF1-009	CASTING STANDARD TYPE GUARD STONES IN CONCRETE [1:2:4(19 MM) & CEMENT 282.5 KG/CU.M]:	NO.	3,000.15	1,915.68	1,084.47
RF1-009A	CASTING STANDARD TYPE GUARD STONES IN IN CONCRETE GRADE 20(19) AS PER DRAWING NO. T/B/100-REV.1 FOR BRIDGES & CULVERTS	NO.	4,364.85	1,838.50	2,526.35
* NOTE	: 19 MM AGGREGATE PER GUARD STONE IS 0.058 CU.M.				
RF1-010	ROUTE NUMBERING WITH REFLECTIVE PAINT ON 2 SIDES:	NO.	1,004.95	937.50	67.45
RF1-011	CASTING STANDARD BOUNDARY MARKERS IN R/F CONCRETE[1:2:4(19MM) WITH ADMIXTURES, INCLUDING 14 DAYS CURING AND LOADING TO VEHICLES AT YARD. (AGGR. TRANSPORT TO PAY SEPARATELY) *:	NO.	3,011.50	1,454.21	1,557.29

^{*} NOTE: 19 MM AGGREGATE PER BOUNDARY MARKER IS 0.039 CU.M.

* * *

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION XII				
	NOTICE BOARDS & SIGN BOARDS				
	[SSCM 810.2 AND 1501.3] (ALL PAINTS SHOULD CONFORM TO THE REQUIREMENTS OF S.L.S. AS GIVEN IN SSCM 1707)				
RS1-001	NOTICE & TRAFFIC SIGN BOARDS ETC. FIXED IN CONCRETE [1:3:6(37.5 MM) AND CEMENT 219 KG/CU.M], (EXCLUDING TRANSPORT OF AGGREGATE):	NO.	2,144.60	1,444.93	699.67
RS1-002	CLEANING & WHITEWASHING 2 COAT TOWN NAME BOARDS (INC. TAR SKIRT)	NO.	593.60	459.38	134.23
RS1-003	CLEANING, PAINTING ONE COAT & RELETTERING ETC. TRFFIC SIGN BOARDS INC. PAINT POST IN B/W	NO.	3,408.60	3,125.00	283.60
RS1-004	CLEANING AND PAINTING 1 COAT ON NOTICE BOARD	NO.	489.85	370.02	119.83
RS1-005	LETTERING & NUMBERING BELOW 50 MM	NO.	84.65	78.13	6.53
RS1-006	LETTERING & NUMBERING 50 MM - 75 MM	NO.	101.60	93.75	7.85
RS1-007	LETTERING & NUMBERING 75 MM - 150 MM	NO.	127.00	117.19	9.81
RS1-008	LETTERING & NUMBERING 150 MM - 225 MM	NO.	169.30	156.25	13.05
RS1-009	LETTERING & NUMBERING 50 MM - 75 MM LETTERING & NUMBERING 75 MM - 150 MM LETTERING & NUMBERING 150 MM - 225 MM PAINTING 2 COATS CONTINUOUS CENTRE LINE, 100 MM WIDE WITH ENAMEL PAINT PAINTING 1 COAT CONTINUOUS CENTRE LINE, 100 MM WIDE WITH ROAD MARKING PAINT(WHITE): PAINTING 2 COATS BROKEN CENTRE LINE, 100 MM WIDE WITH ENAMEL PAINT PAINTING 1 COAT BROKEN CENTRE LINE, 100 MM WIDE WITH ROAD MARKING PAINT(WHITE):	METRE	209.80	156.25	53.55
RS1-010	PAINTING 1 COAT CONTINUOUS CENTRE LINE, 100 MM WIDE WITH ROAD MARKING PAINT(WHITE):	METRE	223.05	164.93	58.12
RS1-011	PAINTING 2 COATS BROKEN CENTRE LINE, 100 MM WIDE WITH ENAMEL PAINT	METRE	199.05	156.25	42.80
RS1-012	PAINTING 1 COAT BROKEN CENTRE LINE, 100 MM WIDE WITH ROAD MARKING PAINT(WHITE) :	METRE	209.80	164.93	44.87
RS1-013	BARRICADING WITH EMPTY (HOT TAR) BARRELS INCLUDING WHITE WASHING, TRANSPORTING AND COST OF BARRELS :	NO.	552.95	240.78	312.17
RS1-014	REVETTMENT TO BANKS ETC. WITH EMPTY BARRELS IN HORIZONTAL TIERS WITH VERTICAL BATTER(1:8), INCLUDING TRANSPORT OF BARRELS:	NO.	911.45	748.59	162.86

HIGHWAY SCHEDULE OF RATES - SUMMARY 2025

MONARAGALA DISTRICT

CODE 	DESCRIPTION OF ITEM	UNIT 	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
RS1-015	ROAD MARKING, CONTINUOUS CENTRE LINE 100 MM WIDTH, USING THERMOPLASTIC PAINT (WHITE) INCLUSIVE BARRICADING (PAINT MATERIAL AND REFLECTIVE GLASS BEADS TO PAY SEPARATELY):	SQ.M	372.85	212.50	160.35
NOTE *	1 KG OF THERMO PLASTIC PAINT COVERS 0.14 SQ.M AREA AT 3.0 MM THICKNESS 25 KG OF GLASS BEADS WILL COVER 100 SQ.M AREA				
RS1-016	ROAD MARKING, STANDARD PEDESTRIAN CROSSING, USING THERMOPLASTIC PAINT (YELLOW), INCLUSIVE BARRICADING (PAINT MATERIAL AND REFLECTIVE GLASS BEADS TO PAY SEPARATELY):	SQ.M	350.35	334.17	16.18
NOTE *	1 KG OF THERMO PLASTIC PAINT COVERS 0.14 SO.M AREA AT 3.0 MM				

THICKNESS 25 KG OF GLASS BEADS WILL COVER 100 SQ.M AREA

White thy of Transport, Highways, Ports and Civil Aviation

MS1-001	SECTION XIII ======== MISCELLANEOUS PREPARING, STOCK PILING PREMIX USING 80/100 PEN, CRAPE BITLIMEN/EYCL, TRANSPORT				
MS1-001	·				
	PEN. GRADE BITUMEN(EXCL. TRANSPORT OF AGGREGATE) (SITE MADE):	CU.M	24,123.00	6,802.12	17,320.88
	PATCHING SHALLOW POT HOLES, DEPTH LESS THAN 20 MM USING 80/100 HOT BITUMEN 1.2 LTR/SQ.M AND 12.5 MM CHIPS SINGLE SIZE AT THE RATE OF 13.75 CU.DECI M/SQ.M INCLUDING HAND TAMPING (RATE INCLUDES COST OF BITUMEN AND MATERIALS) (EXCL. TRANSPORT OF AGGREGATE & BITUMEN):	SQ.M	376.85	115.59	261.26
	PATCHING SHALLOW POT HOLES, DEPTH LESS THAN 20 MM USING MC 30 BITUMEN 1.2 LTR/SQ.M AND 12.5 MM CHIPS SINGLE SIZE AT THE RATE OF 13.75 CU.DECI M/SQ.M INCLUDING HAND TAMPING (RATE INCLUDES COST OF BITUMEN AND MATERIALS) (EXCL. TRANSPORT OF AGGREGATE AND BITUMEN):	SQ.M	398.80	129.35	269.45
	1.2 LTR/SQ.M AND 12.5 MM CHIPS SINGLE SIZE AT THE RATE OF 13.75 CU.DECI M/SQ.M INCLUDING HAND TAMPING (RATE INCLUDES COST OF BITUMEN AND MATERIALS) (EXCL. TRANSPORT OF AGGREGATE AND BITUMEN): PATCHING SHALLOW POT HOLES, DEPTH LESS THAN 20 MM USING EMULSION (CRS 1) AT THE RATE OF 1.2 LTR/SQ.M AND 12.5 MM CHIPS SINGLE SIZE AT THE RATE OF 13.75 CU.DECI M/SQ.M INCLUDING HAND TAMPING, TRANSPORT OF EMULSION TO SITE ETC. (RATE INCLUDES COST OF EMULSION AND OTHER MATERIALS)(EXCL. TRANSPORT OF AGGREGATE): PATCHING POT HOLES OF MEDIUM DEPTH OF 20-75 MM WITH PREMIX MATERIAL (SITE MADE) USING CUT BACK 80/100 BITUMEN 10-20% AT THE RATE OF 83.5 LITRES PER CU. METRE OF 19 MM AND DOWN GAUGE STONE AGGREGATE. INCLUDING PREPARATION OF SUBFACE.	SQ.M	323.65	115.59	208.06
	TACK COAT WITH EMULSION (CSS-1) AT .75 LTR/SQ.M, TRIMMING SIDES, LAYING PREMIX, TAMPING ETC. COMPLETE. (RATE INCLUSIVE OF PREMIX MADE AT SITE & TACK COAT) (EXCL. TRANSPORT OF AGGREGATE):	SQ.M	2,653.70	1,367.58	1,286.12
	PATCHING POTHOLES USING PLANT MADE BITUMEN BOUND BASE (WITH 60/70 BINDER) INCLUDING SEALING THE PATCHING WITH EMULSION(CRS-1) PAINTING @ 7.3 LTR/M.TON, COVER WITH SAND (SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY): (SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY):	M.TON	19,172.70	5,250.00	13,922.70
	PATCHING POT HOLES OF MEDIUM DEPTH OF 20-75 MM USING GRADED AGGREGATE 19 -12.5 MM USING HOT BITUMEN(80/100) @ 2 LTR/SO.M COVERED WITH BLOTTON MATERIAL AT THE RATE 0F 1 CU.M/125 SQ.M INCLUDING PREPARATION OF SURFACE, TACK COAT WITH (CSS-1) AT .75 LTR/SQ.M, TRIMMING SIDES, LAYING AGGREGATE, TAMPING ETC. COMPLETE. (RATE INCLUSIVE OF AGGREGATE & TACK COAT BUT EXCL. TRANSPORT OF AGGREGATE & BITUMEN):	SQ.M	1,556.70	917.58	639.12
	PATCHING DEEP POT HOLES DEEPER THAN 75 MM WITH PREMIX MATERIAL (SITE MADE) TO A DEPTH OF 37.5 MM (OVER THE ALREADY PREPARED SURFACE WITH AGGREGATE AND GRAVEL PAID SEPARATELY) USING 10-20% CUT BACK BITUMEN AT THE RATE OF 83.5 LTR/CU.M OF 19 MM AND DOWN GRADED AGGREGATE INCL. PREPARATION OF SURFACE, TACK COAT WITH EMULSION (CSS-1) .75 LTR/SQ.M., TRIMMING SIDES, LAYING PREMIX, TAMPING ETC. COMPLETE (RATE INCLUSIVE OF PREMIX MADE AT SITE AND TACK COAT) (EXCL. TRANSPORT OF AGGREGATE & BITUMEN):	SQ.M	1,501.35	821.19	680.16

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
MS1-009	PATCHING POT HOLES MORE THAN 75 MM DEEP WITH WATER BOUND GRAVEL MATERIAL USING 50 MM OR 12.5 MM SINGLE SIZE AGGREGATE ALONG WITH USEABLE OLD AGGREGATE OBTAINED FROM PICKING AND PREPARATION OF SURFACE INCLUDING LAYING, WATERING, SPREADING GRAVEL OF APPROVED QUALITY AND TAMPING AS DIRECTED. (AGGREGATE AND GRAVEL WILL BE PAID SEPARATELY):	SQ.M	88.55	86.02	2.53
MS1-010	PATCHING RUTS AND DEPRESSIONS UPTO 75 MM DEPTH USING SITE MADE COLD MIX(CUT BACK) MATERIAL WITH THE SURFACE AND EDGE PREPARED AS PER SPECIFICATIONS AND APPLICATION OF TACK COAT WITH EMULSION (CSS-1) .75 LTR/SQ.M., (EXCL. TRANSPORT OF AGGREGATE):	SQ.M	2,400.85	1,120.87	1,279.98
	PATCHING RUTS AND DEPRESSIONS UPTO 75 MM DEPTH USING PLANT MADE COLD MIX(60/70 CUT BACK) MATERIAL WITH THE SURFACE AND EDGE PREPARED AS PER SPECIFICATIONS AND APPLICATION OF TACK COAT WITH EMULSION (CSS-1) @ .75 LTR/SQ.M (SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY):	SQ.M	2,307.40	600.97	1,706.43
MS1-012	MATERIAL WITH THE SURFACE AND EDGE PREPARED AS PER SPECIFICATIONS AND APPLICATION OF TACK COAT WITH EMULSION (CSS-1) @ .75 LTR/SQ.M (SUPPLY AND TRANSPORT OF PREMIX TO BE PAID SEPARATELY): PATCHING RUTS AND DEPRESSIONS DEEPER THAN 75 MM THE SURFACE AND EDGES PREPARED AS PER SPECIFICATION TACK COAT WITH EMULSION(CSS-1) @ .75 LTR/SQ.M, TRIMMING SIDES, 50 MM DOWN GAUGE AGGREGATED LAID AND COMPACTED WITH SITE MADE COLD MIX(CUT BACK) MATERIAL (AGGREGATE 50 MM DOWN GAUGE AND TRANSPORT WILL BE PAID SEPARATELY): PATCHING RUTS AND DEPRESSIONS UPTO 75 MM DEPTH THE SURFACE AND EDGES PREPARED AS PER SPECIFICATION AND APPLICATION OF TACK COAT WITH EMULSION(CSS-1) AT .75 LTR/SQ.M 50 MM DOWN GAUGE AGGREGATED LAID AND COMPACTED, USING HOT BITUMEN(80/100) @ 2 LTR/SQ.M COVERED WITH BLOTTON MATERIAL (SAND) AT THE RATE OF 1 CU.M/125 SQ.M (AGGREGATE WILL BE PAID SEPARATELY)):	SQ.M	1,996.30	1,300.15	696.15
MS1-013	PATCHING RUTS AND DEPRESSIONS UPTO 75 MM DEPTH THE SURFACE AND EDGES PREPARED AS PER SPECIFICATION AND APPLICATION OF TACK COAT WITH EMULSION(CSS-1) AT .75 LTR/SQ.M 50 MM DOWN GAUGE AGGREGATED LAID AND COMPACTED, USING HOT BITUMEN(80/100) @ 2 LTR/SQ.M COVERED WITH BLOTTON MATERIAL (SAND) AT THE RATE OF 1 CU.M/125 SQ.M (AGGREGATE WILL BE PAID SEPARATELY):	SQ.M	1,520.00	1,061.49	458.51
MS1-014		SQ.M	1,718.95	1,253.90	465.05
MS1-015	CORRECTING & STRENGTHENING THE EDGES OF ROAD WITH SATE MADE COLD MIX 40MM THICK PREPARED USING CUT BACK BITUMEN 10-20% AT THE RATE OF 83.5 LTR/CU.M OF 19 MM AND DOWN GAUGE AGGREGATE OVER A TACK COAT USING WITH EMULSION AT .75 LTR/SQ.M LAID OVER 50 MM AND DOWN GAUGE AGGREGATE LAID, ON POSITION WATERED AND COMPACTED INCLUDING EARTH WORK EXCAVATION TO A WIDTH OF 225 MM AND DEPTH OF 125 MM. (COST OF AGGREGATE AND TRANSPORT TO BE PAID SEPARATELY):	SQ.M	2,430.90	1,715.63	715.27

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
MS1-016	CORRECTING & STRENGTHENING THE EDGES OF ROAD WITH SITE MADE COLD MIX 40 MM THICK PREPARED USING CUTBACK BITUMEN 10-20% AT THE RATE OF 83.5 LTR/CU.M OF 19 AND DOWN GAUGE AGGREGATE OVER A TACK COAT WITH EMULSION AT .75 LTR/SQ.M LAID OVER 50 MM AND DOWN GAUGE AGGREGATE LAID, ON POSITION WATERED AND COMPACTED WITH A BOTTOM LAYER OF 100 MM AGGREGATE CLOSELY PACT, INCLUDING EARTH WORK EXCAVATION TO A WIDTH OF 225 MM AND DEPTH OF 225 MM (AGGREGATE 100 MM, 50 MM DOWN GAUGE AND TRANSPORT WILL BE PAID SEPARATELY):	SQ.M	2,824.55	2,091.07	733.48
MS1-017	PATCH SEALING WITH EMULSION PAINTING THE SURFACE BY SPRAY OF CRS-1 AT THE RATE OF .75 LTR/SQ.M SQUEEGING THE EMULSION AND SPREADING THE BLOTTON MATERIAL (SAND) AT THE RATE OF 1 CU.M/125 SQ.M:	SQ.M	170.20	43.91	126.29
MS1-018	PATCH SEALING WITH HOT BITUMEN PAINTING THE SURFACE BY USING .75 LTR/SQ.M SQEEGING THE BITUMEN AND SPREADING THE BLOTTON MATERIAL (SAND) AT THE RATE OF 1 CU.M/125 SQ.M (TRANSPORT OF BITUMEN PAID SEPARATELY):	SQ.M	203.65	43.91	159.74
MS1-019	PATCH SEALING OF PITTED SURFACE USING HOT SAND BITUMEN MIX 104 LTR/CU.M OF SAND SPREAD AND HAND TAMPED INCLUDING BRUSHING AND CLEANING THE SURFACE BEFORE APPLICATION (EXCLUDING TRANSPORT OF BITUMEN):	SQ.M	480.60	170.25	310.35
MS1-020	PATCH SEALING OF PITTED SURFACES WITH A EMULSION SAND SLURRY USING CRS 1 OR 2 AT THE RATE OF 136.5 LTR/CU.M OF SAND MIX PROPERLY LAID, LEVELLED & SQUEEGED INCLUDING BRUSHING AND CLEANING THE SURFACE BEFORE APPLICATION:	SQ.M	439.20	124.61	314.59
MS1-021	AND HAND TAMPED INCLUDING BRUSHING AND CLEANING THE SURFACE BEFORE APPLICATION (EXCLUDING TRANSPORT OF BITUMEN): PATCH SEALING OF PITTED SURFACES WITH A EMULSION SAND SLURRY USING CRS 1 OR 2 AT THE RATE OF 136.5 LTR/CU.M OF SAND MIX PROPERLY LAID, LEVELLED & SQUEEGED INCLUDING BRUSHING AND CLEANING THE SURFACE BEFORE APPLICATION: GENERAL UPKEEP OF ROAD SIDES INCLUDING MAINTAINING THE RIGHT OF WAY IN A NEAT CONDITION BY TRIMMING, WEEDING & CLEARING OF THE ROAD SIDES, DRAINS, DRAINAGE STRUCTURES, SCUPPER DRAINS AND CLEANING MINOR SLIPS: CLEANING ORDINARY JUNGLE INCLUDING REMOVING HIGH GROWING PLANTS AND TREES OF GIRTH LESS THAN 300 MM OTHER THAN THOSE DESIGNATED TO REMAIN, BY UPROOTING OR BY CUTTING AND THEN UPROOTING THE STUMPS OR BY CUTTING ONLY AS	SQ.M	43.70	42.23	1.47
MS1-022	CLEANING ORDINARY JUNGLE INCLUDING REMOVING HIGH GROWING PLANTS AND TREES OF GIRTH LESS THAN 300 MM OTHER THAN THOSE DESIGNATED TO REMAIN, BY UPROOTING OR BY CUTTING AND THEN UPROOTING THE STUMPS OR BY CUTTING ONLY AS DIRECTED.(SSCM 1203.2):	SQ.M	5.40	5.25	0.15
MS1-023	CLEARING MEDIUM JUNGLE INCLUDING REMOVING ALL HIGH GROWING PLANTS AND TREES OF GIRTH LESS THAN 300 MM OTHER THAN THOSE DESIGNATED TO REMAIN, BY UPROOTING OR BY CUTTING AND THEN UPROOTING THE STUMPS OR BY CUTTING ONLY AS DIRECTED:	SQ.M	7.45	7.29	0.16
MS1-024		SQ.M	9.55	9.33	0.22
MS1-025	REPAIRS TO DAMAGE OF SHOULDERS VERGES AND EMBANKMENTS SLOPES INCLUDING MAKING GOOD DEPRESSIONS, RUTS, HOLES AND ERROSION PATH WITH APPROVED GRAVELLY SOIL AND COMPACTING THE SAME WITH ROLLER (8-10 TON) AS DIRECTED (GRAVELLY SOIL TO BE PAID				
	SEPARATELY IF BROUGHT FROM OUTSIDE) [SSCM 1201.3]:	CU.M	767.80	441.70	326.10

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
MS1-026	REGRADING AND REGRAVELLING OF SHOULDERS WITH GRAVEL OF APPROVED QUALITY, DULY COMPACTED WITH ROLLER(8-10TONS) AS DIRECTED FOR REPAIRING HIGH SIDES CAUSED BY HEAVINGS DEPOSITS AND CONSTRUCTION DEBRIS, TO REQUIRED LEVELS BY USING A GRADER(120-140 HP) (GRAVEL TO BE PAID SEPARATELY)[SSCM 1201.3(b)]:	CU.M	344.30	0.00	344.30
MS1-027	REGRADING AND REGRAVELLING OF SHOULDERS WITH GRAVEL OF APPROVED QUALITY, DULY COMPACTED WITH ROLLER(8-10TONS) AS DIRECTED FOR REPAIRING HIGH SIDES CAUSED BY HEAVINGS DEPOSITS AND CONSTRUCTION DEBRIS, TO REQUIRED LEVELS MANUALLY (GRAVEL(LOOSE VOLUME) TO BE PAID SEPARATELY) [SSCM 1201.3(b)]:	CU.M	859.80	505.05	354.75
MS1-028	REPLACING THE DAMAGE CRACKED CONCRETE SLABS IN THE FOOT WALKS WITH PRECAST/CAST INSITU CEMENT CONCRETE 1:2:4(19MM) USING 19 MM & DOWN GAUGE STONE AGGREGATE TO A MINIMUM THICKNESS OF 50 MM INCLUDING FIXING/LAYING IN POSITION WITH CEMENT MOTAR 1:3 JOINTS OVER A COMPACTED BED ETC. EXCLUDING TRANSPORT OF AGGREGATE. [SSCM 1204.3]:	. SQ.M	3,275.40	2,307.52	967.88
MS1-029	CUTTING AND REMOVING FALLEN TREES UPTO 600 MM GIRTH INCLUDING CUTTING INTO REQUIRED NUMBER OF PIECES INCLUDING DISPOSAL AS DIRECTED. MINIMUM PIECES SHALL NOT BE LESS THAN 2.5 M LENGTH [SSCM 1203.2]	NO.	1,121.10	1,093.75	27.35
MS1-030	19 MM & DOWN GAUGE STONE AGGREGATE TO A MINIMUM THICKNESS OF 50 MM INCLUDING FIXING/LAYING IN POSITION WITH CEMENT MOTAR 1:3 JOINTS OVER A COMPACTED BED ETC. EXCLUDING TRANSPORT OF AGGREGATE. [SSCM 1204.3]: CUTTING AND REMOVING FALLEN TREES UPTO 600 MM GIRTH INCLUDING CUTTING INTO REQUIRED NUMBER OF PIECES INCLUDING DISPOSAL AS DIRECTED. MINIMUM PIECES SHALL NOT BE LESS THAN 2.5 M LENGTH [SSCM 1203.2] CUTTING AND REMOVING FALLEN TREES 600-900 MM GIRTH INCLUDING CUTTING INTO REQUIRED NUMBER OF PIECES INCLUDING DISPOSAL AS DIRECTED. MINIMUM PIECES SHALL NOT BE LESS THAN 2 M LENGTH [SSCM 1203.2] WEEDING MASONRY CULVERTS SMALL BRIDGES AND	NO.	1,601.55	1,562.50	39.05
MS1-031	WEEDING MASONRY CULVERTS SMALL BRIDGES AND RETAINING WALLS [SSCM 1303.3]:	NO.	391.90	275.00	116.90
MS1-032	MASONRY RANDOM RUBBLE WITH BOULDERS INCLUDING COLLECT[SSCM 1006.3(b)]:	CU.M	2,205.90	2,117.65	88.25
MS1-033	FIXING CATS EYES IN TAR MACADAM INCLUDING BREAKING ROAD SURFACE, BARRICADE ETC. [SSCM 810.3(C)]:	NO.	618.75	550.00	68.75
MS1-034	REDUCING HIGH SIDES IN ORDINARY SOIL [SSCM 301.3/1201.3 (c)]:	CU.M	958.50	883.39	75.11
MS1-035	REDUCING HIGH SIDES IN MEDIUM SOIL:	CU.M	1,411.20	1,325.09	86.11
MS1-036	REDUCING HIGH SIDES IN HARD SOIL:	CU.M	1,863.95	1,766.78	97.17
MS1-037	REDUCING HIGH SIDES IN SOFT ROCK:	CU.M	2,316.70	2,208.48	108.22
MS1-038	REDUCING HIGH SIDES IN ROCK REQUIRING BLASTING :	CU.M	5,623.25	3,003.53	2,619.72
MS1-039	WHITE WASHING 1 COAT TO PARAPETS OF BRIDGES AND CULVERTS.[SSCM 1403.3(e)]:	SQ.M	71.45	56.45	15.00

	MONARAGALA DISTRICT				
CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
MS1-040	WHITE WASHING 2 COATS TO PARAPETS OF BRIDGES AND CULVERTS:	SQ.M	120.05	98.79	21.26
MS1-041	WHITE WASHING 1 COAT TO PARAPETS OF BRIDGES AND CULVERTS AFTER CLEANING ATTENDING TO MINOR REPAIRS:	SQ.M	138.85	64.52	74.33
MS1-042	WHITE WASHING 2 COATS TO PARAPETS OF BRIDGES AND CULVERTS AFTER CLEANING ATTENDING TO MINOR REPAIRS:	SQ.M	193.65	112.90	80.75
MS1-043	PAINTING WITH EMULSION 1 COAT TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS AFTER CLEANING AND ATTENDING TO MINOR REPAIRS.[SSCM 1501.3(a)-(v)]:	SQ.M	348.85	165.77	183.08
MS1-044	OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS AFTER CLEANING AND ATTENDING TO MINOR REPAIRS.[SSCM 1501.3(a)-(v)]:	SQ.M	374.85	165.77	209.08
MS1-045	PAINTING WITH ENAMEL 2 COATS TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS AFTER CLEANING AND ATTENDING TO MINOR REPAIRS.[SSCM 1501.3(a)-(v)]:	SQ:M	374.85 600.30	308.93	291.37
MS1-046	PAINTING WITH ENAMEL 2 COATS TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS AFTER CLEANING AND ATTENDING TO MINOR REPAIRS.[SSCM 1501.3(a)-(v)]: PAINTING WITH EMULSION 2 COATS TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS AFTER CLEANING AND ATTENDING TO MINOR REPAIRS: PAINTING 1 COAT EMULSION PAINT TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS INCLUDING PREPARING SURFACE OF OLD WORK.[SSCM 1501.3(b)(v)]: PAINTING SUB COAT EMULSION PAINT TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND	SQ.M	568.55	308.93	259.62
MS1-047	PAINTING 1 COAT EMULSION PAINT TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS INCLUDING PREPARING SURFACE OF OLD WORK.[SSCM 1501.3(b)(v)]:	SQ.M	289.65	165.77	123.88
MS1-048	PAINTING SUB COAT EMULSION PAINT TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS INCLUDING PREPARING SURFACE SSCM 1501.3(b):	SQ.M	255.25	143.16	112.09
MS1-049	PAINTING 1 COAT EMULSION PAINT TO PARAPETS OF BRIDGES AND CULVERTS, GUARD STONES AND K.M. POSTS INCLUDING PREPARING SURFACE OF NEW WORK.[S.S.C.M. 1501.3 (b)(v)]:	SQ.M	266.45	143.16	123.29
MS1-050	CLEANING & PAINTING 100 MM WIDE STRIPE FOR SKIRTING TO GUARD STONES. [SSCM 1501.3(b)(v)]:	METRE	133.25	129.10	4.15
MS1-051	PAINTING 2 COATS STANDARD PEDESTRIAN CROSSING FOR CARRIAGEWAY. [SSCM 810.2(c)]:	METRE	3,296.95	2,348.02	948.93
MS1-052	PAINTING 1 COAT STANDARD PEDESTRIAN CROSSING FOR FOR CARRIAGEWAY USING ROAD MARKING PAINTS. [SSCM 810.2(c)]:	METRE	3,630.85	2,561.48	1,069.37
MS1-053	ERECTING, BARRICADING IN JUNGLE TIMBER 75 - 100 MM DIA. VERTICAL POSTS AT .9 M CENTRES AND 1.2 M ABOVE GROUND INCLUDING WHITE WASHING.[SSCM 1709]:	METRE	923.50	341.53	581.97
MS1-054	TEMPORARY SCAFFOLDING FOR PAINTING OR TARRING BRIDGES AND FOR WEEDING ON BRIDGES OR RETAINING WALL INCLUDING DISMANTLING AFTER WORK.[SSCM 1008.3(a)]:	SQM	207.90	177.42	30.48

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
MS1-055	ROUGHNING EXISTING SMOOTH TARRED METALLED CARRIAGEWAY BY HAND FOR BONDING, COLLECTING DISPOSAL OF ALL LOOSE MATERIALS.[SSCM 403.3(b)]:	SQ.M	30.30	29.57	0.73
MS1-056	SUPPLY OF DIESEL FOR MACHINERIES: (EX-FILLING STATION):	LITRE	286.00	0.00	286.00
MS1-057	PATCHING ROAD WITH PREMIX (LOOSE VOLUME) AFTER PREP. SURFACE WITH EMULSION(CSS-1) AT .75 LTR/SQ.M AS TACK COAT, INCLUDING INTERNAL TRANSPORT AND HAND TAMPING. (SUPPLY OF PREMIX(LOOSE VOL.) PAID SEPARATELY) [SSCM 1102.3(b)(i)]:	CU.M	9,183.00	6,492.93	2,690.07
MS1-058	PATCHING ROAD WITH PREMIX AFTER PREPARING SURFACE WITH EMULSION(CSS-1) AT .75 LTR/SQ.M AS TACK COAT, INCLUDING INTERNAL TRANSPORT AND STAMPING WITH MACHINE.(SUPPLY OF PREMIX PAID SEPARATELY) [SSCM 1102.3(b)(i)]:	M.TON	8,994.65	6,142.86	2,851.79
MS1-059	PAINTING TWO COATS ENAMAL PAINT ON KERBS, AFTER CLEANING AND PREPARING SURFACE.	SQ.M	602.10	403.12	198.98
MS1-060	PREPARING AND STOCK PILING PREMIX AT SITE USING 12.5 MM AGGREGATE AND EMULSION CSS-1. (EXCLUDING TRANSPORT OF AGGREGATE): BREAKING MANUALLY ASPHALT LAYER 2"-3" THICK ON THE CARRIAGEWAY FOR KERB LAYING CUITTING AND REMOVING TREES 300-600MM GIRTH INCLUDING DISPOSAL AS	CU.M	19,183.70	4,505.30	14,678.40
MS1-061	BREAKING MANUALLY ASPHALT LAYER 2"-3" THICK ON THE CARRIAGEWAY FOR KERB LAYING	L.M	744.75	726.56	18.19
MS1-062	CUTTING AND REMOVING TREES 300-600MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	6,389.15	687.50	5,701.65
MS1-063	CUTTING AND REMOVING TREES 600-1200MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	7,686.25	1,062.50	6,623.75
MS1-064	CUTTING AND REMOVING TREES 1200-2000MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	9,143.55	1,593.75	7,549.80
MS1-065	CUTTING AND REMOVING TREES OVER 2000MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	24,122.40	4,500.00	19,622.40
MS1-066	CUTTING AND REMOVING OF OVERHANGING BRANCHES 300-600MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	1,537.50	1,500.00	37.50
MS1-067	CUTTING AND REMOVING OF OVERHANGING BRANCHES 600-1200MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	5,189.05	5,062.50	126.55
MS1-068	CUTTING AND REMOVING OF OVERHANGING BRANCHES OVER 1200MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	6,918.75	6,750.00	168.75
MS1-069	REMOVING OF STUMPS 300-600MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	3,806.25	156.25	3,650.00
MS1-070	REMOVING OF STUMPS 600-1200MM GIRTH INCLUDING DISPOSAL AS DIRECTED	NO	5,629.30	156.25	5,473.05
MS1-071	REMOVING STRINGS OF BARBED WIRE FENCE	L.M	8.55	8.33	0.22

* * *

HIGHWAY SCHEDULE OF RATES - SUMMARY 2025

MONARAGALA DISTRICT

CODE	DESCRIPTION OF ITEM	UNIT	AMOUNT RS.	LABOUR INPUT	OTHER INPUTS
	SECTION XIV				
	======== SURVEYING, LEVELLING AND DAYWORKS				
SV1-001	SUPPLY OF UNSKILLED LABOUR:	DAY	2,500.00	2,500.00	0.00
SV1-002	SUPPLY OF SEMISKILLED LABOUR:	DAY	2,750.00	2,750.00	0.00
SV1-003	SUPPLY OF SKILLED 'A' GRADE LABOUR:	DAY	3,750.00	3,750.00	0.00
SV1-004	SUPPLY OF SKILLED 'B' GRADE LABOUR:	DAY	3,500.00	3,500.00	0.00
SV1-005	CLEARING JUNGLE (LIGHT) TO A WIDTH OF 1.22 METRES FOR SURVEY WORK:	K.M	9,549.70	9,316.77	232.93
SV1-006	CLEARING JUNGLE (MEDIUM) TO A WIDTH OF 1.22 METRES FOR SURVEY WORK:	K.M	12,732.90	12,422.36	310.54
SV1-007	CLEARING JUNGLE (HEAVY) TO A WIDTH OF 1.22 METRES FOR SURVEY WORK:	K.M	19,099.40	18,633.54	465.86
SV1-008	SUPPLY OF LABOUR FOR CHAINING AND CUTTING PEGS AND PEGGING:	K.M	2,626.15	2,562.11	64.04
SV1-009	LEVELLING CHAINING AND PEGGING AND ESTABLISHING BENCH MARKS ON CONCRETE ROCK OR PEGS AND CHECKING BACK LEVELS:	K.M	5,252.35	5,124.22	128.13
SV1-010	SURVEYING INCLUDING FIXING PICKETS & TAKING ANGLES:	K.M	5,252.35	5,124.22	128.13
SV1-011	CHANGING TRAVERSE LINES AND TAKING OFF-SETS:	K.M	7,003.10	6,832.30	170.80
	CLEARING JUNGLE (MEDIUM) TO A WIDTH OF 1.22 METRES FOR SURVEY WORK: CLEARING JUNGLE (HEAVY) TO A WIDTH OF 1.22 METRES FOR SURVEY WORK: SUPPLY OF LABOUR FOR CHAINING AND CUTTING PEGS AND PEGGING: LEVELLING CHAINING AND PEGGING AND ESTABLISHING BENCH MARKS ON CONCRETE ROCK OR PEGS AND CHECKING BACK LEVELS: SURVEYING INCLUDING FIXING PICKETS & TAKING ANGLES: CHANGING TRAVERSE LINES AND TAKING OFF-SETS: ***				

- NOTE: 1. TRANSPORT COST OF ALL RAW MATERIALS AND ROYALTY INCLUDED IN THE GIVEN PRICES.
 - 2. PRICES FROM THE ASPHALT CONCRETE MIXING PLANT CLOSEST TO THE WORK SITE, WHICH IS ABLE TO SUPPLY THE REQUIRED TYPE (HOT/COLD) SHALL BE CONSIDERED.
 - 3. ADD PREMIX TRANSPORT FROM MIXING PLANT TO THE WORK SITE, SEPARATELY
 - 4. BINDER % OF B0-361A, B0-362, B0-362A AND B0-365 ARE BY TOTAL MIX WEIGHT AND BINDER % OF B0-366 IS BY TOTAL WEIGHT OF AGGREGATE

			PRICE : EX-PLANT COST RS. PER M.Ton													
DISTRICT			COL	ОМВО	GAM	GAMPAHA		UTARA	GALLE		MA	TARA	НАМВ	ANTOTA		
LOCATION												110.				
CODE	AGG. SIZE	UNIT	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE		
B0-361	19 mm	PER M.T.	-	NIL	-	NIL	-	NIL	-	NIL	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	NIL	-	NIL		
B0-361A	19 mm	PER M.T.	4.70	14,402.00	4.70	14,317.00	4.70	14,442.00	4.70	14,528.00	4.70	14,581.00	4.70	14,617.00		
BO -361B	19 mm	PER M.T.	-	6,868.00	-	6,739.00	-	6,858.00	-	6,468.00	-	6,454.00	-	6,346.00		
B0-362	37.5 mm	PER M.T.	3.40	12,351.00	3.40	12,233.00	3.40	12,397.00	3.40	12,506.00	3.40	12,430.00	3.40	12,435.00		
B0-362A	19 mm	PER M.T.	4.10	13,432.00	4.10	13,366.00	4.10	13,465.00	4.10	13,575.00	4.10	13,593.00	4.10	13,641.00		
BO -362B	19 mm	PER M.T.	-	6,850.00	-	6,750.00	-	6,840.00	16	6,817.00	-	6,727.00	-	6,624.00		
B0-365 *	19 mm	PER M.T.	5.50	15,960.00	5.50	15,904.00	5.50	15,998.00	5.50	16,136.00	5.50	16,161.00	5.50	16,234.00		
B0-365A**	19 mm	PER M.T.	5.50	16,052.00	5.50	15,952.00	5.50	16,089.00	5.50	16,071.00	5.50	16,203.00	5.50	16,211.00		
B0-366***	19 mm	PER M.T.	6.67	11,289.00	6.67	10,760.00	6.67	10,724.00	6.67	11,112.00	6.67	11,060.00	6.67	10,931.00		
B0-366A	19 mm	PER M.T.	5.90	11,056.00	5.90	10,933.00	5.90	11,025.00	5.90	10,857.00	5.90	10,929.00	5.90	10,803.00		

^{*} Binder for B0-365 is 15% cut-back with Bitumen 60/70 penetration grade; 19mm Aggregate

^{**} Binder for B0-365A is 16% cut-back with Bitumen 60/70 penetration grade; 12.5 Aggregate

^{***} Binder for B0-366 is Emulsion CSS-1

- NOTE: 1. TRANSPORT COST OF ALL RAW MATERIALS AND ROYALTY INCLUDED IN THE GIVEN PRICES.
 - 2. PRICES FROM THE ASPHALT CONCRETE MIXING PLANT CLOSEST TO THE WORK SITE, WHICH IS ABLE TO SUPPLY THE REQUIRED TYPE (HOT/COLD) SHALL BE CONSIDERED.
 - 3. ADD PREMIX TRANSPORT FROM MIXING PLANT TO THE WORK SITE, SEPARATELY
 - 4. BINDER % OF B0-361A, B0-362, B0-362A AND B0-365 ARE BY TOTAL MIX WEIGHT AND BINDER % OF B0-366 IS BY TOTAL WEIGHT OF AGGREGATE

								PRICE : E	X-PLANT COST RS. PER M.Ton									
DISTRICT			КА	NDY	МАТ	HALE	NUWA	RAELIYA	KURU	INEGALA	PU	ГLАМ	MONA	RAGALA	BAD	ULLA		
LOCATION												110.						
CODE	AGG. SIZE	UNIT	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE		
B0-361	19 mm	PER M.T.	-	NIL	-	NIL	-	NIL	-	NIL	7	NIL	-	NIL	-	NIL		
B0-361A	19 mm	PER M.T.	4.70	14,773.00	4.70	15,137.00	4.70	15,335.00	4.70	14,371.00	4.70	14,427.00	4.70	14,543.00	4.70	14,642.00		
B0-361B	19 mm	PER M.T.	-	7,018.00	-	7,270.00	-	7,506.00	-	5,039.00	<i>-</i> -	6,660.00	-	6,510.00	-	6,671.00		
B0-362	37.5 mm	PER M.T.	3.40	12,718.00	3.40	13,054.00	3.40	13,226.00	3.40	12,349.00	3.40	12,189.00	3.40	12,421.00	3.40	12,478.00		
B0-362A	19 mm	PER M.T.	4.10	13,862.00	4.10	14,195.00	4.10	14,362.00	4.10	13,439.00	4.10	13,293.00	4.10	13,567.00	4.10	13,729.00		
B0-362B	19 mm	PER M.T.	-	7,101.00	-	7,331.00	-	7,527.00	:(5)	6,747.00	-	6,486.00	-	6,580.00	-	6,805.00		
B0-365 *	19 mm	PER M.T.	5.50	16,412.00	5.50	16,744.00	5.50	16,895.00	5.50	15,991.00	5.50	15,863.00	5.50	16,161.00	5.50	16,315.00		
B0-365A**	19 mm	PER M.T.	5.50	16,355.00	5.50	16,821.00	5.50	16,984.00	5.50	15,954.00	5.50	15,972.00	5.50	16,167.00	5.50	16,216.00		
B0-366***	19 mm	PER M.T.	6.67	11,043.00	6.67	11,537.00	6.67	11,767.00	6.67	11,070.00	6.67	10,837.00	6.67	10,877.00	6.67	11,026.00		
B0-366A	19 mm	PER M.T.	5.90	11,139.00	5.90	11,520.00	5.90	11,620.00	5.90	10,782.00	5.90	10,719.00	5.90	10,694.00	5.90	10,816.00		

^{*} Binder for B0-365 is 15% cut-back with Bitumen 60/70 penetration grade; 19mm Aggregate

Asphalt Rates -: HSR-2025

^{**} Binder for B0-365A is 16% cut-back with Bitumen 60/70 penetration grade; 12.5 Aggregate

^{***} Binder for B0-366 is Emulsion CSS-1

NOTE: 1. TRANSPORT COST OF ALL RAW MATERIALS AND ROYALTY INCLUDED IN THE GIVEN PRICES.

- 2. PRICES FROM THE ASPHALT CONCRETE MIXING PLANT CLOSEST TO THE WORK SITE, WHICH IS ABLE TO SUPPLY THE REQUIRED TYPE (HOT/COLD) SHALL BE CONSIDERED.
- 3. ADD PREMIX TRANSPORT FROM MIXING PLANT TO THE WORK SITE, SEPARATELY
- 4. BINDER % OF B0-361A, B0-362, B0-362A AND B0-365 ARE BY TOTAL MIX WEIGHT AND BINDER % OF B0-366 IS BY TOTAL WEIGHT OF AGGREGATE

								COST RS. PI	ER M.Ton							
DISTRICT	DISTRICT			TRICT		ANURAI	DHAPURA POLONNARUWA RATHNAPURA		KE	GALLE	TRINCOMALLEE		BATTICALOA		АМІ	PARA
LOCATION												,,0				
CODE	AGG. SIZE	UNIT	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE
B0-361	19 mm	PER M.T.	-	NIL		NIL	-	NIL	-	NIL	7	NIL	-	NIL	-	NIL
B0-361A	19 mm	PER M.T.	4.70	14,672.00	4.70	14,711.00	4.70	14,865.00	4.70	14,047.00	4.70	14,592.00	4.70	15,866.00	4.70	15,088.00
B0-361B	19 mm	PER M.T.	-	6,785.00	-	6,784.00	-	7,177.00	-	6,354.00	- 7	6,500.00	-	7,658.00	-	6,928.00
B0-362	37.5 mm	PER M.T.	3.40	12,490.00	3.40	12,568.00	3.40	12,825.00	3.40	12,021.00	3.40	12,432.00	3.40	13,659.00	3.40	12,924.00
B0-362A	19 mm	PER M.T.	4.10	13,755.00	4.10	13,829.00	4.10	13,909.00	4.10	13,159.00	4.10	13,682.00	4.10	14,949.00	4.10	14,137.00
B0-362B	19 mm	PER M.T.	-	6,851.00	-	6,875.00	-	7,196.00	3	6,462.00	-	6,656.00	-	7,822.00	-	7,037.00
B0-365 *	19 mm	PER M.T.	5.50	16,387.00	5.50	16,418.00	5.50	16,442.00	5.50	15,729.00	5.50	16,284.00	5.50	17,518.00	5.50	16,728.00
B0-365A**	19 mm	PER M.T.	5.50	16,231.00	5.50	16,297.00	5.50	16,531.00	5.50	15,652.00	5.50	16,173.00	5.50	17,432.00	5.50	16,670.00
B0-366***	19 mm	PER M.T.	6.67	11,100.00	6.67	11,147.00	6.67	11,457.00	6.67	10,754.00	6.67	10,877.00	6.67	11,910.00	6.67	11,253.00
B0-366A	19 mm	PER M.T.	5.90	10,955.00	5.90	11,018.00	5.90	11,317.00	5.90	10,560.00	5.90	10,707.00	5.90	11,766.00	5.90	11,063.00

^{*} Binder for B0-365 is 15% cut-back with Bitumen 60/70 penetration grade; 19mm Aggregate

Asphalt Rates -: HSR-2025

^{**} Binder for B0-365A is 16% cut-back with Bitumen 60/70 penetration grade; 12.5 Aggregate

^{***} Binder for B0-366 is Emulsion CSS-1

- NOTE: 1. TRANSPORT COST OF ALL RAW MATERIALS AND ROYALTY INCLUDED IN THE GIVEN PRICES.
 - 2. PRICES FROM THE ASPHALT CONCRETE MIXING PLANT CLOSEST TO THE WORK SITE, WHICH IS ABLE TO SUPPLY THE REQUIRED TYPE (HOT/COLD) SHALL BE CONSIDERED.
 - 3. ADD PREMIX TRANSPORT FROM MIXING PLANT TO THE WORK SITE, SEPARATELY
 - 4. BINDER % OF B0-361A, B0-362, B0-362A AND B0-365 ARE BY TOTAL MIX WEIGHT AND BINDER % OF B0-366 IS BY TOTAL WEIGHT OF AGGREGATE

						PRICE : E	COST RS. P	S. PER M.Ton							
DISTRICT			MAI	NNAR	KILIN	оснсні	MULL	AITIVU	VAV	UNIYA	JA	FFNA			
LOCATION												,'(0)			
CODE	AGG. SIZE	UNIT	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE	% BINDER	PRICE			
B0-361	19 mm	PER M.T.			-		-		-	NIL	7				
B0-361A	19 mm	PER M.T.	4.70	14,506.00	4.70	14,360.00	4.70	14,532.00	4.70	14,903.00	4.70	14,386.00			
B0-361B	19 mm	PER M.T.	-	6,258.00	-	6,161.00	-	6,376.00	-	6,791.00	11-	6,111.00			
B0-362	37.5 mm	PER M.T.	3.40	12,327.00	3.40	12,212.00	3.40	12,393.00	3.40	12,744.00	3.40	12,214.00			
B0-362A	19 mm	PER M.T.	4.10	13,627.00	4.10	13,460.00	4.10	13,582.00	4.10	14,002.00	4.10	13,465.00			
B0-362B	19 mm	PER M.T.	-	6,486.00	-	6,349.00	-	6,488.00		6,965.00	-	6,282.00			
B0-365 *	19 mm	PER M.T.	5.50	16,255.00	5.50	16,088.00	5.50	16,195.00	5.50	16,595.00	5.50	16,102.00			
B0-365A**	19 mm	PER M.T.	5.50	16,078.00	5.50	15,915.00	5.50	16,116.00	5.50	16,517.00	5.50	15,925.00			
B0-366***	19 mm	PER M.T.	6.67	10,668.00	6.67	10,576.00	6.67	10,748.00	6.67	11,145.00	6.67	10,676.00			
B0-366A	19 mm	PER M.T.	5.90	10,547.00	5.90	10,380.00	5.90	10,546.00	5.90	11,061.00	5.90	10,566.00			

^{*} Binder for B0-365 is 15% cut-back with Bitumen 60/70 penetration grade; 19mm Aggregate

Asphalt Rates -: HSR-2025

^{**} Binder for B0-365A is 16% cut-back with Bitumen 60/70 penetration grade; 12.5 Aggregate

^{***} Binder for B0-366 is Emulsion CSS-1

SPECIFICATIONS RELATED TO THE HSR ITEMS HSR-2025

1. EARTHWORKS:

a) Embankment Construction- SSCM section 304:

Type I material MDD>=1600kg/m^3 Type II material MDD>=1500kg/m^3

HSR items: EW1-011, EW1-014

b) Soil for road shoulders and gravel surfacing- SSCM section 409 & 601:

Table 1708-1

Sieve size	Percentage
mm	passing
37.5	100
20	77 -100
5	41 -100
2.36	30 - 80
0.6	18 - 50
0.075	05 - 25

- Consistancy limits for road shoulder materials and gravel surfacings. Table 1708-2

	•	71 100	
	2.36	30 - 80	
	0.6	18 - 50	
	0.075	05 - 25	
			Ċ
	Table 1708-2	- Consistancy lim	its for road shoulder materials and gr
	Climatic Zone	LL	Pl 4 -25 6 - 25
	Wet zone	<55	4 -25
	Dry Zone	< 55	6 - 25
)	Sub Base : CBR >=20% LL <=40 PI <=15		ight Highways, h
	HSR items :	EW1-001, EW1-0	13
)	Aggregates : Single size aggregate be	O. L. L. Coll.	, & 12.5 mm - SSCM section 403 :
	Table 1701-4	18	
	Ciava Ciaa	~	Doroontogo possing

c) Sub Base:

2. Aggregates:

a) Single size aggregate bases - 50, 37.5, 19, & 12.5 mm - SSCM section 403 :

Table 1/01-4							
Sieve Size	Percentage passing						
B.		Nominal size in mm					
mm	50	37.5	19	12.5			
63	100	-	-	-			
50	85 - 100	100	-	-			
37.5	0 - 30	85 - 100	-	-			
28	0 - 7	0 - 30	100	-			
20	0 - 2	0 - 7	85 - 100	100			
14	-	0 - 2	0 - 35	85 - 100			
10	-	-	0 - 7	0 - 35			
5	-	-	-	0 - 5			
2.36	_	_	0 - 2	0 - 2			

AIV <= 30%

FI <= 35%

HSR items: M1-004, M1-007, M1-008, M1-009, A1-005 TO A1-012

SPECIFICATIONS RELATED TO THE HSR ITEMS HSR-2025

b) Water bound macadam and Dry bound macadum - SSCM section 404 : (50 or 63 mm and crusher fines)

Table 1701-6

Sieve Size		7	
	Nominal max size of agg in mm		Crusher fines
mm	63	50	
75	100	-	-
63	90 - 100	100.0	-
50	30 - 70	90 - 100	-
37.5	0 - 15	30 - 70	-
28	-	0 - 15	-
20	0 - 5	-	-
14	-	0 - 5	-
10	-	-	100.0
5	-	-	85 - 100
0.150	-	-	10 - 30

AIV <= 30% FI <= 35%

HSR items: M1-010, M1-011

c) Penetration macadum base - SSCM section 406 :

Table 1701-7

1 abic 1701-7			V V			
Sieve Size	Percentage passing					
	Nominal size in mm					
mm	50	37.5	20	14		
63	100	0 1 - 0	-	-		
50	-	1000 5	-	-		
37.5	50-73	12 oct 13	-	-		
28	-	46-72	100	-		
20	7-26	dil .: dl	52-68	100		
14	- /:	7-27	-	63-88		
10	- <	(X · ·	7-25	-		
5	-	-0	-	6-35		
2.36	0-3	0-3	0-3	0-3		
1.18	- 20.	1 -	-	-		

AIV <= 30% FI <= 35%

HSR items : \$1-037, S1-038

d) Dense Graded Aggregate Bases: SSCM section 405

(ABC construction)

Table 1701-5

14010 1701 0							
Sieve Size		Percentage passing					
		Nominal size in mm					
mm	37.5	28	20				
50	100	=	-				
37.5	95-100	100	-				
28	-	-	100				
20	60-80	70-85	90-100				
10	40-60	50-65	60-75				
5	25-40	35-55	40-60				
2.36	15-30	25-40	30-45				
0.425	7-19	12-24	13-27				
0.75	5-12	5-12	5-12				

AIV <= 30% FI <= 35% CBR >=80%

HSR items: M1-012, M1-013

SPECIFICATIONS RELATED TO THE HSR ITEMS HSR-2025

e) Aggregate grading, binder content and thickness requirements - SSCM section 407 :

Table 407-1

Mix Classification no.	1	2	3	4
Nominal maximum size				
of aggregate in mm	37.5	37.5	19	19
Course	Dense graded	Open graded	Dense graded	Open graded
Thickness mm - Max	100	100	50	40
- Min	60	60	30	30
Sieve size mm		Total % by wei	ght passing	
50	100	100	-	-
37.5	95 -100	95 -100	-	-
28	80-95	53-75	100	100
20	-	-	80-98	96-100
14.0	62-77	10-27	-	50-75
10.0	-	-	49-67	22-42
5.00	-	-	29-44	
2.36	30 - 45	0 - 10	18-30	5 - 20
1.180	-	-	13-24	0-2
300	-	-	5-14	71.
Percent binder content			:	Y
by total weight of mix	3.0 - 4.0	2.5 - 3.5	3.5-4.5	3.0 - 4.0

AIV <= 30% FI <= 35%

HSR items: B0-362, S1-032

3 Surfacing:

a) Asphalt concrete - SSCM section 506 :

Table 506-1

Table 300-T	· ·	- C - C - C - C - C - C - C - C - C - C	
Mix Classification	Binder Course	Wearing Course	Wearing Course
No. Course	C	Type - 1	Type - 2
Thickness mm -	18		
Max	75	75	75
Min	35	35	35
Sieve size mm	Total % by w	eight passing includi	ng filler if used
28	100	100	-
20	90-100	85-100	100
14.00	-	-	82-92
10.0	56-82	66-94	61-81
5.00	36-58	46-74	41-66
2.36	21-38	35-58	27-48
1.18	15-32	26-48	20-40
0.600	10-26	18 - 38	15-35
0.300	6-20	11-28	10-25
0.150	3-13	07-20	7-17
0.075	1-7	3-12	5-9
Percent binder			
content by total	3.5 - 4.5	4.0-6.5	4.0-6.0
weight of mix			

AIV <= 30% FI <= 35% LAAV <= 40%

HSR items: B0-361, S1-031, B0-362A

SPECIFICATIONS RELATED TO THE HSR ITEMS HSR-2025

b) Seal Coat treatments (Surface dressing) - SSCM section 505:

Table 1701-8

Sieve Size	Percentage passing					
		Nominal size in mm				
mm	19	12.5	9.5	6.3		
25	100	-	-	-		
19	85 - 100	100	-	-		
12.5	0 - 25	85 - 100	100	-		
9.5	0 - 7	0 - 25	85 - 100	100		
6.3	-	-	0 - 25	85 - 100		
4.75	-	0 - 7	0 - 10	-		
2.36	0 - 2	0 - 2	0 - 2	0 - 10		
0.075	0 - 0.5	0 - 0.5	0 - 0.5	0 - 0.5		

AIV <= 30% FI <= 35% LAAV <= 40%

HSR items : S1-003, S1-004, S1-005, S1-006, S1-029, S1-030

c) Cold mix surfacings - SSCM section 507 :

Table 507.1

Grading type	Dense	e graded	Open gra	aded
Nominal max size	19 mm	12.5 mm	19 mm	12.5 mm
of aggregate		١.		
Sieve size mm		Total percentage passing by weight		
25	100	00, 11,	100	-
19	90 - 100	100	90 - 100	100
12.5	-	90 - 100	60 - 80	85 - 100
9.5	56 - 80	12. 4. A.	-	-
4.75	35 - 65	44 - 74	18 - 35	35 - 50
2.36	23 - 49	28 - 56	-	15 - 30
0.300	05 - 20	05 22	-	-
0.075	0 - 05	0 - 08	0 - 03	0 - 03
Percent binder as % of	*	OLC.		
wgt of Aggregate	C'	2		
(a) Cutback Bitumen	4.5 - 5.5	5.0 - 6.0	4.5 - 5.0	4.5 - 5.0
(b) Emulsion	5.0 - 6.0	5.5 - 6.5	4.5 - 5.5	5.0 - 6.0

AIV <= 30% FI <= 35% LAAV < 40%

HSR items : B0-365, B0-366, S1-033, S1-033A

4. Binder for Surface applications

a) Prime coat - CSS-1 emiulsion - SSCM section 1702.3 : shall conform to ASTM D2397-98

Cutback bitumen(20-45%) or MC-30, MC-70 or MC-250 or MC-800: SSCM section 1702.2

HSR items : B0-352, S1-022, S1- 023, S1-024, S1-025

b) Sand seal - CRS-1 emulsion - SSCM section 1702.3 : HSR items : B0-353, S1-011, S1-012, S1-013, Tack coat - shall conform to ASTM D2397-98 S1-014, S1-027, S1-035, S1-036

Cutback bitumen (8 - 12%) - SSCM section 1702.2 Bitumen 80 - 100 penetration grade bitumen - SSCM section 1702.1

c) Surface dressing - CRS-2 emulsion - SSCM section 1702.3

Residue on distillation minimum 65% shall conform to ASTM D2397-98 Viscosity min. 100 Saybolt furol seconds

HSR items : B0-354, S1-029, S1-030

	nula for Earth Excavation using Machinery t				1	1					
	er HP and Blade Dimensions received from DG	M(mech)/RC8									
Α.	Excavation :		Unit		L.,						
i	Dozer type :		LIB		- H		- E		- G	D8 -	
	Horse power Hire charge for Dozer	Do	HP		0.405.05	6.435.85	0 405 05	20		10.015.01	
	nile charge for bozer	Rs.	per Hour (wet)	0,430.60	6,435.85	0,430.60	6,435.85	8,756.46	8,756.46	10,215.31	10,215.31
ii	Cutting Blade Details :										
ш.	Length of Load(Blade length)	L	m	2.636	2.636	3.12	3.12	4.27	4.27	4.965	4.965
	Blade height	H	m	1.085				0.97	0.97	1.174	1.174
iii	Assumptions :										
	Slope of cut *	S	ratio	2	:1						
	Width of Load	W=2XH	m	2.17	2.17	2	2	1.94	1.94	2.348	2.348
	Haul distance	D	m	30			60	30	60	30	60
	Average Forward speed		km/h	2.25	2.25	2.25	2.25	2.70	2.70	2.70	2.70
	Avreage time for forward push	=A	minutes	0.8				0.67	1.33	0.67	1.33
	Average Reverse speed	-	km/h	2.85	2.85	3.50		3.50	3.50	2.50	2.50
	Average time for return Ave. time loading and changing Gears	=B	minutes	0.63	1.26 0.35	+	1.03	0.51	1.03	0.72	1.44
	Efficency of Operater	=C E	minutes per cycle %	0.35 75	75	0.35 75	0.35 75	0.35 75	0.35 75	0.35 75	0.35 75
	Break for rest in each hour	R	minutes	10				10	10	10	10
	Average cycle time for Pushing,	••	minutes	10	10	10	10	10	10	10	10
	Returning, Changing gears etc.	T=(A+B+C)	minutes	1.78	3.21	1.66	2.98	1.53	2.71	1.74	3.12
	Bulking factor	В	%	15	-			15	15	15	15
iv	Moldboard capacity :						.0	.0		.5	10
Ė	Volume(Bank) of Cut (LxHxW)/S		cu.m(bank)	3.10	3.10	3.12	3.12	4.02	4.02	6.84	6.84
V	Net loose volume per cycle	٧	cu.m(loose)	3.57	3.57	3.59	3.59	4.62	4.62	7.87	7.87
	Probable cycle output per hour	-						0			
	Cycle output per Hour C=[(60-R)/T]xE/100		cycles/Hr	21.07	11.68		12.58	24.51	13.84	21.55	12.02
vi	Net loose volume per hour	v=CxV	cu.m(bulked)	75.22	41.7	81.1	45.16	113.24	63.94	169.6	94.6
	Net loose volume per day (5 hours)			376.1	208.5	405.5	225.8	566.2	319.7	848	473
	Operational than times to Co			427.85			07				
-	Considering the time for Servicing,		houre/day		1		1	_	1	1	
	Fuelling & Cleaning as Working time	t	hours/day hours/day	6				1 6	6	6	6
	Output per 6 Hours	=txV	cu.m per day	451.32	250.2	486.6		679.44	383.64	1017.6	567.6
vii	Average cost per Cu.m Loose	-17.4	Rs.	85.56				77.33	136.95	60.23	107.98
V.I.	7 Wording Cook por Carm 20000		110.	00.00	101.01	70.00	142.01	77.00	100.00	00.20	107.00
	Average for each dozer			119.95	0, 1	110.93		107.14		84.11	
				/ 19	X9			-			
			0,9	V/A,	-0,						
В.	Loading:		, ,	\bigcirc . \langle	7						
i	Hire Charge for wheel loader 2.7 cu.m		hour(wet)	7,043.20	•	B0-124					
			11: 12.	73.							
	One way haul distance up to :	d	m	10							
	The Maximum time for loading cycle	t	minutes	1.2							
	Capacity of loader bucket	v	cu.m	2.7							
	Assume working time per hour	-									
		T	minutes	50							
	Assume loading bucket efficency	E /	minutes	0.8							
ii	Assume loading bucket efficency Assume machine operater efficency	E e	minutes	0.8 0.75		[/T/t\					
ii	Assume loading bucket efficency Assume machine operater efficency No of loads per hour	E e n	10/4	0.8 0.75 41.66667		[(T/t)	FI				
ii iii	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour	E e	cu.m	0.8 0.75		[(T/t) [v x n x e x	E]				
	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to	E e n	cū.m	0.8 0.75 41.66667 67.5			E]				
	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose)	E e n	10/4	0.8 0.75 41.66667			E]				
iii	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles	E e n	cu.m hours	0.8 0.75 41.66667 67.5			E]				
iii	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose)	E e n	cu.m hours cu.m	0.8 0.75 41.66667 67.5 5 337.5		[v x n x e x	E]				
iii	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose)	E e n	cu.m hours cu.m	0.8 0.75 41.66667 67.5 5 337.5		[v x n x e x		211.48		188.45	
iii	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading	E e n	cu.m hours cu.m	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base &	E e n	cu.m hours cu.m	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials:	E e n	cu.m hours cu.m	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and	E e n	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials:	E e n	cu.m hours cu.m	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance %	E e n	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill	E e n	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials:	E e n	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill	E e n	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance %	E e n	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of	E e n	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34		[v x n x e x		211.48		188.45	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for	E e n V	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29		per cu.m 215.28					
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders	E e n V	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29		per cu.m 215.28		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for	E e n V	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29		per cu.m 215.28					
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material	E e n V Cu.m(loose)	ou.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29		per cu.m 215.28 269.10 236.81		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average	E e n V Cu.m(loose) Cu.m(loose) total cost	cu.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29	Excluding	per cu.m 215.28 269.10 236.81 Deverheads		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material	E e n V Cu.m(loose)	cu.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29		per cu.m 215.28 269.10 236.81 Deverheads		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average	E e n V Cu.m(loose) Cu.m(loose) total cost	cu.m hours cu.m Rs.	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29	Excluding	per cu.m 215.28 269.10 236.81 Deverheads		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average Embankment fill material, Average	E e n V Cu.m(loose) Cu.m(loose) total cost	ou.m hours cu.m Rs. 25	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29	Excluding 6	per cu.m 215.28 269.10 236.81 Deverheads		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average Embankment fill material, Average Say, For Bases, Sub Bases and	E e n V Cu.m(loose) Cu.m(loose) total cost	ou.m hours cu.m Rs. 25	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29 280.37 246.72 per cu.m per cu.m	Excluding 6	per cu.m 215.28 269.10 236.81 overheads		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average Embankment fill material, Average Say, For Bases, Sub Bases and	E e n V Cu.m(loose) Cu.m(loose) total cost	cu.m hours cu.m Rs. 25 10 262.34 230.86	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29 280.37 246.72 per cu.m per cu.m	Excluding 6 Excluding 6	per cu.m 215.28 269.10 236.81 overheads		264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average Embankment fill material, Average Say, For Bases, Sub Bases and Shoulders	E e n V V Cu.m(loose) Cu.m(loose) Cu.m(loose) total cost total cost	eu.m hours cu.m Rs. 25 10 262.34 230.86	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29 280.37 246.72 per cu.m per cu.m	Excluding 6 Excluding 6	269.10 236.81 269.20 269.20 27 236.81 28 29 29 29 29 29 29 29 29 29 29 29 29 29	B0-201	264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average Embankment fill material, Average Say, For Bases, Sub Bases and Shoulders	E e n V V Cu.m(loose) Cu.m(loose) Cu.m(loose) total cost total cost	eu.m hours cu.m Rs. 25 10 262.34 230.86 262.30 230.90	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29 280.37 246.72 per cu.m per cu.m	Excluding of T42.44	per cu.m 215.28 269.10 236.81 20verheads per cube	B0-201	264.35		235.56	
iii iv v	Assume loading bucket efficency Assume machine operater efficency No of loads per hour Loading capacity per hour Assume 5 hours working for loader due to Queing and delays in transport vehicles Out put per day (Loose) Cost of loading per Cu.m (Loose) Sub Total cost of excavation & loading For excavation of Base, Sub Base & Shoulder materials: Allow for borrow pit estiblishment and site maintenance % For excavation of Embankment fill materials: Allow for borrow pit estiblishment and site maintenance % Total cost of excavation and supply of Soil for Sub Bases, Bases and Shoulders Embankment fill material Sub Bases, Bases and Shoulders, Average Embankment fill material, Average Say, For Bases, Sub Bases and Shoulders	E e n V Cu.m(loose) Cu.m(loose) Cu.m(loose) Cutotal cost total cost Rate Rs.	262.34 230.90 230.90	0.8 0.75 41.66667 67.5 5 337.5 104.34 224.29 280.37 246.72 per cu.m per cu.m	Excluding 6 Excluding 6 742.44 653.34	269.10 236.81 269.20 269.20 27 236.81 28 29 29 29 29 29 29 29 29 29 29 29 29 29	B0-201	264.35		235.56	

Cu.m Transport Cost on KM Distance involving Small Quantities

Cost of Transport from 0.5 km up to 1 km per cu.m (T1-003) 409.65

Rate for each subsequent km from 1 km up to 8th km (T1-003A) 63.70

Rate for each subsequent km beyond 8th km (T1-003B) 42.80

Distance/km	Cost/Cu.m/Trip Rs.	Distance/km	Cost/Cu.m/Trip Rs.
0.5 up to 1	409.65	43	2,353.55
2	473.35	44	2,396.35
3	537.05	45	2,439.15
4	600.75	46	2,481.95
5	664.45	47	2,524.75
6	728.15	48	2,567.55
7	791.85	49	2,610.35
8	855.55	50	2,653.15
9	898.35	51	2,695.95
10	941.15	52	2,738.75
11	983.95	54	2,824.35
12	1,026.75	56	2,909.95
13	1,069.55	58	2,995.55
14	1,112.35	60	3,081.15
15	1,155.15	62	3,166.75
16	1,197.95	64	3,252.35
17	1,240.75	66.	3,337.95
18	1,283.55	68	3,423.55
19	1,326.35	70	3,509.15
20	1,369.15	72	3,594.75
21	1,411.95	374	3,680.35
22	1,454.75	76	3,765.95
23	1,497.55	78	3,851.55
24	1,540.35	80	3,937.15
25	1,583.15	82	4,022.75
26	1,625.95	84	4,108.35
27	1,668.75	86	4,193.95
28	1,711.55	88	4,279.55
29	1,754.35	90	4,365.15
30	1,797.15	92	4,450.75
31	1,839.95	94	4,536.35
32	1,882.75	96	4,621.95
33	1,925.55	98	4,707.55
34	1,968.35	100	4,793.15
35	2,011.15	102	4,878.75
36	2,053.95	104	4,964.35
37	2,096.75	106	5,049.95
38	2,139.55	108	5,135.55
39	2,182.35	110	5,221.15
40	2,225.15	112	5,306.75
41	2,267.95	114	5,392.35
42	2,310.75	116	5,477.95

Transport and Paving of Interlocking Blocks-2025

1.	Transport of Interlocking Concrete Paving Block per km transport (short distance - within the province)					
	Transport cost (Rs.)	.=	0.23	per Block/ km		
2.	Paving of Interlocking Concrete Bloc inclusive 50 mm sand bedding and c		and			

transport of Blocks and bedding material to be paid separately. (Depending on the design, Construction of side kerbs and ABC layer and sub grade preparation to be paid separately.)

